

Capalac Basic SM weiß



technical data

Specific use(s)	Decorative protective coating
Density	1,32 g/cm ³
gloss level	silky matt (in accordance with DIN EN 53778)

Components

product code/GISCODE	M-LL01
preservatives	not contained
VOC content in accordance with Directive 2004/42/EC	< 23 % < 310 g/l
VOC-indhold LEED [less water]	310 g/l
lead, cadmium, chromium VI * (* not contained in the formulation)	not contained

environmental labels

building certifications

suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

No.	application site	product type	QS 1	QS 2	QS 3	QS 4
		varnishes/glazes	no	no	no	no
14a	Non-load-bearing metal components such as banisters, metal substructures, frames, steel doors, façade elements, etc.	corrosion protection coatings	no	no	no	no
14b	Non-load-bearing metal components such as banisters, metal substructures, frames, steel doors, façade elements, etc. (metallic effect varnishes)	Effect coatings (e.g. metallic effect varnishes)	no	no	no	no
26	components made of aluminium and stainless steel on the façade: cladding	products for surface coating of metal	yes	yes	yes	yes
27	Factory-coated components, e.g. façade elements, doors, radiators, etc. Galvanising is not considered coating under this criterion.	primer and top coating (e.g. paints, varnishes)	yes	yes	yes	yes

Suitability for use in accordance with LEED	category (IEQ4.2 - 2009)	pigmented lacquer
	VOC limit below limit	550 g/l yes
recycling share	not contained	
production location	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt	