

DisboSEAL 225 Weiß



Technical data

Specific use(s)	Sealant
Density	1,60 g/cm ³

Components

Product Code/GISCODE	RS10
Preservation agents	contained
VOC content in accordance with Directive 2004/42/EC	< 1 %
VOC content LEED [less water]	< 20 g/l
Lead, cadmium, chromium VI *	50 g/l
Hexabromcyclododecane (HBCD)	not contained
SVHC >0,1% - Substances of Very High Concern	not contained
HC plasticisers (* not contained in the formulation)	not contained

Environmental labels

Complies with EMICODE	EC1 plus
-----------------------	----------

Building certifications - DGNB

Suitable according to DGNB criteria ENV1.2 (System version 2018 and 2015)

No.	Application site	Product Type	Considered substances / aspects	QS 1	QS 2	QS 3	QS 4
12	Adhesive bondson small joints undermechanical stress; theareas of glass construction,façade and firesafety are not taken intoaccount here	Sealing compounds,sealants and adhesivesfor attaching componentsin points and lines in the interior and attaching ventilation ducts inside the building. This refers to Acrylic sealants/adhesives, silicone sealants and SMP (hybrid sealants	Chlorinatedparaffins, solvents,HC	Ja	Ja	Ja	Ja
13	Installation adhesives and sealants on thefaçade, windows andexternal doors (applied on the construction site)	Adhesive forestablishing airtightnesson the internal and external façade: e.g. PU, PU hybrid, MS polymer, SMP, etc.	Halogenatedpropellants,chlorinatedparaffins andemissions	Ja	Ja	Ja	Ja

Building certifications - LEED

LEED v.4 (EQ CREDIT: Low emitting materials)	fulfilled
LEED 2009 (IEQ4.1/ IEQ4.2/ IEQ4.3)	fulfilled
Product category	Sealants (other)
VOC limit	420 g/l
Limit fulfilled	yes
AgBB approval	passed
Formaldehyde limit <10µg/m ³ (28d)	fulfilled
Recycling share	not contained
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt

Building certifications - Assessment System NaWoh