according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 14.06.2023 6007987 Date of first issue: 15.11.2019 2.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name DisboPUR 924 PHS Comp. B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-Polyurethane-resin-based coating material, solvent-containing

stance/Mixture

Recommended restrictions

on use

within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Disbon GmbH

> Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone +496154710 Telefax +4961547170222

Website

E-mail address Responsi-

ble/issuing person

msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapor.

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single ex-

posure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

Specific target organ toxicity - single ex-

posure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Long-term (chronic) aquatic hazard, Cat-

H411: Toxic to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 2.1 14.06.2023 6007987 Date of first issue: 15.11.2019

egory 2

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin

dryness or cracking.

Precautionary Statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.
P262 Do not get in eyes, on skin, or on clothing.
P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Additional Labeling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 2.1 14.06.2023 6007987 Date of first issue: 15.11.2019

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Polyisocyanate

Components

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate,	CAS-No. EC-No. Index-No. Registration number 53880-05-0 500-125-5	Classification Skin Sens. 1; H317 STOT SE 3; H335	Concentration (% w/w) >= 50 - < 70
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	01-2119488734-24 64742-95-6 265-199-0 649-356-00-4 01-2119455851-35, 01-2119486773-24	(No specific target organs noted) STOT SE 3; H336 STOT SE 3; H335 Aquatic Chronic 2; H411 Asp. Tox. 1; H304 Flam. Liq. 3; H226 EUH066	>= 30 - < 50
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 615-008-00-5 01-2119490408-31	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Chronic 2; H411 Acute Tox. 3; H331 ———————————————————————————————————	>= 0,25 - < 0,5

according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 2.1 14.06.2023 6007987 Date of first issue: 15.11.2019

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Show this material safety data sheet to the doctor in attend-

ance

When symptoms persist or in all cases of doubt seek medical

advice.

Move out of dangerous area. First aider needs to protect himself.

Never give anything by mouth to an unconscious person.

If inhaled : Call a physician.

If breathing is irregular or stopped, administer artificial respira-

tion.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

Move to fresh air.

In case of skin contact : Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

Take off all contaminated clothing immediately.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

If accidentally swallowed obtain immediate medical attention.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.

May cause respiratory irritation. May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 2.1 14.06.2023 6007987 Date of first issue: 15.11.2019

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

Water

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

Cool closed containers exposed to fire with water spray. In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Standard procedure for chemical fires.

In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 2.1 14.06.2023 6007987 Date of first issue: 15.11.2019

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent

material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Avoid exceeding the given occupational exposure limits (see

section 8).

Provide sufficient air exchange and/or exhaust in work rooms. Contains isocyanates. Please, attend to producer's advice. Liquid product may irritate and sensitize skin and respiratory tract and may cause allergic reaction. Do not inhale vapours. Take care for sufficient fresh air supply during and after use. Product must not be sprayed. Allergics or persons tending to respiratory tract diseases must not be involved in operations

with this product.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Advice on protection against

fire and explosion

Vapors may form explosive mixtures with air. Vapors are heavier than air and may spread along floors. Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Hygiene measures : Keep working clothes separately. Remove and wash contami-

nated clothing before re-use. Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering

eating areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 3

according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 2.1 14.06.2023 6007987 Date of first issue: 15.11.2019

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
3-	4098-71-9	AGW	0,005 ppm	TRGS 430
isocyanatomethyl-			0,046 mg/m3	
3,5,5-			, 3	
trimethylcyclohexyl				
isocyanate				
	Peak-limit category: 1;=2=(I)			
	Further information: In well-founded cases also a momentary value can be			
	established, that never can be exceeded. This substance will be indicated by			
	= = in combination with an exceeding value., airway sensitizing substance			
		AGW (Vapour	0,005 ppm	DE TRGS
		and aerosols)	0,046 mg/m3	900
	Peak-limit category: 1;=2=(I)			
	Further information: In well-found cases also a momentary value can be es-			
	tablished, that never can be exceeded. This substance will be indicated by = =			
	in combination with an exceeding value., Substance sensitizing through the			
	respiratory system			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

	` '	5 5	` '	
Substance name	End Use	Routes of exposure	Potential health effects	Value
3-isocyanatomethyl- 3,5,5- trimethylcyclohexyl isocyanate	Workers	Inhalation	Acute local effects	0,05 mg/m3
	Workers	Inhalation	Long-term local ef- fects	0,05 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
3-isocyanatomethyl-3,5,5-	Sea water	0,006 mg/l
trimethylcyclohexyl isocyanate		
	Fresh water	0,06 mg/l
	Sewage treatment plant	10,6 mg/l
	Fresh water sediment	218,92 mg/kg dry
		weight (d.w.)
	Intermittent use/release	0,04 mg/l

according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 2.1 14.06.2023 6007987 Date of first issue: 15.11.2019

	Soil	44,01 mg/kg dry weight (d.w.)
	Sea sediment	21,89 mg/kg dry
		weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : butyl-rubber
Glove thickness : 0,3 mm
Protective index : Class 3
Wearing time : 30 min

Remarks : Gloves should be discarded and replaced if there is any indi-

cation of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suita-

ble gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes

Long sleeved clothing

Remove and wash contaminated clothing before re-use. Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, dis-

posable suits) to avoid exposed skin surfaces.

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Respiratory protection : When exceeding the WEL substance Limit a respiratory filter

Type A is necessary. Class 1 or 2 has to be chosen depend-

ing on the workplace concentration.

Do not use for spraying.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 2.1 14.06.2023 6007987 Date of first issue: 15.11.2019

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : yellow

Odor : No data available

Odor Threshold : Not relevant

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Upper explosion limit / Upper

flammability limit

7 %(V)

Lower explosion limit / Lower :

flammability limit

0,8 %(V)

Flash point : ca. 45 °C

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 6,95

Concentration: 10 %

Viscosity

Viscosity, dynamic : ca. 2,000 mPa.s (23 °C)

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: not determined

Vapor pressure : 4,9996 hPa

Relative density : not determined

Density : ca. 1,05 g/cm3

Relative vapor density : Heavier than air.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 2.1 14.06.2023 6007987 Date of first issue: 15.11.2019

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : Sustains combustion

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Amines and alcohols cause exothermic reactions.

Mixture reacts slowly with water resulting in evolution of CO2.

10.4 Conditions to avoid

Conditions to avoid : Exposure to water vapor.

Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Amines

Incompatible with oxidizing agents. Incompatible with acids and bases.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 2.1 14.06.2023 6007987 Date of first issue: 15.11.2019

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

No data available

according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 2.1 14.06.2023 6007987 Date of first issue: 15.11.2019

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Uncured product residues and unpurified packaging should be

disposed of as hazardous waste.

Waste should not be disposed of via wastewater.

Material residues: Allow the basic substance to harden with

hardener and dispose of as paint waste.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080111*, waste paint and varnish containing organic solvents

or other dangerous substances

according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 2.1 14.06.2023 6007987 Date of first issue: 15.11.2019

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT

(Solvent naphtha (petroleum), light arom.; Low boiling point

naphtha -unspecified)

IATA : Paint

14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 2.1 14.06.2023 6007987 Date of first issue: 15.11.2019

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen: 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Regulation (EC) No. 1907/2006



DE / EN

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 14.06.2023 6007987 Date of first issue: 15.11.2019 2.1

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

3-isocyanatomethyl-3,5,5trimethylcyclohexyl isocyanate

(Number on list 74)

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener-

ated.

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

None

E2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

ENVIRONMENTAL HAZARDS

P5c FLAMMABLE LIQUIDS

34 Petroleum products: (a) gasolines

> and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a)

to (d)

Water hazard class (Germa- : WGK 3 highly water endangering

ny)

according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 2.1 14.06.2023 6007987 Date of first issue: 15.11.2019

Product code for laquers and

paints / Giscode

: PU50 PU systems, containing solvents, harmful, sensitising

: PU50 PU systems, containing solvents, harmful, sensitising

Volatile organic compounds : < 30 %

< 320 g/l

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapor.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.

H319 : Causes serious eye irritation.

H331 : Toxic if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H335 : May cause respiratory irritation. H336 : May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Resp. Sens. : Respiratory sensitization

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

STOT SE : Specific target organ toxicity - single exposure

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 430 : Germany. TRGS 430 - Isocyanates

DE TRGS 900 / AGW : Time Weighted Average TRGS 430 / AGW : Occupational Exposure Limit

according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 2.1 14.06.2023 6007987 Date of first issue: 15.11.2019

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AlIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; (EQD, to 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EMS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Convention; ICCO - Lethal Concentration; ICCO - Lethal Concentration; ICCO - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adv

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Expo-

sure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture:

Flam. Liq. 3	H226	Based on product data or assessment
Skin Sens. 1	H317	Calculation method
STOT SE 3	H336	Calculation method
STOT SE 3	H335	Calculation method
Aquatic Chronic 2	H411	Calculation method

Classification procedure:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guid-

according to Regulation (EC) No. 1907/2006



DE / EN

DisboPUR 924 PHS Comp. B

Version Revision Date: SDS Number: Date of last issue: 14.06.2023 2.1 14.06.2023 6007987 Date of first issue: 15.11.2019

ance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN