

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version	Revision Date:	SDS Number:	Date of last issue: 05.01.2023
5.1	05.01.2023	6000545	Date of first issue: 05.01.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Capatect AmphiSilan Fassadenputz K20 SPR

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Water-borne coatings

Recommended restrictions : within adequate application - none  
on use

#### 1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH  
Roßdörfer Straße 50  
64372 Ober-Ramstadt

Telephone : +496154710  
Telefax : +4961547170222

E-mail address Responsible/issuing person : msds@dr-rmi.com

#### 1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3 : H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labeling (REGULATION (EC) No 1272/2008)

Hazard Statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read carefully and follow all instructions.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version 5.1      Revision Date: 05.01.2023      SDS Number: 6000545      Date of last issue: 05.01.2023  
Date of first issue: 05.01.2023

		Aquatic Chronic 2; H411 Acute Tox. 2; H330 <hr/> M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 <hr/> specific concentration limit Skin Sens. 1; H317 >= 0,05 %	
Pyridine-2-thiol 1-oxide, sodium salt	3811-73-2 223-296-5 613-344-00-7 01-2119493385-28	Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 3; H311 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT RE 1; H372 (Nervous system) Aquatic Acute 1; H400 Aquatic Chronic 2; H411 EUH070 <hr/> M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 1 <hr/> Acute toxicity estimate  Acute oral toxicity: 500 mg/kg Acute inhalation toxicity (dust/mist): 0,5 mg/l Acute dermal toxicity: 790 mg/kg	>= 0,0025 - < 0,025
octhilonone (ISO)	26530-20-1 247-761-7 613-112-00-5 01-2120768921-45	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1; H314	>= 0,0025 - < 0,025

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version 5.1      Revision Date: 05.01.2023      SDS Number: 6000545      Date of last issue: 05.01.2023  
Date of first issue: 05.01.2023

		<p>Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071</p> <hr/> <p>M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100</p> <hr/> <p>specific concentration limit Skin Sens. 1A; H317 &gt;= 0,0015 %</p> <hr/> <p>Acute toxicity estimate</p> <p>Acute oral toxicity: 125 mg/kg Acute inhalation toxicity (dust/mist): 0,27 mg/l Acute dermal toxicity: 311 mg/kg</p>	
terbutryn	886-50-0 212-950-5	<p>Acute Tox. 4; H302 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Skin Sens. 1; H317</p> <hr/> <p>M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100</p> <hr/> <p>specific concentration limit Skin Sens. 1; H317 &gt;= 3 %</p>	>= 0,0025 - < 0,025
reaction mass of 5-chloro-2-	55965-84-9	Acute Tox. 3; H301	>= 0,0002 - <

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version 5.1      Revision Date: 05.01.2023      SDS Number: 6000545      Date of last issue: 05.01.2023  
Date of first issue: 05.01.2023

methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	613-167-00-5 01-2120764691-48	Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	0,0015
M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100			
specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %			
Substances with a workplace exposure limit :			
Kieselguhr, soda ash flux-calcined	68855-54-9 272-489-0 21-2119488518-22		>= 1 - < 10
aluminium hydroxide	21645-51-2 244-492-7 01-2119529246-39		>= 1 - < 10

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.  
If you feel unwell, seek medical advice (show the label where possible).  
Move out of dangerous area.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version	Revision Date:	SDS Number:	Date of last issue: 05.01.2023
5.1	05.01.2023	6000545	Date of first issue: 05.01.2023

First aider needs to protect himself.

- |                         |   |   |
|-------------------------|---|---|
| If inhaled              | : | Move to fresh air.  |
| In case of skin contact | : | Take off all contaminated clothing immediately.<br>Do NOT use solvents or thinners.<br>In case of contact, immediately flush skin with soap and plenty of water.                                  |
| In case of eye contact  | : | If eye irritation persists: Get medical advice/ attention.<br>IF IN EYES: Rinse cautiously with water for several minutes.<br>Remove contact lenses, if present and easy to do. Continue rinsing. |
| If swallowed            | : | Seek medical advice.<br>Clean mouth with water and drink afterwards plenty of water.<br>If swallowed, DO NOT induce vomiting.   |

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- |                                |   |   |
|--------------------------------|---|---|
| Suitable extinguishing media   | : | Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.<br>Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.<br>Do not use a solid water stream as it may scatter and spread fire. |
| Unsuitable extinguishing media | : | None known.   |

### 5.2 Special hazards arising from the substance or mixture

- |                                       |   |   |
|---------------------------------------|---|---|
| Specific hazards during fire fighting | : | In case of fire hazardous decomposition products may be produced such as:<br>Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). |
|---------------------------------------|---|---|

### 5.3 Advice for firefighters

- |  |   |  |
|--|---|--|
| Special protective equipment for fire-fighters | : | Wear self-contained breathing apparatus for firefighting if necessary. |
|--|---|--|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version	Revision Date:	SDS Number:	Date of last issue: 05.01.2023
5.1	05.01.2023	6000545	Date of first issue: 05.01.2023

Further information : Use water spray to cool unopened containers.  
Standard procedure for chemical fires.  
The product itself does not burn.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole.  
Material can create slippery conditions.  
Do not get in eyes, on skin, or on clothing.

#### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Do not flush into surface water or sanitary sewer system.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

#### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Use only with adequate ventilation.  
For personal protection see section 8.  
No special technical protective measures required.

No interior use.

In addition, the current technical information for this product and its application on [www.caparol.com](http://www.caparol.com) must be observed.

Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version 5.1      Revision Date: 05.01.2023      SDS Number: 6000545      Date of last issue: 05.01.2023  
Date of first issue: 05.01.2023

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

Storage class (TRGS 510) : 12

### 7.3 Specific end use(s)

Specific use(s) : This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Kieselguhr, soda ash flux-calcined	68855-54-9	AGW (Alveolate fraction)	0,3 mg/m <sup>3</sup>	DE TRGS 900
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
aluminium hydroxide	21645-51-2	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	AGW (Inhalable fraction)	10 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version 5.1      Revision Date: 05.01.2023      SDS Number: 6000545      Date of last issue: 05.01.2023  
Date of first issue: 05.01.2023

	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		BM (Alveolar dust fraction)	0,5 mg/m <sup>3</sup>	DE TRGS 527
Pyridine-2-thiol 1-oxide, sodium salt	3811-73-2	AGW (Inhalable fraction)	0,2 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
octhilonone (ISO)	26530-20-1	AGW (Inhalable fraction)	0,05 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(I)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
calcium carbonate	Consumers	Ingestion	Long-term systemic effects	6,10 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	10,00 mg/m <sup>3</sup>
	Consumers	Ingestion	Acute systemic effects	6,10 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	10,00 mg/m <sup>3</sup>
Kieselguhr, soda ash flux-calcined	Consumers	Ingestion	Long-term systemic effects	18,70 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,05 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	0,05 mg/m <sup>3</sup>
aluminium hydroxide	Consumers	Ingestion	Long-term systemic effects	4,74 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	10,76 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	10,76 mg/m <sup>3</sup>
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	10,00 mg/m <sup>3</sup>
Fatty acids, C16-18, zinc salts	Consumers	Ingestion	Long-term systemic effects	8,30 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic	833,00 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version 5.1      Revision Date: 05.01.2023      SDS Number: 6000545      Date of last issue: 05.01.2023  
Date of first issue: 05.01.2023

			effects	bw/day
	Consumers	Inhalation	Long-term systemic effects	25,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	50,00 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	830,00 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
calcium carbonate	Sewage treatment plant	100 mg/l
Kieselguhr, soda ash flux-calcined	Sewage treatment plant	100 mg/l
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sea sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l
glass, oxide, chemicals	Fresh water sediment	174 mg/kg dry weight (d.w.)
	Secondary Poisoning	10,9 mg/kg food
	Sea water	3,4 $\mu\text{g/l}$
	Sewage treatment plant	100 $\mu\text{g/l}$
	Sea sediment	164 mg/kg dry weight (d.w.)
	Soil	147 mg/kg dry weight (d.w.)
	Fresh water	6,5 $\mu\text{g/l}$
Fatty acids, C16-18, zinc salts	Soil	35,6 mg/kg dry weight (d.w.)
	Fresh water	20,6 $\mu\text{g/l}$
	Sea sediment	56,5 mg/kg dry weight (d.w.)
	Sewage treatment plant	52 $\mu\text{g/l}$
	Fresh water sediment	117,8 mg/kg dry weight (d.w.)
	Sea water	6,1 $\mu\text{g/l}$

## 8.2 Exposure controls

### Personal protective equipment

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version	Revision Date:	SDS Number:	Date of last issue: 05.01.2023
5.1	05.01.2023	6000545	Date of first issue: 05.01.2023

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection  
Goggles

Hand protection  
Material : Nitrile rubber  
Glove thickness : 0,2 mm  
Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.  
Wear suitable gloves tested to EN374.  
DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes  
Long sleeved clothing  
  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
  
Skin should be washed after contact.  
  
During spray application: impervious clothing

Respiratory protection : No personal respiratory protective equipment normally required.  
  
DGUV Regulation 112-190 - Use of breathing equipment  
  
During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Color : No data available  
Odor : No data available  
Melting point/freezing point : ca. 0 °C  
Boiling point/boiling range : ca. 100 °C  
Upper explosion limit / Upper flammability limit : not determined

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version	Revision Date:	SDS Number:	Date of last issue: 05.01.2023
5.1	05.01.2023	6000545	Date of first issue: 05.01.2023

Lower explosion limit / Lower flammability limit	:	not determined
Flash point	:	Not applicable
Autoignition temperature	:	not determined
Decomposition temperature	:	Not applicable
pH	:	8 - 9 Concentration: 100 %
Viscosity Viscosity, dynamic	:	No data available
Solubility(ies) Water solubility	:	completely miscible
Partition coefficient: n-octanol/water	:	not determined
Vapor pressure	:	ca. 23,4 hPa (20 °C)
Density	:	1,8000 g/cm <sup>3</sup>
Relative vapor density	:	not determined

### 9.2 Other information

Explosives	:	Not applicable
Oxidizing properties	:	Not applicable
Flammability (liquids)	:	The product is not flammable.
Evaporation rate	:	Not applicable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version	Revision Date:	SDS Number:	Date of last issue: 05.01.2023
5.1	05.01.2023	6000545	Date of first issue: 05.01.2023

### 10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.  
Incompatible with oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **1,2-benzisothiazol-3(2H)-one:**

Acute oral toxicity : LD50 (Rat): 532 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

##### **Pyridine-2-thiol 1-oxide, sodium salt:**

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,5 mg/l  
Test atmosphere: dust/mist  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Acute dermal toxicity : Acute toxicity estimate: 790 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

##### **octhilinone (ISO):**

Acute oral toxicity : Acute toxicity estimate: 125 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version	Revision Date:	SDS Number:	Date of last issue: 05.01.2023
5.1	05.01.2023	6000545	Date of first issue: 05.01.2023

Acute inhalation toxicity : Acute toxicity estimate: 0,27 mg/l  
Test atmosphere: dust/mist  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Acute dermal toxicity : Acute toxicity estimate: 311 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

### terbutryn:

Acute oral toxicity : LD50 Oral (Rat): > 300 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Acute oral toxicity : LD50 (Rat): 66 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg  
Method: OECD Test Guideline 402

### Skin corrosion/irritation

Not classified based on available information.

### Serious eye damage/eye irritation

Not classified based on available information.

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

### Product:

Remarks : Not skin sensitising on the basis of the results of similar tested mixtures, applying bridging principles in accordance with CLP Regulation Article 9(4). Result of studies: Sensitization OECD 429 (LLNA) (mouse) not sensitizing

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version	Revision Date:	SDS Number:	Date of last issue: 05.01.2023
5.1	05.01.2023	6000545	Date of first issue: 05.01.2023

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### STOT-single exposure

Not classified based on available information.

### STOT-repeated exposure

Not classified based on available information.

### Aspiration toxicity

Not classified based on available information.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### **1,2-benzisothiazol-3(2H)-one:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia): 3,27 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l  
plants : Exposure time: 72 h  
Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox- : 1  
icity)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version	Revision Date:	SDS Number:	Date of last issue: 05.01.2023
5.1	05.01.2023	6000545	Date of first issue: 05.01.2023

M-Factor (Chronic aquatic toxicity) : 1

### **Pyridine-2-thiol 1-oxide, sodium salt:**

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 1

### **octhilinone (ISO):**

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

### **terbutryn:**

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

## 12.2 Persistence and degradability

No data available

## 12.3 Bioaccumulative potential

### Components:

#### **Pyridine-2-thiol 1-oxide, sodium salt:**

Partition coefficient: n-octanol/water : Pow: 0,002 (20 °C)

#### **octhilinone (ISO):**

Partition coefficient: n-octanol/water : log Pow: 2,92





# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version 5.1      Revision Date: 05.01.2023      SDS Number: 6000545      Date of last issue: 05.01.2023  
Date of first issue: 05.01.2023

cling.

Waste Code : used product  
080112, waste paint and varnish other than those mentioned  
in 08 01 11\*

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.4 Packing group

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA (Cargo) : Not regulated as a dangerous good  
IATA (Passenger) : Not regulated as a dangerous good

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version	Revision Date:	SDS Number:	Date of last issue: 05.01.2023
5.1	05.01.2023	6000545	Date of first issue: 05.01.2023

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : Not applicable

Water hazard class (Germany) : WGK 1 slightly water endangering  
Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and paints / Giscode : M-SF01F Water-based, silicone resin paints, active agents

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version	Revision Date:	SDS Number:	Date of last issue: 05.01.2023
5.1	05.01.2023	6000545	Date of first issue: 05.01.2023

. : BSW50 Coating materials, water-based, containing solvents, film-protected

Volatile organic compounds : Directive 2004/42/EC  
< 1 %  
< 10 g/l

### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

## SECTION 16: Other information

### Full text of H-Statements

H301 : Toxic if swallowed.  
H302 : Harmful if swallowed.  
H310 : Fatal in contact with skin.  
H311 : Toxic in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H330 : Fatal if inhaled.  
H331 : Toxic if inhaled.  
H351 : Suspected of causing cancer if inhaled.  
H372 : Causes damage to organs through prolonged or repeated exposure.

H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.  
EUH070 : Toxic by eye contact.  
EUH071 : Corrosive to the respiratory tract.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Carc. : Carcinogenicity  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitization  
STOT RE : Specific target organ toxicity - repeated exposure  
DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
DE TRGS 527 / BM : Assessment scale  
DE TRGS 900 / AGW : Time Weighted Average

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version	Revision Date:	SDS Number:	Date of last issue: 05.01.2023
5.1	05.01.2023	6000545	Date of first issue: 05.01.2023

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

### Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs.

Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,

Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

### Classification of the mixture:

Aquatic Chronic 3

H412

### Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capatect AmphiSilan Fassadenputz K20 SPR

Version	Revision Date:	SDS Number:	Date of last issue: 05.01.2023
5.1	05.01.2023	6000545	Date of first issue: 05.01.2023

---

### REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our up-stream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN