

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : DisboADD 901

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Polyurethane-resin-based coating material, solvent-containing

Recommended restrictions on use : within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Disbon GmbH
Roßdörfer Straße 50
64372 Ober-Ramstadt

Telephone : +496154710
Telefax : +4961547170222
E-mail address Responsible/issuing person : msds@dr-rmi.com

1.4 Emergency telephone number

Emergency telephone number 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Acute toxicity, Category 4	H312: Harmful in contact with skin.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

Specific target organ toxicity - repeated exposure, Category 2


H373: May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 + H332 Harmful in contact with skin or if inhaled. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe vapours/ spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P331 Do NOT induce vomiting.

Hazardous components which must be listed on the label:

xylene
Hexamethylene diisocyanate, oligomers
dibutyltin dilaurate
hexamethylene-di-isocyanate

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Asp. Tox. 1; H304 STOT RE 2; H373	>= 70 - < 90
Hexamethylene diisocyanate, oligomers	28182-81-2 500-060-2 01-2119485796-17	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335	>= 10 - < 20
ethylbenzene	100-41-4 202-849-4 601-023-00-4 01-2119489370-35	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 Asp. Tox. 1; H304	>= 1 - < 10
dibutyltin dilaurate	77-58-7 201-039-8 050-030-00-3 01-2119496068-27, 01-2119557828-21	Muta. 2; H341 Repr. 1B; H360FD STOT SE 1; H370 STOT RE 1; H372 Skin Corr. 1C; H314 Eye Irrit. 2; H319 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Skin Sens. 1; H317	>= 0,1 - < 0,25
hexamethylene-di-isocyanate	822-06-0 212-485-8 615-011-00-1 01-2119457571-37	Acute Tox. 4; H302 Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	< 0,1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Show this safety data sheet to the doctor in attendance.
When symptoms persist or in all cases of doubt seek medical advice.
Move out of dangerous area.
First aider needs to protect himself.
Never give anything by mouth to an unconscious person.
- If inhaled : Call a physician.
If breathing is irregular or stopped, administer artificial respiration.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
Move to fresh air.
- In case of skin contact : Do NOT use solvents or thinners.
In case of contact, immediately flush skin with soap and plenty of water.
Take off all contaminated clothing immediately.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
If accidentally swallowed obtain immediate medical attention.
If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

cumstances and the surrounding environment.

Foam

Carbon dioxide (CO₂)

Unsuitable extinguishing media : Water

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Cool closed containers exposed to fire with water spray. In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Standard procedure for chemical fires. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

,For personal protection see section 8.,For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : For personal protection see section 8.
Avoid exceeding the given occupational exposure limits (see section 8).
Provide sufficient air exchange and/or exhaust in work rooms.
Contains isocyanates. Please, attend to producer's advice.
Liquid product may irritate and sensitize skin and respiratory tract and may cause allergic reaction. Do not inhale vapours.
Take care for sufficient fresh air supply during and after use.
Product must not be sprayed. Allergics or persons tending to respiratory tract diseases must not be involved in operations with this product.
- In addition, the current technical information for this product and its application on www.caparol.com must be observed.
- Advice on protection against fire and explosion : Vapours may form explosive mixtures with air. Vapours are heavier than air and may spread along floors. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Hygiene measures : Keep working clothes separately. Remove and wash contaminated clothing before re-use. Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in original container. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Storage class (TRGS 510) : 3, Flammable liquids

7.3 Specific end use(s)

- Specific use(s) : This information is not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version 2.0 Revision Date: 24.11.2020 Print Date 03.12.2020 Date of last issue: 21.11.2019
Date of first issue: 21.11.2019

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		AGW	100 ppm 440 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Skin absorption, European Union (The EU has established a limit value: deviations in value and peak limit are possible), Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		STEL	200 ppm 884 mg/m ³	2000/39/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		AGW	20 ppm 88 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Skin absorption, European Union (The EU has established a limit value: deviations in value and peak limit are possible), Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
dibutyltin dilaurate	77-58-7	AGW (Vapour and aerosols)	0,0018 ppm 0,009 mg/m ³ (Tin)	DE TRGS 900
	Peak-limit: excursion factor (category): 1;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, harm to the unborn child can not be excluded, Skin absorption, Sum of vapor and aerosols., The threshold value is based on the element content of the corresponding metal., Commission for dangerous substances			
hexamethylene-diisocyanate	822-06-0	AGW	0,005 ppm 0,035 mg/m ³	TRGS 430

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version 2.0 Revision Date: 24.11.2020 Print Date 03.12.2020 Date of last issue: 21.11.2019
Date of first issue: 21.11.2019

	Peak-limit: excursion factor (category): 1;=2=(l)		
	Further information: Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., airway sensitizing substance, The exposure limit is established for monomers. For regulatory details on oligomers and polymers see TRGS 430 'Isocyanate'.		
	AGW (Vapour and aerosols)	0,005 ppm 0,035 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 1;=2=(l)		
	Further information: Substance sensitizing through the respiratory system, The exposure limit is established for monomers. For regulatory details on oligomers and polymers see TRGS 430 'Isocyanate'. , Sum of vapor and aerosols., Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).		

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	xylene: 1,5 mg/l (Blood)	Immediately after exposure or after working hours	TRGS 903
		methylhippuric acid (all isomers): 2 g/l (Urine)	Immediately after exposure or after working hours	TRGS 903
ethylbenzene	100-41-4	mandelic acid + phenylglyoxylic acid: 250 mg/g Creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903
hexamethylene-di-isocyanate	822-06-0	hexamethylenedia-mine: 15 µg/g cre-atinine (Urine)	Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
xylene	Consumers	Inhalation	Acute local effects	174,00 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	108,00 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	174,00 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	1,60 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	14,80 mg/m ³
	Workers	Inhalation	Acute systemic effects	289,00 mg/m ³
	Workers	Inhalation	Acute local effects	289,00 mg/m ³
	Workers	Inhalation	Long-term systemic effects	77,00 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version 2.0 Revision Date: 24.11.2020 Print Date 03.12.2020 Date of last issue: 21.11.2019
Date of first issue: 21.11.2019

	Workers	Skin contact	Long-term systemic effects	180,00 mg/kg bw/day
ethylbenzene	Consumers	Ingestion	Long-term systemic effects	1,60 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	15,00 mg/m ³
	Workers	Inhalation	Acute systemic effects	884,00 mg/m ³
	Workers	Inhalation	Acute local effects	293,00 mg/m ³
	Workers	Inhalation	Acute local effects	884,00 mg/m ³
	Workers	Inhalation	Long-term systemic effects	77,00 mg/m ³
	Workers	Inhalation	Long-term systemic effects	442,00 mg/m ³
	Workers	Inhalation	Long-term local effects	442,00 mg/m ³
	Workers	Skin contact	Long-term systemic effects	180,00 mg/kg bw/day
dibutyltin dilaurate	Consumers	Ingestion	Acute systemic effects	0,02 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,00 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	0,16 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,01 mg/m ³
	Consumers	Inhalation	Acute systemic effects	0,04 mg/m ³
	Consumers	Skin contact	Acute systemic effects	1,00 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	0,02 mg/m ³
	Workers	Skin contact	Acute systemic effects	2,08 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	0,42 mg/kg bw/day
hexamethylene-diisocyanate	Workers	Inhalation	Acute systemic effects	0,07 mg/m ³
	Workers	Inhalation	Acute local effects	0,07 mg/m ³
	Workers	Inhalation	Long-term systemic effects	0,04 mg/m ³
	Workers	Inhalation	Long-term local effects	0,04 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
xylene	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Soil	2,31 mg/kg dry

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version 2.0 Revision Date: 24.11.2020 Print Date 03.12.2020 Date of last issue: 21.11.2019
Date of first issue: 21.11.2019

		weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Marine water	0,327 mg/l
	Marine sediment	12,46 mg/kg dry weight (d.w.)
ethylbenzene	Intermittent use/release	0,1 mg/l
	Sewage treatment plant	9,6 mg/l
	Fresh water	0,1 mg/l
	Marine water	0,01 mg/l
	Fresh water sediment	13,7 mg/kg dry weight (d.w.)
	Soil	2,68 mg/kg dry weight (d.w.)
	Marine sediment	1,37 mg/kg dry weight (d.w.)
	Secondary Poisoning	0,02 g/kg food
	Marine water	0,1 mg/l
dibutyltin dilaurate	Sewage treatment plant	100 mg/l
	Fresh water	0,000463 mg/l
	Intermittent use/release	0,00463 mg/l
	Marine water	0,000046 mg/l
	Secondary Poisoning	0,2 mg/kg food
hexamethylene-di-isocyanate	Intermittent use/release	0,774 mg/l
	Fresh water	0,0774 mg/l
	Marine sediment	0,001344 mg/kg dry weight (d.w.)
	Fresh water sediment	0,01334 mg/kg dry weight (d.w.)
	Soil	0,0026 mg/kg dry weight (d.w.)
	Marine water	0,00774 mg/l
	Sewage treatment plant	8,42 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : German trade association rules - BGR 192 Eye protection
Tightly fitting safety goggles

Hand protection

Material : butyl-rubber
Glove thickness : 0,3 mm
Protective index : Class 3
Wearing time : 30 min

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

- Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374.
German trade association leaflet: Carry gloves (ZH 1/706)
- Skin and body protection : Safety shoes
Long sleeved clothing
Remove and wash contaminated clothing before re-use.
Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.
- Respiratory protection : When exceeding the WEL substance Limit a respiratory filter Type A is necessary. Class 1 or 2 has to be chosen depending on the workplace concentration.
Do not use for spraying.

German trade association rules - BGR 190 Breathing protection

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : transparent
- Odour : No data available
- Odour Threshold : Not relevant
- pH : 6,95
Concentration: 10 %
- Melting point/freezing point : not determined
- Boiling point/boiling range : 137 - 143 °C
- Flash point : 24 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

Evaporation rate : Not applicable

Upper explosion limit / Upper flammability limit : 8 %(V)

Lower explosion limit / Lower flammability limit : 1 %(V)

Vapour pressure : 6,4 hPa

Relative vapour density : not determined

Relative density : not determined

Density : 0,94 g/cm³

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : not determined

Auto-ignition temperature : not determined

Decomposition temperature : Not applicable

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm²/s (40 °C)

Explosive properties : Not applicable

Oxidizing properties : Not applicable

9.2 Other information

Flammability (liquids) : The product is not flammable.

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

Hazardous reactions : Amines and alcohols cause exothermic reactions.
Mixture reacts slowly with water resulting in evolution of CO₂.

10.4 Conditions to avoid

Conditions to avoid : Exposure to water vapour.
Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Amines
Incompatible with oxidizing agents.
Incompatible with acids and bases.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Acute toxicity estimate: 4883 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 1.467 mg/kg
Method: Calculation method

Components:

xylene:

Acute inhalation toxicity : LC50 (Rat): 5000 ppm
Exposure time: 4 h
Test atmosphere: gas

Hexamethylene diisocyanate, oligomers:

Acute inhalation toxicity : LC50: 1,5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Remarks: Expert judgement

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat): 3.500 mg/kg
Acute dermal toxicity : LD50 Dermal (Rabbit): 17.800 mg/kg

hexamethylene-di-isocyanate:

Acute oral toxicity : LD50 (Rat): 959 mg/kg
Method: OECD Test Guideline 401
Acute inhalation toxicity : LC50 (Rat): 0,124 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Acute dermal toxicity : LD50 (Rat): > 7.000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Respiratory or skin sensitisation

Product:

Remarks : Causes sensitisation.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

12.2 Persistence and degradability

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Uncured product residues and unpurified packaging should be disposed of as hazardous waste.
Waste should not be disposed of via wastewater.

Uncured product residues and unpurified packaging should be disposed of as hazardous waste.

Material residues: Allow the basic substance to harden with hardener and dispose of as paint waste.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product
080111*, waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transport information

14.1 UN number

ADN : UN 1139

ADR : UN 1139

RID : UN 1139

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

IMDG : UN 1139

IATA : UN 1139

14.2 UN proper shipping name

ADN : COATING SOLUTION
(ethylbenzene, xylene)

ADR : COATING SOLUTION
(ethylbenzene, xylene)

RID : COATING SOLUTION
(ethylbenzene, xylene)

IMDG : COATING SOLUTION
(ethylbenzene, xylene)

IATA : Coating solution
(ethylbenzene, xylene)

14.3 Transport hazard class(es)

ADN : 3

ADR : 3

RID : 3

IMDG : 3

IATA : 3

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG
Packing group : III
Labels : 3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

dibutyltin dilaurate (Number on list 30)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

REACH - List of substances subject to authorisation (Annex XIV) : None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Water contaminating class (Germany) : 2 significantly water endangering

. : PU50 PU systems, containing solvents, harmful, sensitising

Volatile organic compounds : < 75 %
< 750 g/l

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H331	: Toxic if inhaled.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

H341 : Suspected of causing genetic defects.
H360FD : May damage fertility. May damage the unborn child.
H370 : Causes damage to organs.
H372 : Causes damage to organs through prolonged or repeated exposure.
H373 : May cause damage to organs through prolonged or repeated exposure.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Muta. : Germ cell mutagenicity
Repr. : Reproductive toxicity
Resp. Sens. : Respiratory sensitisation
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
TRGS 430 : Germany. TRGS 430 - Isocyanates
TRGS 903 : TRGS 903 - Biological limit values
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
DE TRGS 900 / AGW : Time Weighted Average
TRGS 430 / AGW : Occupational Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture:

Flam. Liq. 3	H226
Acute Tox. 4	H332
Acute Tox. 4	H312
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H335
STOT RE 2	H373
Asp. Tox. 1	H304

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DisboADD 901

Version	Revision Date:	Print Date	Date of last issue: 21.11.2019
2.0	24.11.2020	03.12.2020	Date of first issue: 21.11.2019

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our up-stream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN