according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 2.1 15.05.2023 6025260 Date of first issue: 18.06.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Cool Protect

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Water-borne coatings

stance/Mixture

Recommended restrictions

on use

: within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710 Telefax : +4961547170222

Website

E-mail address Responsi-

ble/issuing person

: msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Cat-

H412: Harmful to aquatic life with long lasting ef-

egory 3

fects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006



DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 15.05.2023 6025260 Date of first issue: 18.06.2021 2.1

Hazard pictograms



Signal Word Warning

Hazard Statements H317 May cause an allergic skin reaction.

> H412 Harmful to aquatic life with long lasting effects.

P101 If medical advice is needed, have product container or **Precautionary Statements**

label at hand.

P102 Keep out of reach of children.

Prevention:

P262 Do not get in eyes, on skin, or on clothing.

P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection.

Response:

IF ON SKIN: Wash with plenty of soap and P302 + P352

water.

Hazardous ingredients which must be listed on the label:

octhilinone (ISO)

1,2-benzisothiazol-3(2H)-one

2-methylisothiazol-3(2H)-one

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Additional Labeling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006



DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 2.1 15.05.2023 6025260 Date of first issue: 18.06.2021

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Silicone resin paint, aqueous, with film protection

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	>= 1 - < 10
octhilinone (ISO)	26530-20-1 247-761-7 613-112-00-5 01-2120768921-45	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Sens. 1A; H317 >= 0,0015 % Acute toxicity estimate Acute oral toxicity: 125 mg/kg Acute inhalation toxicity (dust/mist): 0,27 mg/l Acute dermal toxicity:	>= 0,0025 - < 0,025

according to Regulation (EC) No. 1907/2006



DE / EN

Cool Protect

VersionRevision Date:SDS Number:Date of last issue: 15.03.20232.115.05.20236025260Date of first issue: 18.06.2021

		311 mg/kg	
terbutryn	886-50-0 212-950-5	Acute Tox. 4; H302 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Skin Sens. 1; H317 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Sens. 1; H317 >= 3 %	>= 0,0025 - < 0,025
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 2; H330 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1; H317 >= 0,05 %	>= 0,0025 - < 0,025
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 2; H330 Acute Tox. 3; H311 Acute Tox. 3; H301 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,0025 - < 0,025

according to Regulation (EC) No. 1907/2006



DE / EN

Cool Protect

Version	Revision Date:	SDS Number:	Date of last issue: 15.03.2023
21	15.05.2023	6025260	Date of first issue: 18 06 2021

		EUH071			
		M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1			
		specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %			
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	>= 0,0002 - < 0,0015		
Substances with a workplace exposure limit :					
Talc (Mg3H2(SiO3)4)	14807-96-6 238-877-9 01-2120140278-58		>= 1 - < 10		

according to Regulation (EC) No. 1907/2006



DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 2.1 15.05.2023 6025260 Date of first issue: 18.06.2021

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled : Move to fresh air.

In case of skin contact : Take off all contaminated clothing immediately.

Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed : Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Do not use a solid water stream as it may scatter and spread

fire.

Unsuitable extinguishing : None known.

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 2.1 15.05.2023 6025260 Date of first issue: 18.06.2021

media

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

: In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : Use water spray to cool unopened containers.

Standard procedure for chemical fires. The product itself does not burn.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole.

Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Use only with adequate ventilation.

For personal protection see section 8.

No special technical protective measures required.

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 2.1 15.05.2023 6025260 Date of first issue: 18.06.2021

No interior use.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat,

drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating

areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be care-

fully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline

materials.

Storage class (TRGS 510) : 12

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

CAS-No.	Value type (Form of exposure)	Control parameters	Basis
13463-67-7	AGW (Inhalable fraction)	10 mg/m3 (Titanium dioxide)	DE TRGS 900
Peak-limit category: 2;(II)			
Further information: When there is compliance with the OEL and biological			
tolerance values, there is no risk of harming the unborn child			
	AGW (Alveolate	1,25 mg/m3	DE TRGS
	fraction)	(Titanium dioxide)	900
Peak-limit category: 2;(II)			
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
	Peak-limit cate tolerance value Peak-limit cate Further information peak-limit cate Further information peak-limit cate Further information peak-limit cate pe	of exposure) 13463-67-7 AGW (Inhalable fraction) Peak-limit category: 2;(II) Further information: When there is tolerance values, there is no risk of AGW (Alveolate fraction) Peak-limit category: 2;(II) Further information: When there is	of exposure) 13463-67-7

according to Regulation (EC) No. 1907/2006



DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 2.1 15.05.2023 6025260 Date of first issue: 18.06.2021

		BM (Alveolar	0,5 mg/m3	DE TRGS	
		dust fraction)	, 3	527	
Talc	14807-96-6	AGW (Inhalable	10 mg/m3	DE TRGS	
(Mg3H2(SiO3)4)		fraction)		900	
, , , , ,	Peak-limit cat	egory: 2;(II)			
	Further inform	nation: When there is	compliance with the OEL a	nd biological	
	tolerance valu	ies, there is no risk o	of harming the unborn child	_	
		AGW (Alveolate	1,25 mg/m3	DE TRGS	
		fraction)	_	900	
	Peak-limit category: 2;(II)				
	Further information: When there is compliance with the OEL and biological				
	tolerance valu	tolerance values, there is no risk of harming the unborn child			
		BM (Alveolar	0,5 mg/m3	DE TRGS	
		dust fraction)	_	527	
octhilinone (ISO)	26530-20-1	AGW (Inhalable	0,05 mg/m3	DE TRGS	
		fraction)	_	900	
	Peak-limit category: 2;(I)				
	Further information: Skin absorption, When there is compliance with the OEL				
	and biological tolerance values, there is no risk of harming the unborn child				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health effects	Value
calcium carbonate	Consumers	Ingestion	Long-term systemic effects	6,10 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Consumers	Ingestion	Acute systemic effects	6,10 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
Kaolin, calcined	Workers	Inhalation	Acute systemic effects	3,00 mg/m3
	Workers	Inhalation	Acute local effects	3,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	3,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	3,00 mg/m3
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
Silicic acid, aluminum sodium salt	Workers	Inhalation	Long-term local ef- fects	4,00 mg/m3
1-(2-butoxy-1-	Consumers	Inhalation	Long-term systemic	1,20 mg/m3

according to Regulation (EC) No. 1907/2006



DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 2.1 15.05.2023 6025260 Date of first issue: 18.06.2021

methylethoxy)propan- 2-ol			effects	
	Consumers	Ingestion	Long-term systemic effects	7,50 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	1,10 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	3,00 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
calcium carbonate	Sewage treatment plant	100 mg/l
Kaolin, calcined	Intermittent use/release	25 mg/l
	Fresh water	4,1 mg/l
	Sea water	0,41 mg/l
	Sewage treatment plant	1400 mg/l
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sea sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l
1-(2-butoxy-1- methylethoxy)propan-2-ol	Sewage treatment plant	100 mg/l
	Fresh water	0,519 mg/l
	Soil	0,287 mg/kg dry weight (d.w.)
	Intermittent use/release	5,19 mg/l
	Fresh water sediment	2,96 mg/kg dry weight (d.w.)
	Sea water	0,0519 mg/l
	Sea sediment	0,296 mg/kg dry weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

according to Regulation (EC) No. 1907/2006



DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 15.05.2023 6025260 Date of first issue: 18.06.2021 2.1

Hand protection

Material Nitrile rubber Glove thickness 0,2 mm Protective index Class 3

Remarks Before removing gloves clean them with soap and water.

Wear suitable gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection Safety shoes

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.

During spray application: impervious clothing

Respiratory protection No personal respiratory protective equipment normally re-

quired.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Color white

Odor No data available

Melting point/freezing point ca. 0 °C

Boiling point/boiling range ca. 100 °C

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

: not determined

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 2.1 15.05.2023 6025260 Date of first issue: 18.06.2021

Flash point : Not applicable

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 8-9

Concentration: 100 %

Viscosity

Viscosity, dynamic : No data available

Solubility(ies)

Water solubility : completely miscible

Partition coefficient: n-

octanol/water

not determined

Vapor pressure : ca. 23,4 hPa (20 $^{\circ}$ C)

Density : 1,4700 g/cm3

Relative vapor density : not determined

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

according to Regulation (EC) No. 1907/2006



DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 15.05.2023 6025260 Date of first issue: 18.06.2021 2.1

10.5 Incompatible materials

Materials to avoid Incompatible with acids and bases.

Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

octhilinone (ISO):

Acute oral toxicity Acute toxicity estimate: 125 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute inhalation toxicity Acute toxicity estimate: 0,27 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute dermal toxicity Acute toxicity estimate: 311 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

terbutryn:

Acute oral toxicity LD50 Oral (Rat): > 300 mg/kg

LD50 Dermal (Rat): > 2.000 mg/kg Acute dermal toxicity

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 532 mg/kg

Acute inhalation toxicity LC50 (Rat): 0,4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

: LD50 (Rat): > 2.000 mg/kg Acute dermal toxicity

2-methylisothiazol-3(2H)-one:

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 2.1 15.05.2023 6025260 Date of first issue: 18.06.2021

Acute oral toxicity : LD50 (Rat): 120 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,145 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Acute oral toxicity : LD50 (Rat): 66 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 15.05.2023 6025260 Date of first issue: 18.06.2021 2.1

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna Straus (Water flea)): > 10 mg/l

End point: Immobilization Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

GLP: no

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 10

End point: Growth inhibition Exposure time: 72 h

Test Type: Cell multiplication inhibition test

Method: OECD Test Guideline 201

GLP: no

Ecotoxicology Assessment

Chronic aquatic toxicity Harmful to aquatic life with long lasting effects.

Components:

octhilinone (ISO):

M-Factor (Acute aquatic tox- :

icity)

100

M-Factor (Chronic aquatic

toxicity)

100

terbutryn:

M-Factor (Acute aquatic tox- :

icity)

100

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 2.1 15.05.2023 6025260 Date of first issue: 18.06.2021

M-Factor (Chronic aquatic

toxicity)

100

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia): 3,27 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox-

icity)

: 1

M-Factor (Chronic aquatic

toxicity)

: 1

2-methylisothiazol-3(2H)-one:

M-Factor (Acute aquatic tox- :

icity)

10

M-Factor (Chronic aquatic

toxicity)

: 1

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

M-Factor (Acute aquatic tox-

100

icity)

M-Factor (Chronic aquatic

100

toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

octhilinone (ISO):

Partition coefficient: n- : log Pow: 2,92

octanol/water Method: OECD Test Guideline 117

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Cool Protect

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 15.03.2023

 2.1
 15.05.2023
 6025260
 Date of first issue: 18.06.2021

terbutryn:

Partition coefficient: n-

octanol/water

log Pow: 3,66

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Partition coefficient: n-

log Pow: <= 0,71

octanol/water

Method: OECD Test Guideline 117

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

Harmful to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : .

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

according to Regulation (EC) No. 1907/2006

DE / EN



Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 2.1 15.05.2023 6025260 Date of first issue: 18.06.2021

080112, waste paint and varnish other than those mentioned in 08 01 11*

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

according to Regulation (EC) No. 1907/2006



Cool Protect

DE / EN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 15.03.2023

 2.1
 15.05.2023
 6025260
 Date of first issue: 18.06.2021

Remarks : Not classified as dangerous in the meaning of transport regu-

lations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered:

Number on list 3

formaldehyde (Number on list 72, 28)

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener-

ated.

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water hazard class (Germa-

ny)

WGK 1 slightly water endangering

Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and

paints / Giscode

: M-SF01F Water-based, silicone resin paints, active agents

: BSW50 Coating materials, water-based, containing solvents,

film-protected

according to Regulation (EC) No. 1907/2006



DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 2.1 15.05.2023 6025260 Date of first issue: 18.06.2021

Volatile organic compounds : Directive 2004/42/EC

< 3 % < 40 g/l

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H311 : Toxic in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.

H330 : Fatal if inhaled.

H351 : Suspected of causing cancer if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Carc. : Carcinogenicity
Eye Dam. : Serious eye damage
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 527 / BM : Assessment scale
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community num-

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 2.1 15.05.2023 6025260 Date of first issue: 18.06.2021

ber; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50% of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods Nall Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Stance Inventory; TECI - Thailand Existing Chemicals Inventory; TR

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture: Classification procedure:

Skin Sens. 1 H317 Calculation method

Aquatic Chronic 3 H412 Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Cool Protect

Version Revision Date: SDS Number: Date of last issue: 15.03.2023 2.1 15.05.2023 6025260 Date of first issue: 18.06.2021

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN