

DisboFLOOR 475 Comp. A RAL7032

Version	Revision Date:	SDS Number:	Date of last issue: 20.09.2021
2.0	30.01.2023	6025687	Date of first issue: 20.09.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name	:	DisboFLOOR 475 Comp. A RAL7032				
1.2 Relevant identified uses of	the s	substance or mixture and uses advised against				
Use of the Sub- stance/Mixture	:	_				
Recommended restrictions on use	:	within adequate application - none				
1.3 Details of the supplier of th	e saf	ety data sheet				
Company	:	Disbon GmbH Roßdörfer Straße 50 64372 Ober-Ramstadt				
Telephone	:	+496154710				
Telefax	:	+4961547170222				
E-mail address Responsi- ble/issuing person	:	msds@dr-rmi.com				
1.4 Emergency telephone						
Emergency telephone 1	:	+49613284463 GBK GmbH				
SECTION 2: Hazards identification						
2.1 Classification of the substance or mixture						
Classification (REGULATI	ON (E	EC) No 1272/2008)				
Skin irritation, Category 2 H315: Causes skin irritation.						

Eye irritation, Category 2H319: Causes serious eye irritation.Skin sensitization, Category 1H317: May cause an allergic skin reaction.Long-term (chronic) aquatic hazard, Category 2H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)



DisboFL	DisboFLOOR 475 Comp. A RAL7032					
Version 2.0	Revision Date: 30.01.2023	SDS Nu 6025687		Date of last issue: 20.09.2021 Date of first issue: 20.09.2021		
Hazard	pictograms					
Signal V	Word	: Warni	ng			
Hazard	Statements	: H315 H317 H319 H411	May cause Causes se	in irritation. an allergic skin reaction. rious eye irritation. uatic life with long lasting effects.		
Precaut	tionary Statements	P262 P264	Wash skin Avoid relea	in eyes, on skin, or on clothing. thoroughly after handling. ase to the environment. ective gloves/ eye protection.		
		attent P362	+P313 If e ion.	eye irritation persists: Get medical advice/ ke off contaminated clothing and wash it		

Hazardous ingredients which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane bisphenol-F epoxy resin MW <700 oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 1,6-Hexanediol, reaction products with epichlorohydrin Cashew (Anacardium occidentale) Nutshell Extract, Decarboxylated, Distilled Fatty acids, C14-18 and C16-18-unsatd., 2-phenoxyethyl esters, maleated maleic anhydride

Additional Labeling

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



DisboFLOOR 475 Comp. A RAL7032

Version	Revision Date:	SDS Number:	Date of last issue: 20.09.2021
2.0	30.01.2023	6025687	Date of first issue: 20.09.2021

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

.

Chemical nature : Epoxide-resin-based coating material, totally solid

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 \longrightarrow specific concentration limit Eye Irrit. 2; H319 >= 5 % Skin Irrit. 2; H315 >= 5 %	>= 25 - < 30
bisphenol-F epoxy resin MW <700	9003-36-5 500-006-8 01-2119454392-40	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 10 - < 20
oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	68609-97-2 271-846-8 603-103-00-4 01-2119485289-22	Skin Irrit. 2; H315 Skin Sens. 1; H317	>= 1 - < 10
titanium dioxide; [in powder form containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	>= 1 - < 10
1,6-Hexanediol, reaction products with epichlorohydrin	933999-84-9 01-2119463471-41	Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 Aquatic Chronic 3; H412	>= 1 - < 2,5
Cashew (Anacardium occidentale) Nutshell Extract, Decarboxylated,	8007-24-7	Acute Tox. 4; H302 Acute Tox. 4; H312	>= 1 - < 3



DisboFLOOR 475 Comp. A RAL7032

sion	Revision Date: 30.01.2023	SDS Number: 6025687	Date of last issue: 20.09.2021 Date of first issue: 20.09.2021
Distill		01-2119502 01-2120074 16-18- 91001-64-8	481-58 Skin Sens. 1A; H317 Eye Dam. 1; H318
	acids, C14-18 and C ² d., 2-phenoxyethyl es ated		Eye Irrit. 2; H319 < 0,1 Skin Sens. 1A; H317
malei	c anhydride	108-31-6 203-571-6 607-096-00- 01-2119472 01-2120759	128-31, Resp. Sens. 1; H334
			specific concentration limit Skin Sens. 1A; H317 >= 0,001 %
	ances with a workpla		
bariur	n sulfate	7727-43-7 231-784-4 01-2119491	274-35

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice	li P N	Never give anything by mouth to an unconscious person. f you feel unwell, seek medical advice (show the label where possible). Move out of dangerous area. First aider needs to protect himself.
If inhaled	: N	Nove to fresh air.
In case of skin contact	lı c	Do NOT use solvents or thinners. n case of contact, immediately flush skin with soap and plenty of water. Fake off all contaminated clothing immediately.
In case of eye contact	F	F IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue insing. Immediately call a POISON CENTER or doctor/ phy-



Dis	DisboFLOOR 475 Comp. A RAL7032					
Vers 2.0		Revision Date: 30.01.2023	SE	OS Number: 25687	Date of last issue: 20.09.2021 Date of first issue: 20.09.2021	
				sician.		
	If swall	owed	:		water and drink afterwards plenty of water. NOT induce vomiting.	
4.2	Most im	portant symptoms a	nd e	effects, both acute	e and delayed	
	Risks		:	Causes skin irrita May cause an alle Causes serious e	ergic skin reaction.	
4.3	Indicati	on of any immediate	med	dical attention and	special treatment needed	
	Treatm	ent	:	No information av	ailable.	
SEC	CTION	5: Firefighting meas	sur	es		
5.1 Extinguishing media Suitable extinguishing media : Use extinguishing measures that are appropriate to local cumstances and the surrounding environment. Foam Carbon dioxide (CO2)				he surrounding environment.		
	Unsuita media	able extinguishing	:	None known.		
5.2	Special	hazards arising from	the	substance or mi	xture	
	-	c hazards during fire	:	Cool closed conta	ainers exposed to fire with water spray. Apposition products formed under fire condi-	
5.3	Advice	for firefighters				
	Specia	l protective equipment fighters	:	In the event of fire	e, wear self-contained breathing apparatus.	
	Further	information	:	be disposed of in Standard procedu	contaminated fire extinguishing water must accordance with local regulations. Ire for chemical fires. and/or explosion do not breathe fumes.	

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
 - Personal precautions : Do not get in eyes, on skin, or on clothing.



DisboFLOOR 475 Comp. A RAL7032

Version 2.0	Revision Date: 30.01.2023	SDS Number: 6025687	Date of last issue: 20.09.2021 Date of first issue: 20.09.2021				
6.2 Environmental precautions							
Enviror	nmental precautions	If the product cont respective authori	akage or spillage if safe to do so. aminates rivers and lakes or drains inform ties. urface water or sanitary sewer system.				
6.3 Methods and material for containment and cleaning up							
Method	ds for cleaning up	Soak up with inert	closed containers for disposal. absorbent material (e.g. sand, silica gel, rsal binder, sawdust).				

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet. , For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Advice on safe handling For personal protection see section 8. 5 Avoid exceeding the given occupational exposure limits (see section 8). Provide sufficient air exchange and/or exhaust in work rooms. In addition, the current technical information for this product and its application on www.caparol.com must be observed. Advice on protection against : The product is flammable but not readily ignited. fire and explosion Hygiene measures : Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Storage class (TRGS 510)	:	10



DisboFLOOR 475 Comp. A RAL7032

Version	Revision Date:	SDS Number:	Date of last issue: 20.09.2021
2.0	30.01.2023	6025687	Date of first issue: 20.09.2021

7.3 Specific end use(s)

Specific use(s)

: This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
barium sulfate	7727-43-7	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900	
	Dook limit oot			900	
	Peak-limit cat			and high giag	
	Further information: When there is compliance with the OEL and biolog tolerance values, there is no risk of harming the unborn child				
		AGW (Alveolate 1,25 mg/m3 DE TRG			
		fraction)	· , ·g,e	900	
	Peak-limit cat	,	L		
			s compliance with the OEL	and biological	
			of harming the unborn child		
		BM (Alveolar	0,5 mg/m3	DE TRGS	
		dust fraction)		527	
titanium dioxide; [in	13463-67-7	AGW (Inhalable	10 mg/m3	DE TRGS	
powder form con-		fraction)	(Titanium dioxide)	900	
taining 1 % or					
more of particles					
with aerodynamic					
diameter ≤ 10 µm]		2 (II)			
	Peak-limit cat				
			s compliance with the OEL of harming the unborn child		
		AGW (Alveolate	1,25 mg/m3	DE TRGS	
		fraction)	(Titanium dioxide)	900	
	Peak-limit cat				
			s compliance with the OEL		
	tolerance valu		of harming the unborn child		
		BM (Alveolar	0,5 mg/m3	DE TRGS	
		dust fraction)		527	
maleic anhydride	108-31-6	AGW (Vapour	0,02 ppm	DE TRGS	
		and aerosols)	0,081 mg/m3	900	
		egory: 1; =2.5=(l)			
			cases also a momentary v		
			eded. This substance will b		
			value., When there is com		
			es, there is no risk of harm		
	child, Substar	ice sensilizing throug	gh the skin and respiratory	System	



DisboFLOOR 475 Comp. A RAL7032

Version	Revision Date:	SDS Number:	Date of last issue: 20.09.2021
2.0	30.01.2023	6025687	Date of first issue: 20.09.2021

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health ef- fects	Value
barium sulfate	Consumers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	13000,00 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
bisphenol-F epoxy resin MW <700	Consumers	Skin contact	Long-term systemic effects	62,50 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	6,25 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	8,70 mg/m3
	Workers	Skin contact	Acute local effects	8,30 µg/cm2
	Workers	Skin contact	Long-term systemic effects	104,15 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	29,39 mg/m3
titanium dioxide; [in powder form contain- ing 1 % or more of particles with aerody- namic diameter \leq 10 µm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
1,6-Hexanediol, reac- tion products with epichlorohydrin	Consumers	Skin contact	Acute systemic ef- fects	1,70 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	1,70 mg/kg bw/day
	Consumers	Skin contact	Long-term local ef- fects	13,60 µg/cm2
	Consumers	Inhalation	Long-term local ef- fects	0,27 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	2,90 mg/m3
	Consumers	Ingestion	Acute systemic ef- fects	0,83 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,90 mg/m3
	Consumers	Skin contact	Acute local effects	13,60 µg/cm2
maleic anhydride	Consumers	Inhalation	Long-term systemic	0,05 mg/m3



DisboFLOOR 475 Comp. A RAL7032

/ersion 2.0	Revision Date: 30.01.2023	SDS Nun 6025687		of last issue: 20.09.2021 of first issue: 20.09.2021	
				effects	
		Consumers	Ingestion	Long-term systemic effects	0,06 mg/kg bw/day
		Consumers	Ingestion	Acute systemic ef- fects	0,10 mg/kg bw/day
		Consumers	Skin contact	Acute systemic ef- fects	0,10 mg/kg bw/day
		Consumers	Inhalation	Long-term local ef- fects	0,08 mg/m3
		Consumers	Skin contact	Long-term systemic effects	0,10 mg/kg bw/day
		Workers	Inhalation	Acute systemic ef- fects	0,80 mg/m3
		Workers	Inhalation	Acute systemic ef- fects	0,95 mg/m3
		Workers	Inhalation	Acute local effects	0,80 mg/m3
		Workers	Inhalation	Long-term systemic effects	0,40 mg/m3
		Workers	Inhalation	Long-term systemic effects	0,19 mg/m3
		Workers	Inhalation	Long-term local ef- fects	0,40 mg/m3
		Workers	Inhalation	Long-term local ef- fects	0,32 mg/m3
		Workers	Skin contact	Acute systemic ef- fects	0,20 mg/kg bw/day
		Workers	Skin contact	Long-term systemic effects	0,20 mg/kg bw/day
		Consumers	Inhalation	Acute systemic ef- fects	

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
barium sulfate	Fresh water	115 μg/l
	Fresh water sediment	600,4 mg/kg dry weight (d.w.)
	Soil	207,7 mg/kg dry weight (d.w.)
	Sewage treatment plant	62,2 mg/l
bisphenol-F epoxy resin MW <700	Fresh water	0,003 mg/l
	Fresh water sediment	0,294 mg/kg dry weight (d.w.)
	Intermittent use/release	0,0254 mg/l
	Sea sediment	0,0294 mg/kg dry weight (d.w.)
	Sea water	0,0003 mg/l
	Sewage treatment plant	10 mg/l
	Soil	0,237 mg/kg dry



DisboFLOOR 475 Comp. A RAL7032

sion	Revision Date: 30.01.2023	SDS Number:Date of last issue:6025687Date of first issue	
1			woight (d.w.)
titoniu	m diavida: [in nowday	form Sewage treatment plant	weight (d.w.) 100 mg/l
titanium dioxide; [in powder form containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 µm]		parti-	Too mg/i
		Fresh water	0,184 mg/l
		Soil	100 mg/kg dry weight (d.w.)
		Sea water	0,0184 mg/l
		Fresh water sediment	1000 mg/kg dr weight (d.w.)
		Sea sediment	100 mg/kg dry weight (d.w.)
		Intermittent use/release	0,193 mg/l
	exanediol, reaction pr vith epichlorohydrin	od- Sea water	0,00115 mg/l
		Fresh water	0,0115 mg/l
		Soil	0,223 mg/kg d weight (d.w.)
		Sewage treatment plant	1 mg/l
		Intermittent use/release	0,115 mg/l
		Sea sediment	0,0283 mg/kg weight (d.w.)
		Fresh water sediment	0,283 mg/kg d weight (d.w.)
maleid	c anhydride	Fresh water	0,075 mg/l
	y	Fresh water sediment	0,334 mg/kg d weight (d.w.)
		Soil	0,0415 mg/kg weight (d.w.)
		Sea water	0,01 mg/l
		Intermittent use/release	0,4281 mg/l
		Sewage treatment plant	44,6 mg/l
		Soil	0,01 mg/kg dry weight (d.w.)
		Sea water	0,0075 mg/l
		Secondary Poisoning	6,67 mg/kg for
		Fresh water	0,1 mg/l
		Sewage treatment plant	4,46 mg/l
		Sea sediment	0,006 mg/kg d weight (d.w.)
		Fresh water sediment	0,06 mg/kg dry weight (d.w.)
		Intermittent use/release	0,75 mg/l
		Sea sediment	0,0334 mg/kg weight (d.w.)



DisboFLOOR 475 Comp. A RAL7032

Version 2.0	Revision Date: 30.01.2023		OS Number: 25687	Date of last issue: 20.09.2021 Date of first issue: 20.09.2021				
8.2 Exposure controls								
Pers	onal protective equipm	nent						
Eye/f	ace protection	:	DGUV Regulation	112-192 - Use of eye and face protection				
			Tightly fitting safe	ty goggles				
	protection							
	aterial	:	Nitrile rubber					
	love thickness rotective index	:	0,2 mm Class 3					
E I		•	01035 0					
R	emarks	:	cation of degrada moving gloves cle ble gloves tested	discarded and replaced if there is any indi- tion or chemical breakthrough. Before re- ean them with soap and water. Wear suita- to EN374. 112-195 - Use of protective gloves				
Skin	and body protection	:	contaminated clot Additional body ga task being perform	arments should be used based upon the ned (e.g., sleevelets, apron, gauntlets, dis- avoid exposed skin surfaces.				
				tection according to the amount and con- dangerous substance at the work place.				
			Skin should be wa	ashed after contact.				
Resp	iratory protection	:	used under condition	or brushing: This product should not be tions of poor ventilation unless a protective ropriate gas filter (i.e. type A1 according to 37) is used.				
			DGUV Regulation	112-190 - Use of breathing equipment				
				lication: Do not breathe spray dust. Use n filter for paint spraying.				

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state

: liquid

liquid



DisboFLOOR 475 Comp. A RAL7032

Vers 2.0	sion	Revision Date: 30.01.2023		S Number: 25687	Date of last issue: 20.09.2021 Date of first issue: 20.09.2021
	Color		:	No data available)
				gray	
	Odor		:	No data available	9
				characteristic	
	Melting	point/freezing point	:	not determined	
	Boiling	point/boiling range	:	not determined	
		explosion limit / Upper bility limit	:	not determined	
		explosion limit / Lower bility limit	:	not determined	
	Flash p	oint	:		
	Autoign	ition temperature	:	not determined	
	Decom	position temperature	:	Not applicable	
	pН		:	substance/mixtur	e is non-soluble (in water)
				substance/mixtur	e is non-soluble (in water)
	Viscosi Visc	ty osity, dynamic	:		
				No data available)
	Visc	osity, kinematic	:	Not applicable	
	Flow tin	ne	:	> 60 s at 23 °C Cross section: 6 Method: ISO 243	
	Solubili Wat	ty(ies) er solubility	:	partly miscible	
	Partition octanol	n coefficient: n- /water	:	not determined	
	Vapor p	pressure	:	not determined	
	Bulk de	nsity	:	Not applicable	



DisboFLOOR 475 Comp. A RAL7032

Versio 2.0	on Revision Date: 30.01.2023	SDS Number: 6025687	Date of last issue: 20.09.2021 Date of first issue: 20.09.2021	
F	Relative vapor density	: not determined	d	
	ther information Dxidizing properties	: Not applicable		
Flammability (liquids)		: The product is not flammable.		
E	Evaporation rate	: Not applicable		

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	: Hazardous decomposition products formed under fire condi- tions.
10.4 Conditions to avoid	

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid

: Incompatible with acids. Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Product:		
Acute oral toxicity	:	Acute toxicity estimate: > 2.000 mg/kg Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2.000 mg/kg Method: Calculation method



rsion	Revision Date: 30.01.2023	SDS Number: 6025687	Date of last issue: 20.09.2021 Date of first issue: 20.09.2021
<u>Com</u>	oonents:		
Fatty	acids, C14-18 and C	C16-18-unsatd., 2-ph	enoxyethyl esters, maleated:
Acute	oral toxicity	: LD50 (Rat): 8 Method: OEC	295 mg/kg D Test Guideline 401
malei	c anhydride:		
Acute	oral toxicity		ale and female): 1.090 mg/kg D Test Guideline 401
	corrosion/irritation		
Cause	es skin irritation.		
<u>Com</u>	oonents:		
malei	c anhydride:		
Speci		: Rabbit	
A3300	ssment	: Causes burns	
Saria		• •, ,•	
	us eye damage/eye		
	es serious eye irritation		
Cause			
Cause Com	es serious eye irritatio		
Cause Comp malei Speci	es serious eye irritatio ponents: c anhydride: es	on. : Rabbit	
Cause Comp malei Speci	es serious eye irritatio ponents: c anhydride:	on.	S.
Cause Comp malei Speci Asses	es serious eye irritatio ponents: c anhydride: es	on. : Rabbit : Causes burns	5.
Cause Comj malei Speci Asses Resp	es serious eye irritation ponents: c anhydride: es ssment	on. : Rabbit : Causes burns	5.
Cause Comp malei Speci Asses Resp Skin	es serious eye irritatio ponents: c anhydride: es essment iratory or skin sens	on. : Rabbit : Causes burns itization	5.
Cause Comp malei Speci Asses Resp Skin Resp	es serious eye irritatio <u>conents:</u> c anhydride: es ssment iratory or skin sensi sensitization cause an allergic skin iratory sensitization	n. : Rabbit : Causes burns itization reaction.	5.
Cause Comp malei Speci Asses Resp Skin Resp	es serious eye irritatio <u>conents:</u> c anhydride: es ssment iratory or skin sensi sensitization cause an allergic skin	n. : Rabbit : Causes burns itization reaction.	S.
Cause Comp malei Speci Asses Resp Skin Resp Nay c Resp	es serious eye irritatio <u>conents:</u> c anhydride: es ssment iratory or skin sensi sensitization cause an allergic skin iratory sensitization	n. : Rabbit : Causes burns itization reaction.	5.
Cause Comp malei Speci Asses Resp Skin Resp Nay c Resp Not cl Comp	es serious eye irritation c anhydride: es ssment iratory or skin sensitistion cause an allergic skin iratory sensitization assified based on aver-	n. : Rabbit : Causes burns itization reaction.	5.
Cause Comp malei Speci Asses Resp Skin Resp Not cl Comp malei Speci	es serious eye irritation c anhydride: es es esment iratory or skin sense sensitization ause an allergic skin iratory sensitization assified based on ave conents: c anhydride: es	on. : Rabbit : Causes burns itization reaction. ailable information.	
Cause Comp malei Speci Asses Resp Skin Resp Nay o Resp Not cl Comp malei	es serious eye irritation c anhydride: es es esment iratory or skin sense sensitization ause an allergic skin iratory sensitization assified based on ave conents: c anhydride: es	 c. Rabbit c. Causes burns itization reaction. ailable information. 	
Cause Comp malei Speci Asses Resp Skin Resp Not cl Comp malei Speci Resu	es serious eye irritation c anhydride: es es esment iratory or skin sense sensitization ause an allergic skin iratory sensitization assified based on ave conents: c anhydride: es	on. : Rabbit : Causes burns itization reaction. ailable information.	



Disbo	FLOOR 475 Com	p. A RAL7032							
Version 2.0	Revision Date: 30.01.2023	SDS Number: 6025687	Date of last issue: 20.09.2021 Date of first issue: 20.09.2021						
	productive toxicity								
Not	Not classified based on available information.								
	OT-single exposure								
Not	classified based on avail	able information.							
	OT-repeated exposure								
Not	classified based on avail	able information.							
-	biration toxicity								
Not	classified based on avail	able information.							
11.2 Info	ormation on other hazar	ds							
Enc	locrine disrupting prop	erties							
Pro	duct:								
Ass	essment	ered to have e REACH Article	/mixture does not contain components consid- ndocrine disrupting properties according to 57(f) or Commission Delegated regulation 0 or Commission Regulation (EU) 2018/605 at or higher.						
Fur	ther information								
<u>Pro</u>	duct:								
Rer	narks		roduct only contains epoxy resins with high ht, follow good industrial hygiene practice and d skin contact.						
050T									

SECTION 12: Ecological information

12.1 Toxicity

Components:

barium sulfate:		
Toxicity to fish	:	Remarks: No toxicity at the limit of solubility.
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No toxicity at the limit of solubility.
Toxicity to algae/aquatic plants	:	Remarks: No toxicity at the limit of solubility.
Toxicity to fish (Chronic tox- icity)	:	Remarks: No toxicity at the limit of solubility.
Toxicity to daphnia and other	:	Remarks: No toxicity at the limit of solubility.



Disbo	LOOR 475 Com	p.	A RAL7032	
Version 2.0	Revision Date: 30.01.2023		DS Number: 25687	Date of last issue: 20.09.2021 Date of first issue: 20.09.2021
aqua ic tox	tic invertebrates (Chron- icity)	-		
	istence and degradabi ata available	lity		
12.3 Bioa	ccumulative potential			
Com	ponents:			
oxira	ne, mono[(C12-14-alky	/lox	v)methvl1 derivs.:	
Partit	ion coefficient: n- iol/water		log Pow: 3,77	est Guideline 107
1,6-H	exanediol, reaction pr	odu	cts with epichloro	hydrin:
Partit	ion coefficient: n- ol/water			-
Fatty	acids, C14-18 and C1	6-18	-unsatd., 2-pheno	xyethyl esters, maleated:
	ion coefficient: n- ol/water	:	log Pow: > 4,1	
male	ic anhydride:			
	ion coefficient: n- ol/water	:	log Pow: -2,61 (1 pH: 4 - 9	9,8 °C)
	i lity in soil ata available			
12.5 Resu	llts of PBT and vPvB a	sse	ssment	
Prod	uct:			
	ssment	:	to be either persis	nixture contains no components considered stent, bioaccumulative and toxic (PBT), or nd very bioaccumulative (vPvB) at levels of
12.6 Endo	ocrine disrupting prop	ertie	S	
Prod	uct:			
	ssment	:	ered to have end REACH Article 57	ixture does not contain components consid- ocrine disrupting properties according to 7(f) or Commission Delegated regulation or Commission Regulation (EU) 2018/605 at higher.



DisboF	DisboFLOOR 475 Comp. A RAL7032				
Version 2.0	Revision Date: 30.01.2023		DS Number: 025687	Date of last issue: 20.09.2021 Date of first issue: 20.09.2021	
12.7 Othe	r adverse effects				
<u>Prod</u> Additi matio	ional ecological infor-	:	Toxic to aquatic o effects in the aqu	organisms, may cause long-term adverse atic environment.	
SECTION	N 13: Disposal consi	ider	ations		
13.1 Wast	e treatment methods				
Produ	uct	:	disposed of as ha Material residues hardener and dis	residues and unpurified packaging should be azardous waste. : Allow the basic substance to harden with pose of as paint waste. t be disposed of via wastewater.	
Conta	aminated packaging	:	Only completely o cling.	emptied containers should be given for recy-	
Wast	e Code	:	used product 080111*, waste p or other dangeror	aint and varnish containing organic solvents us substances	
SECTION	14: Transport info	rma	tion		

14.1 UN number or ID number

ADN	: UN 3082
ADR	: UN 3082
RID	: UN 3082
IMDG	: UN 3082
ΙΑΤΑ	: UN 3082
14.2 UN proper shipping n	ame
ADN	 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl]propane, bisphenol-F epoxy resin MW <700)
ADR	 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl]propane, bisphenol-F epoxy resin MW <700)
RID	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl]propane, bisphenol-F epoxy



DisboFLOOR 475 Comp. A RAL7032

Version 2.0	Revision Date: 30.01.2023		DS Number: 25687	Date of last issue: 20.09.2021 Date of first issue: 20.09.2021	
			resin MW <700)		
IMDG)	:	N.O.S.	ALLY HAZARDOUS SUBSTANCE, LIQUID, propoxi)phenyl]propane, bisphenol-F epoxy	
			resin MW <700)		
ΙΑΤΑ		:	Environmentally hazardous substance, liquid, n.o.s. (bis-[4-(2,3-epoxipropoxi)phenyl]propane, bisphenol-F epoxy resin MW <700)		
14.3 Trans	sport hazard class(es)				
			Class	Subsidiary risks	
ADN		:	9		
ADR		:	9		
RID		:	9		
IMDG	3	:	9		
ΙΑΤΑ		:	9		
14.4 Pack	ing group				
Class	ing group ification Code rd Identification Number Is	:	III M6 90 9		
Class Haza Label	ing group sification Code rd Identification Number Is el restriction code	:	III M6 90 9 (-)		
Class	ing group ification Code rd Identification Number Is	:	III M6 90 9		
IMDG Packi Label EmS	ing group Is	:	III 9 F-A, S-F		
	(Cargo) ing instruction (cargo ift)	:	964		
Packi	ing instruction (LQ)	: : :	Y964 III Miscellaneous		



DisboFLOOR 475 Comp. A RAL7032

Version	Revision Date:	SDS Number:	Date of last issue: 20.09.2021
2.0	30.01.2023	6025687	Date of first issue: 20.09.2021

IATA (Passenger)

Packing instruction (passen-	:	964
ger aircraft)		
Packing instruction (LQ)	:	Y964
Packing group	:	111
Labels	:	Miscellaneous

14.5 Environmental hazards

ADN Environmentally hazardous	:	yes
ADR Environmentally hazardous	:	yes
RID Environmentally hazardous	:	yes
IMDG Marine pollutant	:	yes
IATA (Passenger) Environmentally hazardous	:	yes
IATA (Cargo) Environmentally hazardous	:	yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).	: This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical

safety assessment has to be gener-

ated.



DisboFLOOR 475 Comp. A RAL7032

Version 2.0	Revision Date: 30.01.2023	SDS Number: 6025687	Date of last issue: 20.09.2021 Date of first issue: 20.09.2021
	gulation (EC) No 1005/200 e the ozone layer	9 on substances tha	at de- : Not applicable
	gulation (EU) 2019/1021 o s (recast)	n persistent organic	pollu- : Not applicable
	ACH - List of substances s nex XIV)	subject to authorisati	on : None
pea con	reso III: Directive 2012/18 n Parliament and of the C trol of major-accident haz gerous substances.	council on the	E2 ENVIRONMENTAL HAZARDS
Wa ny)	ter hazard class (Germa-		sly hazardous to water ccording to AwSV, Annex 1 (5.2)
	duct code for laquers and hts / Giscode	: RE1 Epoxy res	in products, solvent-free, sensitising
		: RE30 Epoxy re	sin products, sensitising, totally solid
Vola	atile organic compounds	: Directive 2004/ < 2 % < 20 g/l	/42/EC

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H302 :	Harmful if swallowed.
H312 :	Harmful in contact with skin.
H314 :	Causes severe skin burns and eye damage.
H315 :	Causes skin irritation.
H317 :	May cause an allergic skin reaction.
H318 :	Causes serious eye damage.
H319 :	Causes serious eye irritation.
H334 :	May cause allergy or asthma symptoms or breathing difficul-
	ties if inhaled.





DisboFLOOR 475 Comp. A RAL7032

Version 2.0	Revision Date: 30.01.2023		DS Number: 25687	Date of last issue: 20.09.2021 Date of first issue: 20.09.2021	
H351 H372 H411 H412 EUH07	71	:	Suspected of causing cancer if inhaled. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. Corrosive to the respiratory tract.		
Full te	xt of other abbreviat	tions			
Carc. Eye Da Eye Irr Resp. Skin C Skin S Stot DE TR DE TR DE TR	c Chronic am. it. Sens. orr. rit. ens.		 Acute toxicity Long-term (chronic) aquatic hazard Carcinogenicity Serious eye damage Eye irritation Respiratory sensitization Skin corrosion Skin irritation Skin sensitization Specific target organ toxicity - repeated exposure Germany. TRGS 527 - Activities with nanomaterials Germany. TRGS 900 - Occupational exposure limit value Assessment scale Time Weighted Average 		

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Maritime Organization; IECC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; IECC - Inventory of existing Chemical Substances to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)XAR - (Quantit

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite



DisboFLOOR 475 Comp. A RAL7032

Version	Revision Date:	SDS Number:	Date of last issue: 20.09.2021
2.0	30.01.2023	6025687	Date of first issue: 20.09.2021

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the	Classification procedure:	
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN