according to Regulation (EC) No. 1907/2006



DisboADD 995

Version Revision Date: Print Date Date of last issue: -

1.0 12.01.2021 07.07.2023 Date of first issue: 12.01.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : DisboADD 995

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Thinner, Diluent

stance/Mixture

Recommended restrictions

on use

within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Disbon GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710 Telefax : +4961547170222

Telefax E-mail address Responsi-

ble/issuing person

: msds@dr-rmi.com

1.4 Emergency telephone number

Emergency telephone num: +49613284463 GBK GmbH

ber 1

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Acute toxicity, Category 4 H332: Harmful if inhaled.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous

ovetem

H336: May cause drowsiness or dizziness.

system

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version Revision Date: Print Date Date of last issue: -

1.0 12.01.2021 07.07.2023 Date of first issue: 12.01.2021

Specific target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

ways.

Long-term (chronic) aquatic hazard, Cat-

egory 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms









Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or

repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P260 Do not breathe vapours/ spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P331 Do NOT induce vomiting.

Hazardous components which must be listed on the label:

xylene

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified 4-methylpentan-2-one

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version Revision Date: Print Date Date of last issue: -

1.0 12.01.2021 07.07.2023 Date of first issue: 12.01.2021

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration
			(% w/w)
	Index-No.		
	Registration number		
xylene	1330-20-7	Flam. Liq. 3; H226	>= 50 - < 70
	215-535-7	Acute Tox. 4; H332	
	601-022-00-9	Acute Tox. 4; H312	
	01-2119488216-32	Skin Irrit. 2; H315	
		Eye Irrit. 2; H319	
		STOT SE 3; H335	
		Asp. Tox. 1; H304	
		STOT RE 2; H373	
Solvent naphtha (petroleum), light	64742-95-6	STOT SE 3; H336	>= 30 - < 50
arom.; Low boiling point naphtha -	265-199-0	STOT SE 3; H335	
unspecified	649-356-00-4	Aquatic Chronic 2;	
·	01-2119455851-35,	H411	
	01-2119486773-24	Asp. Tox. 1; H304	
		Flam. Liq. 3; H226	
4-methylpentan-2-one	108-10-1	Flam. Liq. 2; H225	>= 1 - < 10
	203-550-1	Acute Tox. 4; H332	
	606-004-00-4	Eye Irrit. 2; H319	
	01-2119473980-30	STOT SE 3; H335	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled : Call a physician.

If breathing is irregular or stopped, administer artificial respira-

tion.

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version **Revision Date:** Print Date Date of last issue: -

07.07.2023 1.0 12.01.2021 Date of first issue: 12.01.2021

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

Move to fresh air.

In case of skin contact In case of contact, immediately flush skin with soap and plenty

of water.

Take off all contaminated clothing immediately.

If eye irritation persists: Get medical advice/ attention. In case of eye contact

> IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed Aspiration may cause pulmonary oedema and pneumonitis.

> Take victim immediately to hospital. If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Fire residues and contaminated fire extinguishing water must

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version Revision Date: Print Date Date of last issue: -

1.0 12.01.2021 07.07.2023 Date of first issue: 12.01.2021

be disposed of in accordance with local regulations. Use water spray to cool unopened containers.

Standard procedure for chemical fires.

In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Ensure adequate ventilation. Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

,For personal protection see section 8.,For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Avoid exceeding the given occupational exposure limits (see

section 8).

Provide sufficient air exchange and/or exhaust in work rooms.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Advice on protection against

fire and explosion

Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version Revision Date: Print Date Date of last issue: -

1.0 12.01.2021 07.07.2023 Date of first issue: 12.01.2021

Hygiene measures : Keep working clothes separately. Remove and wash contami-

nated clothing before re-use. Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do

not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Take measures to prevent the build up of electrostatic charge. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully

resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 3, Flammable liquids

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
xylene	1330-20-7	TWA	50 ppm 221 mg/m3	2000/39/EC
	Further information: Indicative, Identifies the possibility of significant uptake			icant uptake
	through the sl	KIN		
		STEL	100 ppm	2000/39/EC
			442 mg/m3	
	Further inform	ation: Indicative, Ide	entifies the possibility of signif	icant uptake
	through the sl	kin		
	_	AGW	100 ppm	DE TRGS
			440 mg/m3	900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Skin absorption, European Union (The EU has estab-			
	lished a limit value: deviations in value and peak limit are possible), Senate			
	commission for the review of compounds at the work place dangerous for the			
	health (MAK-commission).			
4-methylpentan-2-	108-10-1	TWA	20 ppm	2000/39/EC
one			83 mg/m3	
	Further information: Indicative			
		STEL	50 ppm	2000/39/EC
			208 mg/m3	
	Further inform	ation: Indicative		

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version Revision Date: Print Date Date of last issue: -

1.0 12.01.2021 07.07.2023 Date of first issue: 12.01.2021

	AGW	20 ppm	DE TRGS	
		83 mg/m3	900	
Peak-lin	Peak-limit: excursion factor (category): 2;(I)			
tolerand Europea and pea	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Skin absorption, European Union (The EU has established a limit value: deviations in value and peak limit are possible), Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	xylene: 1,5 mg/l	Immediately after	TRGS 903
		(Blood)	exposure or after	
			working hours	
		methylhippuric acid	Immediately after	TRGS 903
		(all isomers): 2 g/l	exposure or after	
		(Urine)	working hours	
4-methylpentan-2-one	108-10-1	4-methylpentan-2-	Immediately after	TRGS 903
		one: 0,7 mg/l	exposure or after	
		(Urine)	working hours	

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
xylene	Consumers	Inhalation	Acute local effects	174,00 mg/m3
	Consumers	Skin contact	Long-term systemic effects	108,00 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	174,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	1,60 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	14,80 mg/m3
	Workers	Inhalation	Acute systemic effects	289,00 mg/m3
	Workers	Inhalation	Acute local effects	289,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	77,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	180,00 mg/kg bw/day
4-methylpentan-2-one	Consumers	Ingestion	Long-term systemic effects	4,20 mg/kg bw/day
	Consumers	Inhalation	Acute local effects	155,20 mg/m3
	Consumers	Inhalation	Acute systemic effects	155,20 mg/m3
	Consumers	Skin contact	Long-term systemic effects	4,20 mg/kg bw/day
	Consumers	Inhalation	Long-term local ef- fects	14,70 mg/m3

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version Revision Date: Print Date Date of last issue: -

1.0 12.01.2021 07.07.2023 Date of first issue: 12.01.2021

Consumers	Inhalation	Long-term systemic effects	14,70 mg/m3
Workers	Inhalation	Acute systemic effects	208,00 mg/m3
Workers	Inhalation	Acute local effects	208,00 mg/m3
Workers	Inhalation	Long-term systemic effects	83,00 mg/m3
Workers	Inhalation	Long-term local ef- fects	83,00 mg/m3
Workers	Skin contact	Long-term systemic effects	11,80 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
xylene	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Soil	2,31 mg/kg dry
		weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Marine water	0,327 mg/l
	Marine sediment	12,46 mg/kg dry
		weight (d.w.)
4-methylpentan-2-one	Sewage treatment plant	27,5 mg/l
	Fresh water	0,6 mg/l
	Intermittent use/release	1,5 mg/l
	Marine water	0,06 mg/l
	Soil	1,3 mg/kg dry weight (d.w.)
	Fresh water sediment	8,27 mg/kg dry weight (d.w.)
	Marine sediment	0,83 mg/kg dry weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye protection : German trade association rules - BGR 192 Eye protection

Tightly fitting safety goggles

Hand protection

Material : butyl-rubber Glove thickness : 0,3 mm Protective index : Class 3

Remarks : Gloves should be discarded and replaced if there is any indi-

cation of degradation or chemical breakthrough. Before re-

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version Revision Date: Print Date Date of last issue: -

1.0 12.01.2021 07.07.2023 Date of first issue: 12.01.2021

moving gloves clean them with soap and water. Wear suita-

ble gloves tested to EN374.

German trade association leaflet: Carry gloves (ZH 1/706)

Skin and body protection : Safety shoes

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.

During spray application: impervious clothing

Respiratory protection : When exceeding the WEL substance Limit a respiratory filter

Type A is necessary. Class 1 or 2 has to be chosen depend-

ing on the workplace concentration.

German trade association rules - BGR 190 Breathing protec-

tion

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : No data available

Odour : solvent-like

Odour Threshold : Not relevant

pH : 6,95

Concentration: 10 %

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Flash point : 28 °C

Evaporation rate : not determined

Upper explosion limit / Upper : not determined

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version **Revision Date:** Print Date Date of last issue: -

07.07.2023 1.0 12.01.2021 Date of first issue: 12.01.2021

flammability limit

Lower explosion limit / Lower : not determined

flammability limit

Vapour pressure not determined

Relative vapour density not determined

Relative density not determined

0,866 g/cm3 Density

Solubility(ies)

Water solubility not determined

Partition coefficient: n-

octanol/water

not determined

Auto-ignition temperature not determined

Decomposition temperature No data available

Viscosity

Viscosity, dynamic No data available

Explosive properties Not applicable

Oxidizing properties Not applicable

9.2 Other information

Flammability (liquids) Sustains combustion

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid Protect from frost, heat and sunlight.

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version Revision Date: Print Date Date of last issue: -

1.0 12.01.2021 07.07.2023 Date of first issue: 12.01.2021

10.5 Incompatible materials

Materials to avoid : Acids

Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute inhalation toxicity : Acute toxicity estimate: 8242 ppm

Exposure time: 4 h
Test atmosphere: gas
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Remarks: Based on available data, the classification criteria

are not met.

Components:

xylene:

Acute inhalation toxicity : LC50 (Rat): 5000 ppm

Exposure time: 4 h Test atmosphere: gas

Skin corrosion/irritation

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system

and the skin.

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version **Revision Date:** Print Date Date of last issue: -

07.07.2023 Date of first issue: 12.01.2021 1.0 12.01.2021

Respiratory or skin sensitisation

Product:

Remarks No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version Revision Date: Print Date Date of last issue: -

1.0 12.01.2021 07.07.2023 Date of first issue: 12.01.2021

cling.

Waste Code : used product

080111*, waste paint and varnish containing organic solvents

or other dangerous substances

SECTION 14: Transport information

14.1 UN number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

Not permitted for transport

14.2 UN proper shipping name

ADN : PAINT RELATED MATERIAL
ADR : PAINT RELATED MATERIAL
RID : PAINT RELATED MATERIAL
IMDG : PAINT RELATED MATERIAL
IATA : PAINT RELATED MATERIAL
Not permitted for transport

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA (Cargo) : 3

IATA (Passenger) : Not permitted for transport

14.4 Packing group

ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version Revision Date: Print Date Date of last issue: -

1.0 12.01.2021 07.07.2023 Date of first issue: 12.01.2021

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo) : Not permitted for transport

IATA (Passenger) : Not permitted for transport

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

This product is a mixture and does not contain Substances of Very High

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version Revision Date: Print Date Date of last issue: -

1.0 12.01.2021 07.07.2023 Date of first issue: 12.01.2021

Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener-

ated.

REACH - List of substances subject to authorisation : None

(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLÄMMABLE LIQUIDS

E2 ENVIRONMENTAL

HAZARDS

34 Petroleum products: (a)

gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in

points (a) to (d)

: M-VM04 Special thinners

Volatile organic compounds : < 100 %

< 870 g/l

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version Revision Date: Print Date Date of last issue: -

1.0 12.01.2021 07.07.2023 Date of first issue: 12.01.2021

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour. H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Irrit. : Skin irritation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 903 : TRGS 903 - Biological limit values

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; EMS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; IECSC - Inventory of Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population; LD50 - Lethal Dose to 50% of a test population; LD50 - Lethal Dose to 50% of a test population; Chemicals Inventory; LC50 - Lethal Concentration in Convention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observed (Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemicals Safety and Pollution Prevention; PBT - Persistent, Biotac

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version Revision Date: Print Date Date of last issue: -

1.0 12.01.2021 07.07.2023 Date of first issue: 12.01.2021

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Safety Data Sheet:

H304

H411

ECHA WebSite

Asp. Tox. 1

Aquatic Chronic 2

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Expo-

sure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture:

Flam. Liq. 3 H226 Based on product data or assessment Acute Tox. 4 H332 Calculation method Skin Irrit. 2 H315 Calculation method Eye Irrit. 2 H319 Calculation method STOT SE 3 H336 Calculation method STOT SE 3 H335 Calculation method STOT RE 2 H373 Calculation method

Classification procedure:

Calculation method

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

according to Regulation (EC) No. 1907/2006



DisboADD 995

Version Revision Date: Print Date Date of last issue: -

1.0 12.01.2021 07.07.2023 Date of first issue: 12.01.2021

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN