according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : DisboCOR 876 Comp. A Sonderton

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-

Polyurethane-resin-based coating material, solvent-containing

stance/Mixture

Recommended restrictions

within adequate application - none

on use

1.3 Details of the supplier of the safety data sheet

Company : Disbon GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710 Telefax : +4961547170222

E-mail address Responsi-

ble/issuing person

: msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapor.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Specific target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure.

Long-term (chronic) aquatic hazard, Cat-H412: Harmful to aquatic life with long lasting ef-

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

egory 3 fects.

#### 2.2 Label elements

## Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :







Signal Word : Warning

Hazard Statements: H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or

repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P260 Do not breathe vapours/ spray.

P262 Do not get in eyes, on skin, or on clothing. P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

### Hazardous ingredients which must be listed on the label:

Reaction mass of ethylbenzene and m-xylene and p-xylene

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified

### **Additional Labeling**

EUH208

Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, methacrylic acid, monoester with propane-1,2-diol, n-butyl acrylate, methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

# 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : 2-C-PUR top coat

# Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Reaction mass of ethylbenzene and m-xylene and p-xylene	Not Assigned 01-2119488216-32, 01-2119555267-33	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335 (respiratory tract irritation) STOT RE 2; H373 (hearing organs)	>= 10 - < 20
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	64742-95-6 265-199-0 649-356-00-4 01-2119455851-35, 01-2119486773-24	STOT SE 3; H336 STOT SE 3; H335 Aquatic Chronic 2; H411 Asp. Tox. 1; H304 Flam. Liq. 3; H226 EUH066	>= 2,5 - < 10
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 1 - < 10
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous	>= 1 - < 10

according to Regulation (EC) No. 1907/2006



DE / EN

# DisboCOR 876 Comp. A Sonderton

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

1	01-2119475791-29	system)	1 1
bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate	41556-26-7 255-437-1 01-2119491304-40	Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Repr. 2; H361f	>= 0,25 - < 1
methacrylic acid, monoester with propane-1,2-diol	27813-02-1 248-666-3 607-125-00-5 01-2119490226-37	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 0,1 - < 1
n-butyl acrylate	141-32-2 205-480-7 607-062-00-3 01-2119453155-43	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 0,1 - < 1
styrene	100-42-5 202-851-5 601-026-00-0 01-2119457861-32, 01-2120762099-46	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT RE 1; H372 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 0,1 - < 0,25
methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	82919-37-7 280-060-4	Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Repr. 2; H361f M-Factor (Acute	>= 0,1 - < 0,25
Substances with a workplace even	laura limit :	aquatic toxicity): 1	
Substances with a workplace exportance (Mg3H2(SiO3)4)	14807-96-6 238-877-9 01-2120140278-58		>= 1 - < 10
Quartz (SiO2)	14808-60-7 238-878-4 01-2120770509-45		>= 1 - < 10

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

### **SECTION 4: First aid measures**

#### 4.1 Description of first-aid measures

General advice : Show this material safety data sheet to the doctor in attend-

ance.

When symptoms persist or in all cases of doubt seek medical

advice.

Move out of dangerous area. First aider needs to protect himself.

Never give anything by mouth to an unconscious person.

If inhaled : Call a physician.

If breathing is irregular or stopped, administer artificial respira-

tion.

If unconscious, place in recovery position and seek medical

advice

If symptoms persist, call a physician.

Move to fresh air.

In case of skin contact : Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

Take off all contaminated clothing immediately.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

If accidentally swallowed obtain immediate medical attention.

If swallowed, DO NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

Causes serious eye irritation. May cause respiratory irritation.

May cause damage to organs through prolonged or repeated

exposure.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

according to Regulation (EC) No. 1907/2006



DE / EN

# DisboCOR 876 Comp. A Sonderton

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

Water

## 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

Cool closed containers exposed to fire with water spray. In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

# 5.3 Advice for firefighters

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Standard procedure for chemical fires.

In the event of fire and/or explosion do not breathe fumes.

# **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition.

### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent

material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13).

#### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

# **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Avoid exceeding the given occupational exposure limits (see

section 8).

Provide sufficient air exchange and/or exhaust in work rooms. Contains isocyanates. Please, attend to producer's advice. Liquid product may irritate and sensitize skin and respiratory tract and may cause allergic reaction. Do not inhale vapours. Take care for sufficient fresh air supply during and after use. Product must not be sprayed. Allergics or persons tending to respiratory tract diseases must not be involved in operations

with this product.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Advice on protection against

fire and explosion

Vapors may form explosive mixtures with air. Vapors are heavier than air and may spread along floors. Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Hygiene measures : Keep working clothes separately. Remove and wash contami-

nated clothing before re-use. Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering

eating areas.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 3

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

7.3 Specific end use(s)

Specific use(s) : This information is not available.

# **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

## **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Reaction mass of ethylbenzene and m-xylene and p-xylene	Not Assigned	TWA	50 ppm 221 mg/m3	2000/39/EC
	Further inform through the sl	kin	entifies the possibility of signi	•
		STEL	100 ppm 442 mg/m3	2000/39/EC
	Further inform through the sl		entifies the possibility of signi	ficant uptake
		AGW	100 ppm 440 mg/m3	DE TRGS 900
	Peak-limit cat			
	Further information: Skin absorption, European Union (The EU has estab lished a limit value: deviations in value and peak limit are possible), Sena commission for the review of compounds at the work place dangerous for health (MAK-commission).			ible), Senate
		AGW	200 mg/m3	DE TRGS 900
	Peak-limit cat			
	Further information: See also No. 2.9 of the TRGS 900, Commission for dangerous substances, Group exposure limit for hydrocarbon solvent mixtures			
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m3	2019/1831/E U
	Further inform	nation: Indicative		
		TWA	50 ppm 241 mg/m3	2019/1831/E U
	Further inform	nation: Indicative		
		AGW	62 ppm 300 mg/m3	DE TRGS 900
	Peak-limit cat	egory: 2;(I)		
	Further inform	nation: When there is	s compliance with the OEL are of harming the unborn child	nd biological
2-methoxy-1- methylethyl ace-	108-65-6	STEL	100 ppm 550 mg/m3	2000/39/EC

according to Regulation (EC) No. 1907/2006



DE / EN

# DisboCOR 876 Comp. A Sonderton

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

tate	I					
	Further inform		possibility of significant uptal	ke through the		
	SKIII, IIIUICALIV	TWA	50 ppm 275 mg/m3	2000/39/EC		
	Further inform		possibility of significant uptal	ke through the		
	Skiii, ilidicativ	AGW	50 ppm 270 mg/m3	DE TRGS 900		
	Peak-limit cat	egory: 1:(I)		1000		
	Further inform	nation: When there is	s compliance with the OEL are of harming the unborn child	nd biological		
Talc (Mg3H2(SiO3)4)	14807-96-6	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900		
, , ,	Peak-limit cat	egory: 2;(II)		-		
			s compliance with the OEL are of harming the unborn child	nd biological		
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900		
	Peak-limit category: 2;(II)					
	Further inform	nation: When there is	s compliance with the OEL are of harming the unborn child	nd biological		
		BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527		
Quartz (SiO2)	14808-60-7	TWA (Respirable dust)	0,1 mg/m3	2004/37/EC		
	Further inform	nation: Carcinogens	or mutagens			
n-butyl acrylate	141-32-2	TWA	2 ppm 11 mg/m3	2000/39/EC		
	Further inform	nation: Indicative	,			
		STEL	10 ppm 53 mg/m3	2000/39/EC		
	Further inform	nation: Indicative				
		AGW	2 ppm 11 mg/m3	DE TRGS 900		
	Peak-limit cat	egory: 2;(I)		1		
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child,					
styrene	100-42-5	nsitizing through the AGW	20 ppm 86 mg/m3	DE TRGS 900		
	Peak-limit cat	edory: 5:(II)	00 mg/m3	300		
	Peak-limit category: 2;(II)  Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child					

# **Biological occupational exposure limits**

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Reaction mass of	Not As-	xvlene: 1.5 mg/l	Immediately after	TRGS 903

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

VersionRevision Date:SDS Number:Date of last issue: 13.04.20222.011.01.20236023721Date of first issue: 01.02.2021

ethylbenzene and m- xylene and p-xylene	signed	(Blood)	exposure or after working hours	
		methylhippuric acid (all isomers): 2 g/l (Urine)	Immediately after exposure or after working hours	TRGS 903
styrene	100-42-5	mandelic acid + phenylglyoxylic acid: 600 mg/g Creatinine (Urine)	In case of long- term exposure: after more than one shift, Immedi- ately after expo- sure or after work- ing hours	TRGS 903

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health effects	Value
Reaction mass of ethylbenzene and m-xylene and p-xylene	Workers	Inhalation	Acute systemic effects	289,00 mg/m3
	Workers	Inhalation	Acute local effects	289,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	77,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	180,00 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	174,00 mg/m3
	Consumers	Inhalation	Acute local effects	174,00 mg/m3
	Consumers	Inhalation	Long-term systemic effects	14,80 mg/m3
	Consumers	Skin contact	Long-term systemic effects	108,00 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1,60 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	48,00 mg/m3
	Workers	Inhalation	Acute systemic effects	600,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	300 mg/m3
	Workers	Inhalation	Acute local effects	600 mg/m3
	Workers	Skin contact	Long-term systemic effects	7,00 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	12,00 mg/m3
	Consumers	Inhalation	Acute systemic effects	300 mg/m3
	Consumers	Inhalation	Long-term local ef-	35,7 mg/m3

according to Regulation (EC) No. 1907/2006



DE / EN

# DisboCOR 876 Comp. A Sonderton

VersionRevision Date:SDS Number:Date of last issue: 13.04.20222.011.01.20236023721Date of first issue: 01.02.2021

	1	1	fects	
	Consumers	Inhalation	Acute local effects	300 mg/m3
	Consumers	Skin contact	Long-term systemic effects	3,40 mg/kg bw/day
	Consumers	Skin contact	Acute systemic ef- fects	6 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	2 mg/kg bw/day
2-methoxy-1- methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275,00 mg/m3
	Workers	Inhalation	Acute local effects	550,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	796,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33,00 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	33,00 mg/m3
	Consumers	Skin contact	Long-term systemic effects	320,00 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	36,00 mg/kg bw/day
n-butyl acrylate	Workers	Inhalation	Long-term local ef- fects	11,00 mg/m3
	Workers	Skin contact	Acute local effects	0,28 mg/cm2
	Workers	Skin contact	Long-term local ef- fects	0,28 mg/cm2
styrene	Consumers	Inhalation	Acute systemic ef- fects	174,25 mg/m3
	Consumers	Skin contact	Long-term systemic effects	343,00 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2,10 mg/kg bw/day
	Consumers	Inhalation	Acute local effects	182,75 mg/m3
	Consumers	Inhalation	Long-term systemic effects	10,20 mg/m3
	Consumers	Inhalation	Long-term systemic effects	1,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	7,70 µg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	10,00 mg/m3
	Consumers	Inhalation	Acute local effects	10,00 mg/m3
	Consumers	Inhalation	Long-term local effects	1,00 mg/m3
	Workers	Inhalation	Acute systemic effects	289,00 mg/m3
	Workers	Inhalation	Acute systemic ef-	100,00 mg/m3

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

		1	fects	
Work	ers In	halation	Acute local effects	100,00 mg/m3
Work	ers In	halation	Acute local effects	306,00 mg/m3
Work	ers In	halation	Long-term systemic effects	100,00 mg/m3
Work	ers In	halation	Long-term systemic effects	85,00 mg/m3
Work	ers In	halation	Long-term local effects	100,00 mg/m3
Work	ers S	kin contact	Long-term systemic effects	406,00 mg/kg bw/day

# Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Soil	0,0903 mg/kg dry
		weight (d.w.)
	Sea sediment	0,0981 mg/kg dry
		weight (d.w.)
	Intermittent use/release	0,36 mg/l
	Sewage treatment plant	35,6 mg/l
	Sea water	0,018 mg/l
	Fresh water	0,18 mg/l
2-methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l
	Intermittent use/release	6,35 mg/l
	Sea sediment	0,329 mg/kg dry weight (d.w.)
	Fresh water sediment	3,29 mg/kg dry
	1 Tool Water Scament	weight (d.w.)
	Sewage treatment plant	100 mg/l
	Sea water	0,0635 mg/l
	Soil	0,29 mg/kg dry
		weight (d.w.)
n-butyl acrylate	Fresh water	0,00272 mg/l
	Sea water	0,00027 mg/l
	Soil	1 mg/kg dry weight (d.w.)
	Sewage treatment plant	3,5 mg/l
	Intermittent use/release	0,011 mg/l
	Sea sediment	0,00338 mg/kg dry weight (d.w.)
	Fresh water sediment	0,0338 mg/kg dry weight (d.w.)
styrene	Soil	0,146 mg/kg dry weight (d.w.)
	Fresh water	0,04 mg/l
	Sea sediment	0,418 mg/kg dry
		weight (d.w.)

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

Fresh water sediment	0,418 mg/kg dry weight (d.w.)
Sea water	0,04 mg/l
Fresh water	0,028 mg/l
Sea sediment	0,307 mg/kg dry weight (d.w.)
Intermittent use/release	0,04 mg/l
Fresh water sediment	0,614 mg/kg dry weight (d.w.)
Sewage treatment plant	5 mg/l
Sea water	0,014 mg/l
Soil	0,2 mg/kg dry weight (d.w.)

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Tightly fitting safety goggles

Hand protection

Material : butyl-rubber
Glove thickness : 0,3 mm
Protective index : Class 3
Wearing time : 30 min

Remarks : Gloves should be discarded and replaced if there is any indi-

cation of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suita-

ble gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes

Long sleeved clothing

Remove and wash contaminated clothing before re-use. Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, dis-

posable suits) to avoid exposed skin surfaces.

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Respiratory protection : When exceeding the WEL substance Limit a respiratory filter

Type A is necessary. Class 1 or 2 has to be chosen depend-

ing on the workplace concentration.

Do not use for spraying.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

# **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : No data available

Odor : No data available

Odor Threshold : Not relevant

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Flash point : 31 °C

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 6,95

Concentration: 10 %

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Flow time : > 60 s at 23 °C

Cross section: 6 mm Method: ISO 2431

Solubility(ies)

Water solubility : partly miscible

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

Partition coefficient: n-

octanol/water

: not determined

Vapor pressure : not determined

Relative density : not determined

Density : 1,2000 g/cm3

Relative vapor density : Heavier than air.

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : Sustains combustion

Evaporation rate : Not applicable

## **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Amines and alcohols cause exothermic reactions.

Mixture reacts slowly with water resulting in evolution of CO2.

10.4 Conditions to avoid

Conditions to avoid : Exposure to water vapor.

Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Amines

Incompatible with oxidizing agents. Incompatible with acids and bases.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

**Components:** 

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 14.000 mg/kg

### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

## Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

#### STOT-single exposure

May cause respiratory irritation.

### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

### **Aspiration toxicity**

Not classified based on available information.

#### 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

### **Components:**

### methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

M-Factor (Acute aquatic tox- : 1

icity)

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### **Components:**

#### n-butyl acetate:

Partition coefficient: n- : log Pow: 2,3 (25 °C)

octanol/water Method: OECD Test Guideline 117

# 2-methoxy-1-methylethyl acetate:

Partition coefficient: n- : log Pow: 1,2 (20 °C)

octanol/water Method: OECD Test Guideline 117

#### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

0.1% or higher.

#### 12.6 Endocrine disrupting properties

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

### **Product:**

Additional ecological infor-

mation

Harmful to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Uncured product residues and unpurified packaging should be

disposed of as hazardous waste.

Waste should not be disposed of via wastewater.

Material residues: Allow the basic substance to harden with

hardener and dispose of as paint waste.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080111\*, waste paint and varnish containing organic solvents

or other dangerous substances

# **SECTION 14: Transport information**

### 14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

### 14.2 UN proper shipping name

ADN : PAINT RELATED MATERIAL
ADR : PAINT RELATED MATERIAL
RID : PAINT RELATED MATERIAL
IMDG : PAINT RELATED MATERIAL

IATA : Paint related material

### 14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

# 14.4 Packing group

#### **ADN**

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

#### **ADR**

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

#### **RID**

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

#### **IMDG**

Packing group : III
Labels : 3
EmS Code : F-E, <u>S-E</u>

#### IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

355

IATA (Passenger)

Packing instruction (passen-

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

**ADN** 

Environmentally hazardous : no

**ADR** 

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 liters, not

goods/merchandise of Class 3

IMDG: Packages smaller than or equal to 450 liters, not

goods/merchandise of Class 3

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)  Conditions of restriction for the following entries should be considered: Number on list 3

diisooctyl 2,2'-

[(dioc-

tylstannylene)bis(thio)]diacetate

(Number on list 20)

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

This product is a mixture and does not contain Substances of Very High

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener-

ated.

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

: Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving

dangerous substances.

P5c FLAMMABLE LIQUIDS

34 Petroleum products: (a) gasolines

and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a)

to (d)

Water hazard class (Germa-

WGK 2 obviously hazardous to water

ny)

Classification according to AwSV, Annex 1 (5.2)

: PU30 PU systems, containing solvents, harmful

Volatile organic compounds : Directive 2004/42/EC

< 32 % < 380 g/l

# Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 876 Comp. A Sonderton**

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

regulations, where applicable.

#### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H226 : Flammable liquid and vapor.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H335
H336
H361d
May cause drowsiness or dizziness.
Suspected of damaging the unborn child.

H361f : Suspected of damaging fertility.

H372 : Causes damage to organs through prolonged or repeated

exposure.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.
 H411 : Toxic to aquatic life with long lasting effects.
 H412 : Harmful to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers

from the risks related to exposure to carcinogens or mutagens

at work

2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a

fifth list of indicative occupational exposure limit values

according to Regulation (EC) No. 1907/2006



DE / EN

# DisboCOR 876 Comp. A Sonderton

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 2.0 11.01.2023 6023721 Date of first issue: 01.02.2021

DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 903 : TRGS 903 - Biological limit values

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit 2004/37/EC / TWA : Long term exposure limit 2019/1831/EU / TWA : Limit Value - eight hours 2019/1831/EU / STEL : Short term exposure limit DE TRGS 527 / BM : Assessment scale

DE TRGS 527 / BM : Assessment scale
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AlIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELX - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; CDCD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persi

#### **Further information**

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

# Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

### Classification of the mixture:

Classification procedure:

according to Regulation (EC) No. 1907/2006



DE / EN

DisboC	DisboCOR 876 Comp. A Sonderton						
Version 2.0	Revision Date: 11.01.2023	SDS Number: 6023721	Date of last issue: 13.04.2022 Date of first issue: 01.02.2021				
Flam.	. Liq. 3	H226	Based on product data or assessment				
Skin I	rrit. 2	H315	Calculation method				
Eye lı	rrit. 2	H319	Calculation method				
STOT	SE 3	H335	Calculation method				
STOT	TRE 2	H373	Calculation method				
Aqua	tic Chronic 3	H412	Calculation method				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### **REACH Information**

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN