according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 11.01.2023 6020741 Date of first issue: 23.07.2020 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name DisboCOR 875 Basis Eisenglimmer

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-Polyurethane-resin-based coating material, solvent-containing

stance/Mixture

Recommended restrictions

on use

within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Disbon GmbH

> Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710 Telefax +4961547170222

E-mail address Responsi-

ble/issuing person

: msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapor.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single ex-

posure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Specific target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure.

Long-term (chronic) aquatic hazard, Cat-H412: Harmful to aquatic life with long lasting ef-

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 11.01.2023 6020741 Date of first issue: 23.07.2020 3.0

egory 3 fects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal Word Warning

Hazard Statements H226 Flammable liquid and vapor.

> Causes skin irritation. H315

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or

repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P260 Do not breathe vapours/ spray.

P262 Do not get in eyes, on skin, or on clothing. P264 Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area. P271

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

Reaction mass of ethylbenzene and m-xylene and p-xylene

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified

Additional Labeling

EUH208

Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, methacrylic acid, monoester with propane-1,2-diol, n-butyl acrylate, methyl 1,2,2,6,6pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : 2-C-PUR EG top coat

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Reaction mass of ethylbenzene and m-xylene and p-xylene	Not Assigned 01-2119488216-32, 01-2119555267-33	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335 (respiratory tract irritation) STOT RE 2; H373 (hearing organs)	>= 10 - < 20
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 1 - < 10
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	64742-95-6 265-199-0 649-356-00-4 01-2119455851-35, 01-2119486773-24	STOT SE 3; H336 STOT SE 3; H335 Aquatic Chronic 2; H411 Asp. Tox. 1; H304 Flam. Liq. 3; H226 EUH066	>= 2,5 - < 10
bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate	41556-26-7 255-437-1 01-2119491304-40	Skin Sens. 1; H317 Aquatic Acute 1; H400	>= 0,25 - < 1

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

		Aquatic Chronic 1; H410 Repr. 2; H361f	
methacrylic acid, monoester with propane-1,2-diol	27813-02-1 248-666-3 607-125-00-5 01-2119490226-37	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 0,1 - < 1
n-butyl acrylate	141-32-2 205-480-7 607-062-00-3 01-2119453155-43	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 0,1 - < 1
methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	82919-37-7 280-060-4	Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Repr. 2; H361f M-Factor (Acute aquatic toxicity): 1	>= 0,1 - < 0,25
Substances with a workplace exposure limit :			
Talc (Mg3H2(SiO3)4)	14807-96-6 238-877-9 01-2120140278-58		>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Show this material safety data sheet to the doctor in attend-

ance.

When symptoms persist or in all cases of doubt seek medical

advice.

Move out of dangerous area. First aider needs to protect himself.

Never give anything by mouth to an unconscious person.

If inhaled : Call a physician.

If breathing is irregular or stopped, administer artificial respira-

tion.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

Move to fresh air.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

In case of skin contact : Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

Take off all contaminated clothing immediately.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

If accidentally swallowed obtain immediate medical attention.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

Causes serious eye irritation. May cause respiratory irritation.

May cause damage to organs through prolonged or repeated

exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

Water

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

Cool closed containers exposed to fire with water spray.
 In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

for fire-fighters

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Standard procedure for chemical fires.

In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent

material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Avoid exceeding the given occupational exposure limits (see

section 8).

Provide sufficient air exchange and/or exhaust in work rooms. Contains isocyanates. Please, attend to producer's advice. Liquid product may irritate and sensitize skin and respiratory tract and may cause allergic reaction. Do not inhale vapours. Take care for sufficient fresh air supply during and after use. Product must not be sprayed. Allergics or persons tending to

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

respiratory tract diseases must not be involved in operations

with this product.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Advice on protection against

fire and explosion

Vapors may form explosive mixtures with air. Vapors are heavier than air and may spread along floors. Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Hygiene measures : Keep working clothes separately. Remove and wash contami-

nated clothing before re-use. Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering

eating areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 3

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Reaction mass of ethylbenzene and m-xylene and p-xylene	Not As- signed	TWA	50 ppm 221 mg/m3	2000/39/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			icant uptake
		STEL	100 ppm 442 mg/m3	2000/39/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		AGW	100 ppm	DE TRGS

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

			440 mg/m3	900	
	Peak-limit ca	tegory: 2;(II)		l	
	Further informalished a limit commission	nation: Skin absorptivalue: deviations in	ion, European Union (The E value and peak limit are pos apounds at the work place d	sible), Senate	
	Tieaitii (WAK	AGW	200 mg/m3	DE TRGS 900	
	Peak-limit ca	tegory: 2;(II)		000	
	Further inform	nation: See also No.	2.9 of the TRGS 900, Comure limit for hydrocarbon sol	mission for dan- vent mixtures	
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m3	2019/1831/E U	
	Further inform	nation: Indicative			
		TWA	50 ppm 241 mg/m3	2019/1831/E U	
	Further inform	nation: Indicative		•	
		AGW	62 ppm 300 mg/m3	DE TRGS 900	
	Peak-limit ca	tegory: 2;(I)			
	Further information tolerance val	mation: When there i ues, there is no risk	s compliance with the OEL a of harming the unborn child	and biological	
Talc (Mg3H2(SiO3)4)	14807-96-6	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900	
	Peak-limit category: 2;(II)				
	Further information: When there is compliance with the OEL and biologic tolerance values, there is no risk of harming the unborn child		_		
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900	
	Peak-limit category: 2;(II)				
			s compliance with the OEL a of harming the unborn child	and biological	
		BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527	
n-butyl acrylate	141-32-2	TWA	2 ppm 11 mg/m3	2000/39/EC	
	Further information: Indicative				
		STEL	10 ppm 53 mg/m3	2000/39/EC	
	Further information: Indicative				
		AGW	2 ppm 11 mg/m3	DE TRGS 900	
	Peak-limit category: 2;(I)				
	Further informand biological	nation: Skin absorpt	ion, When there is complian here is no risk of harming th e skin		

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Reaction mass of	Not As-	xylene: 1,5 mg/l	Immediately after	TRGS 903
ethylbenzene and m-	signed	(Blood)	exposure or after	
xylene and p-xylene			working hours	
		methylhippuric acid	Immediately after	TRGS 903
		(all isomers): 2 g/l	exposure or after	
		(Urine)	working hours	

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo-		
(5.000)		sure	fects	0.00
Hematite (Fe2O3)	Consumers	Inhalation	Acute systemic effects	0,09 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0,00 mg/kg bw/day
	Consumers	Ingestion	Acute systemic ef- fects	0,00 mg/kg bw/day
	Workers	Inhalation	Acute systemic ef- fects	0,18 mg/m3
Reaction mass of ethylbenzene and m-xylene and p-xylene	Workers	Inhalation	Acute systemic effects	289,00 mg/m3
	Workers	Inhalation	Acute local effects	289,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	77,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	180,00 mg/kg bw/day
	Consumers	Inhalation	Acute systemic ef- fects	174,00 mg/m3
	Consumers	Inhalation	Acute local effects	174,00 mg/m3
	Consumers	Inhalation	Long-term systemic effects	14,80 mg/m3
	Consumers	Skin contact	Long-term systemic effects	108,00 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1,60 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	48,00 mg/m3
	Workers	Inhalation	Acute systemic effects	600,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	300 mg/m3
	Workers	Inhalation	Acute local effects	600 mg/m3
	Workers	Skin contact	Long-term systemic effects	7,00 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic	12,00 mg/m3

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

		1	effects	
	Consumers	Inhalation	Acute systemic ef- fects	300 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	35,7 mg/m3
	Consumers	Inhalation	Acute local effects	300 mg/m3
	Consumers	Skin contact	Long-term systemic effects	3,40 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	6 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	2 mg/kg bw/day
n-butyl acrylate	Workers	Inhalation	Long-term local ef- fects	11,00 mg/m3
	Workers	Skin contact	Acute local effects	0,28 mg/cm2
	Workers	Skin contact	Long-term local ef- fects	0,28 mg/cm2

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Hematite (Fe2O3)	Fresh water	0,32 µg/l
	Secondary Poisoning	0,43 mg/kg food
	Sewage treatment plant	1,9 mg/l
n-butyl acetate	Fresh water sediment	0,981 mg/kg dry
		weight (d.w.)
	Soil	0,0903 mg/kg dry
		weight (d.w.)
	Sea sediment	0,0981 mg/kg dry
		weight (d.w.)
	Intermittent use/release	0,36 mg/l
	Sewage treatment plant	35,6 mg/l
	Sea water	0,018 mg/l
	Fresh water	0,18 mg/l
n-butyl acrylate	Fresh water	0,00272 mg/l
	Sea water	0,00027 mg/l
	Soil	1 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	3,5 mg/l
	Intermittent use/release	0,011 mg/l
	Sea sediment	0,00338 mg/kg
		dry weight (d.w.)
	Fresh water sediment	0,0338 mg/kg dry
		weight (d.w.)

8.2 Exposure controls

Personal protective equipment

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Tightly fitting safety goggles

Hand protection

Material : butyl-rubber
Glove thickness : 0,3 mm
Protective index : Class 3
Wearing time : 30 min

Remarks : Gloves should be discarded and replaced if there is any indi-

cation of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suita-

ble gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes

Long sleeved clothing

Remove and wash contaminated clothing before re-use. Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, dis-

posable suits) to avoid exposed skin surfaces.

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Respiratory protection : When exceeding the WEL substance Limit a respiratory filter

Type A is necessary. Class 1 or 2 has to be chosen depend-

ing on the workplace concentration.

Do not use for spraying.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : black

No data available

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

Odor : No data available

Odor Threshold : Not relevant

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Flash point : 30 °C

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 6,95

Concentration: 10 %

Viscosity

Viscosity, dynamic : 3.000 mPa.s

No data available

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Method: ISO 3219

Flow time : > 60 s at 23 °C

Cross section: 6 mm Method: ISO 2431

Solubility(ies)

Water solubility : partly miscible

Partition coefficient: n-

octanol/water

not determined

Vapor pressure : not determined

Relative density : not determined

Density : 1,4820 g/cm3

Relative vapor density : Heavier than air.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : Sustains combustion

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Amines and alcohols cause exothermic reactions.

Mixture reacts slowly with water resulting in evolution of CO2.

10.4 Conditions to avoid

Conditions to avoid : Exposure to water vapor.

Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Amines

Incompatible with oxidizing agents. Incompatible with acids and bases.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

Method: Calculation method

Components:

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 14.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

SECTION 12: Ecological information

12.1 Toxicity

Components:

methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

M-Factor (Acute aquatic tox- : 1

icity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

n-butyl acetate:

Partition coefficient: n- : log Pow: 2,3 (25 °C)

octanol/water Method: OECD Test Guideline 117

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

Harmful to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Uncured product residues and unpurified packaging should be

disposed of as hazardous waste.

Waste should not be disposed of via wastewater.

Material residues: Allow the basic substance to harden with

hardener and dispose of as paint waste.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080111*, waste paint and varnish containing organic solvents

or other dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT RELATED MATERIAL
ADR : PAINT RELATED MATERIAL
RID : PAINT RELATED MATERIAL
IMDG : PAINT RELATED MATERIAL

IATA : Paint related material

14.3 Transport hazard class(es)

Class Subsidiary risks

 ADN
 : 3

 ADR
 : 3

 RID
 : 3

 IMDG
 : 3

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

IATA : 3

14.4 Packing group

ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen: 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 11.01.2023 6020741 Date of first issue: 23.07.2020 3.0

14.6 Special precautions for user

Remarks ADR: Packages smaller than or equal to 450 liters, not

goods/merchandise of Class 3

IMDG: Packages smaller than or equal to 450 liters, not

goods/merchandise of Class 3

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

diisooctyl 2,2'-[(dioc-

tylstannylene)bis(thio)]diacetate

(Number on list 20)

REACH - Candidate List of Substances of Very High

Concern for Authorization (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener-

ated.

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving

P5c FLAMMABLE LIQUIDS

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 11.01.2023 6020741 Date of first issue: 23.07.2020 3.0

dangerous substances.

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same

> purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a)

to (d)

ny)

Water hazard class (Germa- : WGK 2 obviously hazardous to water

Classification according to AwSV, Annex 1 (5.2)

: PU30 PU systems, containing solvents, harmful

Volatile organic compounds : Directive 2004/42/EC

> < 30 % < 440 g/l

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H226 Flammable liquid and vapor. H304 May be fatal if swallowed and enters airways. Harmful in contact with skin. H312 H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

Harmful if inhaled. H332

May cause respiratory irritation. H335 H336 May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

H361f : Suspected of damaging fertility.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a

fifth list of indicative occupational exposure limit values

DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 903 : TRGS 903 - Biological limit values

2000/39/EC / TWA: Limit Value - eight hours2000/39/EC / STEL: Short term exposure limit2019/1831/EU / TWA: Limit Value - eight hours2019/1831/EU / STEL: Short term exposure limit

DE TRGS 527 / BM : Assessment scale
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AlIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EMS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Cori Civil Aviation Organization; IECSC - Inventry of Existing Chemical Substances in China; IMDG - International Maritime Dargerous Goods; IMO - International Maritime Organization; IECSC - Inventry of Existing Chemicals Substances in China; IMDG - International Maritime Dargerous Goods; IMO - International Convention for the Prevention to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observed (Adverse) Effect Concentration; DO (A)EL - No Observed (Adverse) Effect Level; NOELR - No Observed (Adverse) Effect Concentration and Development; OPPTS - Office of Chemical Safe

Further information

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture:

Classification procedure:

Flam. Liq. 3	H226	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 875 Basis Eisenglimmer

Version Revision Date: SDS Number: Date of last issue: 13.04.2022 3.0 11.01.2023 6020741 Date of first issue: 23.07.2020

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN