according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6021066 Date of first issue: 04.09.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : DisboCOR 863 Sonderton

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Solvent-borne coatings

stance/Mixture

Recommended restrictions

on use

within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Disbon GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710 Telefax : +4961547170222

Website

E-mail address Responsi-

ble/issuing person

: msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapor.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single exH336: May cause drowsiness or dizziness.

Specific target organ toxicity - single exposure, Category 3, Central nervous

posure, Category 3, Central hervous

system

Specific target organ toxicity - repeated exposure, Category 2

Tiodo. May daded dreweineds of dizzineds.

H373: May cause damage to organs through pro-

longed or repeated exposure.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6.0 04.07.2023 6021066 Date of first issue: 04.09.2020

Long-term (chronic) aquatic hazard, Cat-H411: Toxic to aquatic life with long lasting effects. egory 2

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :







Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or

repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P260 Do not breathe vapours/ spray.

P262 Do not get in eyes, on skin, or on clothing.
P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha 2-methoxy-1-methylethyl acetate

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6.0 04.07.2023 6021066 Date of first issue: 04.09.2020

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : 1-C-EG universal coating, actively pigmented

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
Naphtha (petroleum), hydrotreat-	64742-48-9	Flam. Liq. 3; H226	>= 10 - < 20
ed heavy; Low boiling point ydro-	265-150-3	STOT SE 3; H336	
gen treated naphtha	649-327-00-6	Asp. Tox. 1; H304	
	01-2119457273-39,	EUH066	
	01-2119463258-33		
naphtha (petroleum), hydrodesul-	64742-82-1	Flam. Liq. 3; H226	>= 2,5 - < 10
phurized heavy; Low boiling point	265-185-4	STOT SE 3; H336	
hydrogen treated naphtha	649-330-00-2	Asp. Tox. 1; H304	
	01-2119458049-33,	Aquatic Chronic 2;	
	01-2119473977-17,	H411	
	01-2119463586-28	STOT RE 1; H372	
		(Central nervous	
		system)	
		EUH066	
O see the see the left of the see tests	100.05.0	Flore Lie o 11000	4 40
2-methoxy-1-methylethyl acetate	108-65-6	Flam. Liq. 3; H226	>= 1 - < 10
	203-603-9	STOT SE 3; H336	
	607-195-00-7	(Central nervous	
butan-1-ol	01-2119475791-29 71-36-3	system) Flam. Liq. 3; H226	>= 1 - < 3
Dulan-1-01	200-751-6	Acute Tox. 4; H302	>= 1 - < 3
	603-004-00-6	Skin Irrit. 2; H315	
	01-2119484630-38,	Eye Dam. 1; H318	
	01-2119464630-36,	STOT SE 3; H336	
	01-2120070404-50	STOT SE 3; H335	
zinc oxide	1314-13-2		>= 1 - < 2,5
ZITIC UXIUE	215-222-5	Aquatic Acute 1; H400	>= 1 - < 2,5
	030-013-00-7	Aquatic Chronic 1;	
	030-013-00-1	Aqualic Official 1,	

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6021066 Date of first issue: 04.09.2020

trizinc bis(orthophosphate)	01-2119463881-32, 01-2120089607-43, 01-2120767291-53 7779-90-0 231-944-3	H410 Aquatic Acute 1; H400	>= 1 - < 2,5	
	030-011-00-6 01-2119485044-40	Aquatic Chronic 1; H410		
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40	Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Repr. 2; H361f	>= 1 - < 2,5	
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)	123-26-2 204-613-6 01-2119978265-26	Skin Sens. 1B; H317 Aquatic Chronic 3; H412 specific concentration limit Skin Sens. 1B; H317 > 25 %	>= 0,1 - < 0,25	
2-ethylhexanoic acid, zirconium salt	22464-99-9 245-018-1 01-2119979088-21	Repr. 1B; H360D	>= 0,1 - < 0,3	
Substances with a workplace exposure limit :				
barium sulfate	7727-43-7 231-784-4 01-2119491274-35		>= 1 - < 10	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled : Call a physician.

If breathing is irregular or stopped, administer artificial respira-

tion.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

Move to fresh air.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6021066 Date of first issue: 04.09.2020

In case of skin contact : Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water

Take off all contaminated clothing immediately.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed : Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated

exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Do not use a solid water stream as it may scatter and spread

fire.

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

: Cool closed containers exposed to fire with water spray. In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 04.07.2023 6021066 Date of first issue: 04.09.2020 6.0

5.3 Advice for firefighters

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Do not get in eyes, on skin, or on clothing.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Ensure adequate ventilation. Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Non-sparking tools should be used.

For personal protection see section 8.

Avoid exceeding the given occupational exposure limits (see

section 8).

Provide sufficient air exchange and/or exhaust in work rooms.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Advice on protection against

fire and explosion

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Keep away from

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6.0 04.07.2023 6021066 Date of first issue: 04.09.2020

heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Hygiene measures : Avoid contact with the skin and the eyes. Wash hands before

eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protec-

tive equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 3

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
Naphtha (petrole- um), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	AGW	300 mg/m3	DE TRGS 900	
	Peak-limit cat	egory: 2;(II)			
	Further inform	nation: Group exposu	re limit for hydrocarbon solv	ent mixtures	
barium sulfate	7727-43-7	AGW (Inhalable	10 mg/m3	DE TRGS	
		fraction)		900	
	Peak-limit category: 2;(II)				
	Further inform	ation: When there is	compliance with the OEL ar	nd biological	
	tolerance valu	es, there is no risk o	of harming the unborn child		
		AGW (Alveolate	1,25 mg/m3	DE TRGS	
		fraction)		900	
	Peak-limit cat	egory: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
		BM (Alveolar	0,5 mg/m3	DE TRGS	
		dust fraction)		527	
2-methoxy-1-	108-65-6	STEL	100 ppm	2000/39/EC	

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6.0 04.07.2023 6021066 Date of first issue: 04.09.2020

methylethyl ace-			550 mg/m3		
tate			_		
	Further inform skin, Indicativ		possibility of significant uptak	ce through the	
		TWA	50 ppm 275 mg/m3	2000/39/EC	
		Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 270 mg/m3	DE TRGS 900	
	Peak-limit cat	Peak-limit category: 1;(I)			
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
butan-1-ol	71-36-3	AGW	100 ppm 310 mg/m3	DE TRGS 900	
	Peak-limit cat	Peak-limit category: 1;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
butan-1-ol	71-36-3	1-butanol: 2 mg/g	Before next shift	TRGS 903
		Creatinine		
		(Urine)		
		1-butanol: 10 mg/g	Immediately after	TRGS 903
		Creatinine	exposure or after	
		(Urine)	working hours	

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health effects	Value
Hematite (Fe2O3)	Consumers	Inhalation	Acute systemic effects	0,09 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0,00 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	0,00 mg/kg bw/day
	Workers	Inhalation	Acute systemic effects	0,18 mg/m3
barium sulfate	Consumers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	13000,00 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Inhalation	Long-term local effects	10,00 mg/m3
2-methoxy-1- methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275,00 mg/m3

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6021066 Date of first issue: 04.09.2020

	Workers	Inhalation	Acute local effects	550,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	796,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33,00 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	33,00 mg/m3
	Consumers	Skin contact	Long-term systemic effects	320,00 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	36,00 mg/kg bw/day
butan-1-ol	Consumers	Inhalation	Long-term local ef- fects	55,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	3,13 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	310,00 mg/m3
zinc oxide	Consumers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,50 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	0,50 mg/m3
	Workers	Inhalation	Long-term systemic effects	5,00 mg/m3
trizinc bis(orthophosphate)	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,50 mg/m3
	Workers	Inhalation	Long-term systemic effects	5,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
Reaction mass of Bis(1,2,2,6,6- pentamethyl-4- piperidyl) sebacate and Methyl 1,2,2,6,6- pentamethyl-4- piperidyl sebacate	Consumers	Inhalation	Acute local effects	0,58 mg/m3
	Consumers	Ingestion	Long-term systemic effects	1,25 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic	0,58 mg/m3

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6021066 Date of first issue: 04.09.2020

			effects	
	Consumers	Inhalation	Acute systemic ef- fects	0,58 mg/m3
	Consumers	Skin contact	Long-term systemic effects	1,25 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	1,25 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	1,25 mg/kg bw/day
	Workers	Inhalation	Acute systemic effects	2,35 mg/m3
	Workers	Inhalation	Acute local effects	2,35 mg/m3
	Workers	Inhalation	Long-term systemic effects	2,35 mg/m3
	Workers	Skin contact	Acute systemic effects	2,50 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	2,50 mg/kg bw/day
N,N'-ethane-1,2- diylbis(12- hydroxyoctadecan-1- amide)	Consumers	Inhalation	Long-term local effects	0,83 mg/m3
	Workers	Inhalation	Long-term local ef- fects	3,35 mg/m3
2-ethylhexanoic acid, zirconium salt	Consumers	Inhalation	Long-term systemic effects	8,13 mg/m3
	Consumers	Skin contact	Long-term systemic effects	3,25 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4,51 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	6,49 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	32,97 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Hematite (Fe2O3)	Fresh water	0,32 μg/l
	Secondary Poisoning	0,43 mg/kg food
	Sewage treatment plant	1,9 mg/l
barium sulfate	Fresh water	115 μg/l
	Fresh water sediment	600,4 mg/kg dry weight (d.w.)
	Soil	207,7 mg/kg dry weight (d.w.)
	Sewage treatment plant	62,2 mg/l
2-methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l
	Intermittent use/release	6,35 mg/l
	Sea sediment	0,329 mg/kg dry

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6021066 Date of first issue: 04.09.2020

		weight (d.w.)
	Fresh water sediment	3,29 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 mg/l
	Sea water	0,0635 mg/l
	Soil	0,29 mg/kg dry
		weight (d.w.)
butan-1-ol	Sewage treatment plant	2476 mg/l
	Fresh water	0,082 mg/l
	Intermittent use/release	2,25 mg/l
	Fresh water sediment	0,178 mg/kg dry
		weight (d.w.)
	Sea water	0,0082 mg/l
	Sea sediment	0,0178 mg/kg dry
		weight (d.w.)
	Soil	0,015 mg/kg dry
		weight (d.w.)
zinc oxide	Fresh water sediment	117,8 mg/kg dry
		weight (d.w.)
	Sea water	6,1 µg/l
	Fresh water	20,6 μg/l
	Sea sediment	56,5 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 μg/l
	Soil	35,6 mg/kg dry
		weight (d.w.)
trizinc bis(orthophosphate)	Sea sediment	56,5 mg/kg dry
		weight (d.w.)
	Fresh water	20,6 μg/l
	Soil	35,6 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 μg/l
	Fresh water sediment	117,8 mg/kg dry
		weight (d.w.)
D # (D) (1.0.0.0.0	Sea water	6,1 µg/l
Reaction mass of Bis(1,2,2,6,6- pentamethyl-4-piperidyl) seba- cate and Methyl 1,2,2,6,6- pentamethyl-4-piperidyl sebacate	Sea water	0,00022 mg/l
	Soil	0,21 mg/kg dry
		weight (d.w.)
	Fresh water	0,0022 mg/l
	Sewage treatment plant	1 mg/l
	Fresh water sediment	1,05 mg/kg dry
		weight (d.w.)
	Intermittent use/release	0,009 mg/l
	Sea sediment	0,11 mg/kg dry
		weight (d.w.)
N,N'-ethane-1,2-diylbis(12-	Sewage treatment plant	0,1 mg/l

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6021066 Date of first issue: 04.09.2020

hydroxyoctadecan-1-amide)		
2-ethylhexanoic acid, zirconium salt	Fresh water	0,36 mg/l
	Sea sediment	0,637 mg/kg dry weight (d.w.)
	Intermittent use/release	0,493 mg/l
	Sea water	0,036 mg/l
	Soil	1,06 mg/kg dry weight (d.w.)
	Fresh water sediment	6,37 mg/kg dry weight (d.w.)
	Sewage treatment plant	71,7 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Tightly fitting safety goggles

Hand protection

Material : Nitrile rubber
Glove thickness : 0,2 mm
Protective index : Class 3

Remarks : Gloves should be discarded and replaced if there is any indi-

cation of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suita-

ble gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.

During spray application: impervious clothing

Respiratory protection : Roller application or brushing: This product should not be

used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to

standard EN 14387) is used.

DGUV Regulation 112-190 - Use of breathing equipment

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6.0 04.07.2023 6021066 Date of first issue: 04.09.2020

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : colorless

Odor : No data available

Odor Threshold : Not relevant

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Flash point : 38 °C

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 6,95

Concentration: 10 %

Viscosity

Viscosity, dynamic : 5,000 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : partly miscible

Partition coefficient: n-

octanol/water

: not determined

Vapor pressure : not determined

Relative density : not determined

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6.0 04.07.2023 6021066 Date of first issue: 04.09.2020

Density : 1,6060 g/cm3

Relative vapor density : Heavier than air.

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : Sustains combustion

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.

Hazardous decomposition products formed under fire condi-

tions.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6.0 04.07.2023 6021066 Date of first issue: 04.09.2020

Method: Calculation method

Components:

butan-1-ol:

Acute oral toxicity : LD50 (Rat): 790 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 3.430 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 04.07.2023 6021066 Date of first issue: 04.09.2020 6.0

SECTION 12: Ecological information

12.1 Toxicity

Components:

barium sulfate:

Toxicity to fish Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No toxicity at the limit of solubility.

Toxicity to algae/aquatic

plants

Remarks: No toxicity at the limit of solubility.

Toxicity to fish (Chronic tox-

icity)

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

Remarks: No toxicity at the limit of solubility.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Partition coefficient: nlog Pow: 1,99 - 18,02 (20 °C)

octanol/water pH: 7

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naph-

Partition coefficient: n-

log Pow: 1,99 - 18,02 (20 °C)

octanol/water pH: 7

2-methoxy-1-methylethyl acetate:

Partition coefficient: nlog Pow: 1,2 (20 °C)

Method: OECD Test Guideline 117 octanol/water

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6pentamethyl-4-piperidyl sebacate:

Partition coefficient: nlog Pow: 2,37 - 2,77 (25 °C)

octanol/water pH: 7,0

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6.0 04.07.2023 6021066 Date of first issue: 04.09.2020

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : .

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080112, waste paint and varnish other than those mentioned

in 08 01 11*

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1263 **ADR** : UN 1263

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6.0 04.07.2023 6021066 Date of first issue: 04.09.2020

RID : UN 1263 IMDG : UN 1263 IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT RELATED MATERIAL
ADR : PAINT RELATED MATERIAL
RID : PAINT RELATED MATERIAL
IMDG : PAINT RELATED MATERIAL

(zinc oxide, trizinc bis(orthophosphate))

IATA : Paint related material

14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III Labels : 3

EmS Code : F-E, <u>S-E</u>

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6.0 04.07.2023 6021066 Date of first issue: 04.09.2020

366

IATA (Cargo)

Packing instruction (cargo

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen- : 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener-

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6.0 04.07.2023 6021066 Date of first issue: 04.09.2020

ated.

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

: None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving

dangerous substances.

E2 ENVIRONMENTAL HAZARDS

P5c FLAMMABLE LIQUIDS

34 Petroleum products: (a) gasolines

and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a)

to (d)

Water hazard class (Germa-

ny)

WGK 2 obviously hazardous to water

Classification according to AwSV, Annex 1 (5.2)

: BSL60 Coating materials, solvent-based, carcinogenic ingre-

dients, classified

Volatile organic compounds : Directive 2004/42/EC

< 23 % < 370 g/l

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6.0 04.07.2023 6021066 Date of first issue: 04.09.2020

regulations, where applicable.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapor.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H360D : May damage the unborn child.
H361f : Suspected of damaging fertility.

H372 : Causes damage to organs through prolonged or repeated

exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.
 H411 : Toxic to aquatic life with long lasting effects.
 H412 : Harmful to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 903 : TRGS 903 - Biological limit values

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit DE TRGS 527 / BM : Assessment scale DE TRGS 900 / AGW : Time Weighted Average

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6.0 04.07.2023 6021066 Date of first issue: 04.09.2020

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AlIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; (EQD, No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EMS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International International Concentration; ICCO - International Concentration; ICCO - Lethal Dose to 50% of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals;

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture: Classification procedure: Flam. Liq. 3 Based on product data or assessment H226 Eye Irrit. 2 Calculation method H319 Skin Sens. 1 H317 Calculation method STOT SE 3 H336 Calculation method STOT RE 2 H373 Calculation method Aquatic Chronic 2 H411 Calculation method

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 863 Sonderton

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 6021066 Date of first issue: 04.09.2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN