according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : DisboCOR 871 Comp. A Rotbraun

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : epoxide-resin-based coating material, solvent-containing

stance/Mixture

Recommended restrictions

on use

within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Disbon GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710 Telefax : +4961547170222

E-mail address Responsi-

ble/issuing person

: msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapor.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure.

Long-term (chronic) aquatic hazard, Cat-

egory 2

H411: Toxic to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms









Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eve irritation.

H373 May cause damage to organs through prolonged or

repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P260 Do not breathe vapours/ spray.

P262 Do not get in eyes, on skin, or on clothing.P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

xylene

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	25068-38-6 500-033-5 603-074-00-8 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 specific concentration limit Eye Irrit. 2; H319 >= 5 % Skin Irrit. 2; H315 >= 5 %	>= 10 - < 20
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Asp. Tox. 1; H304 STOT RE 2; H373 Aquatic Chronic 3; H412	>= 10 - < 20
trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 10 - < 20
zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32, 01-2120089607-43, 01-2120767291-53	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 2,5 - < 10
1-methoxy-2-propanol	107-98-2 203-539-1 603-064-00-3	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 10

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

	01-2119457435-35		
ethylbenzene	100-41-4	Acute Tox. 4; H332	>= 1 - < 2,5
_	202-849-4	STOT RE 2; H373	
	601-023-00-4	Asp. Tox. 1; H304	
	01-2119489370-35	Aquatic Chronic 3;	
		H412	
		Flam. Liq. 2; H225	
butan-1-ol	71-36-3	Flam. Liq. 3; H226	>= 1 - < 3
	200-751-6	Acute Tox. 4; H302	
	603-004-00-6	Skin Irrit. 2; H315	
	01-2119484630-38,	Eye Dam. 1; H318	
	01-2120076484-50	STOT SE 3; H336	
		STOT SE 3; H335	
oxirane, mono[(C12-14-	68609-97-2	Skin Irrit. 2; H315	>= 1 - < 10
alkyloxy)methyl] derivs.	271-846-8	Skin Sens. 1; H317	
	603-103-00-4		
	01-2119485289-22		
Substances with a workplace e	xposure limit :	·	·
barium sulfate	7727-43-7		>= 20 - < 30
	231-784-4		
	01-2119491274-35		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled : Move to fresh air.

If symptoms persist, call a physician.

If unconscious, place in recovery position and seek medical

advice.

If breathing is irregular or stopped, administer artificial respira-

tion.

Call a physician.

In case of skin contact : Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

Take off all contaminated clothing immediately.

In case of eye contact : IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ phy-

sician.

If swallowed : Call a physician.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

May cause damage to organs through prolonged or repeated

exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

Cool closed containers exposed to fire with water spray. Hazardous decomposition products formed under fire condi-

tions.

5.3 Advice for firefighters

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Standard procedure for chemical fires.

In the event of fire and/or explosion do not breathe fumes.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Ensure adequate ventilation. Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Avoid exceeding the given occupational exposure limits (see

section 8).

Provide sufficient air exchange and/or exhaust in work rooms.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Advice on protection against :

fire and explosion

The product is flammable but not readily ignited.

Hygiene measures : Avoid contact with the skin and the eyes. Wash hands before

eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protec-

tive equipment before entering eating areas.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 3

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
barium sulfate	7727-43-7	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900
	Peak-limit cat	egory: 2;(II)		
			s compliance with the OEL ar	nd biological
	tolerance valu		of harming the unborn child	
		AGW (Alveolate	1,25 mg/m3	DE TRGS
		fraction)		900
	Peak-limit cat			
			s compliance with the OEL are of harming the unborn child	nd biological
		BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527
xylene	1330-20-7	TWA	50 ppm 221 mg/m3	2000/39/EC
	Further inform skin, Indicativ		possibility of significant uptal	ke through the
		STEL	100 ppm 442 mg/m3	2000/39/EC
	Further inform skin, Indicativ		possibility of significant uptal	ke through the
		AGW	50 ppm 220 mg/m3	DE TRGS 900
	Peak-limit cat	egory: 2;(II)		
		nation: Skin absorption	on	
1-methoxy-2- propanol	107-98-2	STEL	150 ppm 568 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

		TWA	100 ppm 375 mg/m3	2000/39/EC		
		Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		AGW	100 ppm 370 mg/m3	DE TRGS 900		
	Peak-limit ca	ategory: 2;(I)				
	Further infor	mation: When there i	s compliance with the OEL a of harming the unborn child	nd biological		
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m3	2000/39/EC		
	Further information: Identifies the possibility of signification skin, Indicative			ke through the		
		STEL	200 ppm 884 mg/m3	2000/39/EC		
		Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		AGW	20 ppm 88 mg/m3	DE TRGS 900		
	Peak-limit ca	Peak-limit category: 2;(II)				
		• • •	on, When there is complianc	e with the OEL		
	and biologic	and biological tolerance values, there is no risk of harming the unborn child				
butan-1-ol	71-36-3	AGW	100 ppm 310 mg/m3	DE TRGS 900		
	Peak-limit category: 1;(I)					
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child					

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
1-methoxy-2-propanol	107-98-2	1-Methoxypropan- 2-ol: 15 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
ethylbenzene	100-41-4	mandelic acid + phenylglyoxylic acid: 250 mg/g Creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903
butan-1-ol	71-36-3	1-butanol: 2 mg/g Creatinine (Urine)	Before next shift	TRGS 903
		1-butanol: 10 mg/g Creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health effects	Value
barium sulfate	Consumers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	13000,00 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Inhalation	Long-term local effects	10,00 mg/m3
reaction product: bi- sphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	Consumers	Skin contact	Long-term systemic effects	3,57 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	3,57 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	0,75 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,75 mg/kg bw/day
	Workers	Inhalation	Acute systemic effects	12,25 mg/m3
	Workers	Inhalation	Long-term systemic effects	12,25 mg/m3
	Workers	Skin contact	Acute systemic effects	8,33 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	8,33 mg/kg bw/day
xylene	Consumers	Inhalation	Acute local effects	174,00 mg/m3
	Consumers	Skin contact	Long-term systemic effects	108,00 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	174,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	1,60 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	14,80 mg/m3
	Workers	Inhalation	Acute systemic effects	289,00 mg/m3
	Workers	Inhalation	Acute local effects	289,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	77,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	180,00 mg/kg bw/day
trizinc bis(orthophosphate)	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

	Consumers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,50 mg/m3
	Workers	Inhalation	Long-term systemic effects	5,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
diiron trioxide	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
zinc oxide	Consumers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,50 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	0,50 mg/m3
	Workers	Inhalation	Long-term systemic effects	5,00 mg/m3
1-methoxy-2-propanol	Consumers	Inhalation	Long-term systemic effects	43,90 mg/m3
	Consumers	Skin contact	Long-term systemic effects	78,00 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	33,00 mg/kg bw/day
	Workers	Inhalation	Acute systemic ef- fects	553,50 mg/m3
	Workers	Inhalation	Acute local effects	553,50 mg/m3
	Workers	Inhalation	Long-term systemic effects	369,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	183,00 mg/kg bw/day
ethylbenzene	Consumers	Ingestion	Long-term systemic effects	1,60 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	15,00 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	884,00 mg/m3
	Workers	Inhalation	Acute local effects	293,00 mg/m3
	Workers	Inhalation	Acute local effects	884,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	77,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	442,00 mg/m3

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

	Workers	Inhalation	Long-term local effects	442,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	180,00 mg/kg bw/day
butan-1-ol	Consumers	Inhalation	Long-term local ef- fects	55,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	3,13 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	310,00 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
barium sulfate	Fresh water	115 μg/l
	Fresh water sediment	600,4 mg/kg dry
		weight (d.w.)
	Soil	207,7 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	62,2 mg/l
reaction product: bisphenol-A-	Fresh water sediment	0,996 mg/kg dry
(epichlorhydrin); epoxy resin		weight (d.w.)
(number average molecular		
weight ≤ 700)		
	Soil	0,196 mg/kg dry
		weight (d.w.)
	Sea sediment	0,0996 mg/kg dry
		weight (d.w.)
	Intermittent use/release	0,018 mg/l
	Fresh water	0,006 mg/l
	Secondary Poisoning	11 mg/kg food
	Sea water	0,0006 mg/l
	Sewage treatment plant	10 mg/l
xylene	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Soil	2,31 mg/kg dry
		weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Sea water	0,327 mg/l
	Sea sediment	12,46 mg/kg dry
		weight (d.w.)
trizinc bis(orthophosphate)	Sea sediment	56,5 mg/kg dry
		weight (d.w.)
	Fresh water	20,6 μg/l
	Soil	35,6 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 μg/l
	Fresh water sediment	117,8 mg/kg dry

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

		weight (d.w.)
	Sea water	6,1 µg/l
zinc oxide	Fresh water sediment	117,8 mg/kg dry
		weight (d.w.)
	Sea water	6,1 µg/l
	Fresh water	20,6 μg/l
	Sea sediment	56,5 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 μg/l
	Soil	35,6 mg/kg dry
		weight (d.w.)
1-methoxy-2-propanol	Fresh water sediment	52,3 mg/kg dry
, , ,		weight (d.w.)
	Intermittent use/release	100 mg/l
	Fresh water	10 mg/l
	Sea water	1 mg/l
	Sewage treatment plant	100 mg/l
	Sea sediment	5,2 mg/kg dry
		weight (d.w.)
	Soil	4,59 mg/kg dry
		weight (d.w.)
ethylbenzene	Intermittent use/release	0,1 mg/l
	Sewage treatment plant	9,6 mg/l
	Fresh water	0,1 mg/l
	Sea water	0,01 mg/l
	Fresh water sediment	13,7 mg/kg dry
		weight (d.w.)
	Soil	2,68 mg/kg dry
		weight (d.w.)
	Sea sediment	1,37 mg/kg dry
		weight (d.w.)
	Secondary Poisoning	0,02 g/kg food
	Sea water	0,1 mg/l
butan-1-ol	Sewage treatment plant	2476 mg/l
	Fresh water	0,082 mg/l
	Intermittent use/release	2,25 mg/l
	Fresh water sediment	0,178 mg/kg dry
		weight (d.w.)
	Sea water	0,0082 mg/l
	Sea sediment	0,0178 mg/kg dry
		weight (d.w.)
	Soil	0,015 mg/kg dry
		weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

Tightly fitting safety goggles

Hand protection

Material : butyl-rubber
Glove thickness : 0,2 mm
Protective index : Class 3
Wearing time : 30 min

Remarks : Gloves should be discarded and replaced if there is any indi-

cation of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suita-

ble gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes

Use appropriate degowning techniques to remove potentially

contaminated clothing.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, dis-

posable suits) to avoid exposed skin surfaces.

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.

During spray application: impervious clothing

Respiratory protection : Roller application or brushing: This product should not be

used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to

standard EN 14387) is used.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : No data available

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

Odor : No data available

Odor Threshold : Not relevant

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Flash point : 30 °C

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 6,95

Concentration: 10 %

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Flow time : > 60 s at 23 °C

Cross section: 6 mm Method: ISO 2431

Solubility(ies)

Water solubility : partly miscible

Partition coefficient: n-

octanol/water

not determined

Vapor pressure : not determined

Relative density : not determined

Density : 1,8000 g/cm3

Relative vapor density : Heavier than air.

9.2 Other information

Explosives : Not applicable

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

Oxidizing properties : Not applicable

Flammability (liquids) : Sustains combustion

Evaporation rate : Not applicable

Solvent separation : < 3 %(V)

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.

Hazardous decomposition products formed under fire condi-

tions.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids.

Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapor

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Components:

xylene:

Acute oral toxicity : LD50 (Rat): 4.300 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27,5 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat): 3.500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 17.800 mg/kg

butan-1-ol:

Acute oral toxicity : LD50 (Rat): 790 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 3.430 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 11.01.2023 6022055 Date of first issue: 12.01.2021 1.3

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks Although the product only contains epoxy resins with high

molecular weight, follow good industrial hygiene practice and

avoid prolonged skin contact.

SECTION 12: Ecological information

12.1 Toxicity

Components:

barium sulfate:

Toxicity to fish Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No toxicity at the limit of solubility.

Toxicity to algae/aquatic

plants

Remarks: No toxicity at the limit of solubility.

Toxicity to fish (Chronic tox-

icity)

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

Remarks: No toxicity at the limit of solubility.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.:

Partition coefficient: n- : log Pow: 3,77

octanol/water Method: OECD Test Guideline 107

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Uncured product residues and unpurified packaging should be

disposed of as hazardous waste.

Material residues: Allow the basic substance to harden with

hardener and dispose of as paint waste.

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

cling.

Waste Code : used product

080111*, waste paint and varnish containing organic solvents

or other dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT

(trizinc bis(orthophosphate), zinc oxide)

IATA : Paint

14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR

Packing group : III Classification Code : F1

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

Hazard Identification Number : 30 Labels : 3 Tunnel restriction code : (D/E)

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen: 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

MDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 11.01.2023 6022055 Date of first issue: 12.01.2021 1.3

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener-

ated.

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving

dangerous substances.

FLAMMABLE LIQUIDS P5c

E2 **ENVIRONMENTAL HAZARDS**

Water hazard class (Germa-

WGK 2 obviously hazardous to water

ny)

Classification according to AwSV, Annex 1 (5.2)

: RE70 Epoxy resin products, sensitising, containing solvents

Directive 2004/42/EC Volatile organic compounds

> < 21 % < 370 g/I

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

regulations, where applicable.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapor.
H226 : Flammable liquid and vapor.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin. H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation. H336 : May cause drowsiness or dizziness.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H373 : May cause damage to organs through prolonged or repeated

exposure if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 903 : TRGS 903 - Biological limit values

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit DE TRGS 527 / BM : Assessment scale

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AlIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; (EQ bo 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EMS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Existing Chemicals Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; IECSC - Invensing Albert Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observed (Adverse) Effect Loading Rate; NZIOC - New Ze

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture:

Classification procedure:

Flam. Liq. 3	H226	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 2	H411	Calculation method

according to Regulation (EC) No. 1907/2006



DE / EN

DisboCOR 871 Comp. A Rotbraun

Version Revision Date: SDS Number: Date of last issue: 20.04.2022 1.3 11.01.2023 6022055 Date of first issue: 12.01.2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN