

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : DisboCOR 871 Comp. B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : epoxide-resin-based coating material, solvent-containing

Recommended restrictions  
on use : within adequate application - none

#### 1.3 Details of the supplier of the safety data sheet

Company : Disbon GmbH  
Roßdörfer Straße 50  
64372 Ober-Ramstadt

Telephone : +496154710  
Telefax : +4961547170222

E-mail address Respon-  
sible/issuing person : msds@dr-rmi.com

#### 1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single ex- posure, Category 3, Respiratory system	H335: May cause respiratory irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

Specific target organ toxicity - repeated exposure, Category 2

H373: May cause damage to organs through prolonged or repeated exposure.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Danger

Hazard Statements :

- H226 Flammable liquid and vapor.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe vapours/ spray.
- P262 Do not get in eyes, on skin, or on clothing.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### **Response:**

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### **Hazardous ingredients which must be listed on the label:**

xylene

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

Formaldehyde, polymer with benzeneamine, hydrogenated

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

3-aminomethyl-3,5,5-trimethylcyclohexylamine  
m-phenylenebis(methylamine)  
3,6-diazaoctanethylenediamin

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Asp. Tox. 1; H304 STOT RE 2; H373 Aquatic Chronic 3; H412	>= 30 - < 50
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylene-tetramine	68082-29-1 500-191-5 01-2119972320-44	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Eye Dam. 1; H318 Aquatic Chronic 2; H411	>= 20 - < 25
ethylbenzene	100-41-4 202-849-4 601-023-00-4 01-2119489370-35	Acute Tox. 4; H332 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Flam. Liq. 2; H225	>= 10 - < 20

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version 2.2      Revision Date: 11.01.2023      SDS Number: 6021064      Date of last issue: 20.04.2022  
Date of first issue: 10.12.2020

butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38, 01-2120076484-50	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 STOT SE 3; H335	$\geq 3 - < 10$
benzyl alcohol	100-51-6 202-859-9 603-057-00-5 01-2119492630-38	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319	$\geq 1 - < 10$
Formaldehyde, polymer with benzeneamine, hydrogenated	135108-88-2  01-2119983522-33	Acute Tox. 4; H302 Skin Corr. 1C; H314 Skin Sens. 1; H317 STOT RE 2; H373 (Kidney) Aquatic Chronic 3; H412	$\geq 1 - < 2,5$
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2 220-666-8 612-067-00-9 01-2119514687-32	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Chronic 3; H412  specific concentration limit Skin Sens. 1A; H317 $\geq 0,001 \%$  Acute toxicity estimate  Acute oral toxicity: 1.030 mg/kg	$\geq 1 - < 2,5$
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412 EUH071	$\geq 0,25 - < 1$
3,6-diazaoctanethylenediamin	112-24-3 203-950-6 612-059-00-5	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412	$\geq 0,25 - < 1$

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

salicylic acid	69-72-7 200-712-3 607-732-00-5 01-2119486984-17, 01-2120762977-34	Acute Tox. 4; H302 Eye Dam. 1; H318 Repr. 2; H361d	$\geq 0,1 - < 1$
----------------	---	--	------------------

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person.  
If you feel unwell, seek medical advice (show the label where possible).  
Move out of dangerous area.  
First aider needs to protect himself.
- If inhaled : Move to fresh air.  
  
If symptoms persist, call a physician.  
  
If unconscious, place in recovery position and seek medical advice.  
  
If breathing is irregular or stopped, administer artificial respiration.  
  
Call a physician.
- In case of skin contact : Do NOT use solvents or thinners.  
In case of contact, immediately flush skin with soap and plenty of water.  
Take off all contaminated clothing immediately.
- In case of eye contact : IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
- If swallowed : Call a physician.  
Clean mouth with water and drink afterwards plenty of water.  
If swallowed, DO NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye damage.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

Harmful if inhaled.  
May cause respiratory irritation.  
May cause damage to organs through prolonged or repeated exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Foam  
Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.  
Hazardous decomposition products formed under fire conditions.

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Standard procedure for chemical fires.  
In the event of fire and/or explosion do not breathe fumes.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.  
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
Ensure adequate ventilation.  
Remove all sources of ignition.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Do not flush into surface water or sanitary sewer system.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.  
, For personal protection see section 8., For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Provide sufficient air exchange and/or exhaust in work rooms.

In addition, the current technical information for this product and its application on [www.caparol.com](http://www.caparol.com) must be observed.

Advice on protection against fire and explosion : The product is flammable but not readily ignited.

Hygiene measures : Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 3

### 7.3 Specific end use(s)

Specific use(s) : This information is not available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version 2.2      Revision Date: 11.01.2023      SDS Number: 6021064      Date of last issue: 20.04.2022  
Date of first issue: 10.12.2020

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
xylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 220 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: Skin absorption			
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	200 ppm 884 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	20 ppm 88 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
butan-1-ol	71-36-3	AGW	100 ppm 310 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 1;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
benzyl alcohol	100-51-6	AGW (Vapour and aerosols)	5 ppm 22 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(I)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

##### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l	Immediately after exposure or after working hours	TRGS 903



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version 2.2      Revision Date: 11.01.2023      SDS Number: 6021064      Date of last issue: 20.04.2022  
Date of first issue: 10.12.2020

ethylbenzene	100-41-4	(Urine) mandelic acid + phenylglyoxylic acid: 250 mg/g Creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903
butan-1-ol	71-36-3	1-butanol: 2 mg/g Creatinine (Urine)	Before next shift	TRGS 903
		1-butanol: 10 mg/g Creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health ef- fects	Value
xylene	Consumers	Inhalation	Acute local effects	174,00 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	108,00 mg/kg bw/day
	Consumers	Inhalation	Acute systemic ef- fects	174,00 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	1,60 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	14,80 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic ef- fects	289,00 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	289,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	77,00 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	180,00 mg/kg bw/day
Fatty acids, C18- unsatd., dimers, oli- gomeric reaction products with tall-oil fatty acids and triethy- lenetetramine	Consumers	Inhalation	Long-term systemic effects	0,97 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	0,56 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,56 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	1,10 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	3,90 mg/m <sup>3</sup>
ethylbenzene	Consumers	Ingestion	Long-term systemic effects	1,60 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic	15,00 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version  
2.2

Revision Date:  
11.01.2023

SDS Number:  
6021064

Date of last issue: 20.04.2022  
Date of first issue: 10.12.2020

			effects	
	Workers	Inhalation	Acute systemic effects	884,00 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	293,00 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	884,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	77,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	442,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	442,00 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	180,00 mg/kg bw/day
butan-1-ol	Consumers	Inhalation	Long-term local effects	55,00 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	3,13 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	310,00 mg/m <sup>3</sup>
benzyl alcohol	Consumers	Skin contact	Acute systemic effects	20,00 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	5,40 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	4,00 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	20,00 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	27,00 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	110,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	22,00 mg/m <sup>3</sup>
	Workers	Skin contact	Acute systemic effects	40,00 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	8,00 mg/kg bw/day
Formaldehyde, polymer with benzeneamine, hydrogenated	Workers	Inhalation	Acute systemic effects	2,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	0,20 mg/m <sup>3</sup>
	Workers	Skin contact	Acute systemic effects	6,00 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	2,00 mg/kg bw/day

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version 2.2      Revision Date: 11.01.2023      SDS Number: 6021064      Date of last issue: 20.04.2022  
Date of first issue: 10.12.2020

3-aminomethyl-3,5,5-trimethylcyclohexylamine	Consumers	Ingestion	Long-term systemic effects	0,53 mg/kg bw/day
	Workers	Inhalation	Acute local effects	0,07 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	0,07 mg/m <sup>3</sup>
m-phenylenebis(methylamine)	Workers	Inhalation	Long-term systemic effects	1,20 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	0,20 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	0,33 mg/kg bw/day
salicylic acid	Consumers	Inhalation	Long-term systemic effects	4,00 mg/m <sup>3</sup>
	Consumers	Ingestion	Acute systemic effects	4,00 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	1,00 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1,00 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	5,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	5,00 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	2,30 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
xylene	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Soil	2,31 mg/kg dry weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Sea water	0,327 mg/l
	Sea sediment	12,46 mg/kg dry weight (d.w.)
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylene-tetramine	Sea sediment	43,4 mg/kg dry weight (d.w.)
	Sea water	0,000434 mg/l
	Fresh water	0,00434 mg/l
	Intermittent use/release	0,0434 mg/l
	Soil	86,78 mg/kg dry

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version 2.2      Revision Date: 11.01.2023      SDS Number: 6021064      Date of last issue: 20.04.2022  
Date of first issue: 10.12.2020

		weight (d.w.)
	Fresh water sediment	434,02 mg/kg dry weight (d.w.)
	Sewage treatment plant	3,84 mg/l
ethylbenzene	Intermittent use/release	0,1 mg/l
	Sewage treatment plant	9,6 mg/l
	Fresh water	0,1 mg/l
	Sea water	0,01 mg/l
	Fresh water sediment	13,7 mg/kg dry weight (d.w.)
	Soil	2,68 mg/kg dry weight (d.w.)
	Sea sediment	1,37 mg/kg dry weight (d.w.)
	Secondary Poisoning	0,02 g/kg food
	Sea water	0,1 mg/l
butan-1-ol	Sewage treatment plant	2476 mg/l
	Fresh water	0,082 mg/l
	Intermittent use/release	2,25 mg/l
	Fresh water sediment	0,178 mg/kg dry weight (d.w.)
	Sea water	0,0082 mg/l
	Sea sediment	0,0178 mg/kg dry weight (d.w.)
	Soil	0,015 mg/kg dry weight (d.w.)
benzyl alcohol	Sewage treatment plant	39 mg/l
	Fresh water	1 mg/l
	Sea sediment	0,527 mg/kg dry weight (d.w.)
	Sea water	0,1 mg/l
	Fresh water sediment	5,27 mg/kg dry weight (d.w.)
	Soil	0,456 mg/kg dry weight (d.w.)
	Intermittent use/release	2,3 mg/l
Formaldehyde, polymer with benzeneamine, hydrogenated	Sea sediment	1,5 mg/kg dry weight (d.w.)
	Fresh water sediment	15 mg/kg dry weight (d.w.)
	Fresh water	0,015 mg/l
	Soil	1,8 mg/kg dry weight (d.w.)
	Sewage treatment plant	1,9 mg/l
	Intermittent use/release	0,15 mg/l
	Sea water	0,0015 mg/l
3-aminomethyl-3,5,5-trimethylcyclohexylamine	Sea sediment	0,578 mg/kg dry weight (d.w.)
	Fresh water sediment	5,784 mg/kg dry

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version 2.2      Revision Date: 11.01.2023      SDS Number: 6021064      Date of last issue: 20.04.2022  
Date of first issue: 10.12.2020

		weight (d.w.)
	Fresh water	0,06 mg/l
	Sewage treatment plant	3,18 mg/l
	Sea water	0,006 mg/l
	Soil	1,121 mg/kg dry weight (d.w.)
	Intermittent use/release	0,23 mg/l
m-phenylenebis(methylamine)	Soil	0,045 mg/kg dry weight (d.w.)
	Sewage treatment plant	10 mg/l
	Sea sediment	0,043 mg/kg dry weight (d.w.)
	Fresh water sediment	0,43 mg/kg dry weight (d.w.)
	Fresh water	0,094 mg/l
	Intermittent use/release	0,152 mg/l
	Sea water	0,0094 mg/l
salicylic acid	Sea water	0,02 mg/l
	Intermittent use/release	1 mg/l
	Sewage treatment plant	162 mg/l
	Soil	0,166 mg/kg dry weight (d.w.)
	Fresh water sediment	1,42 mg/kg dry weight (d.w.)
	Sea sediment	0,142 mg/kg dry weight (d.w.)
	Fresh water	0,2 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Tightly fitting safety goggles

#### Hand protection

Material : butyl-rubber  
Glove thickness : 0,2 mm  
Protective index : Class 3  
Wearing time : 30 min

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374.  
DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes  
Use appropriate degowning techniques to remove potentially

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

contaminated clothing.  
Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.  
Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.  
During spray application: impervious clothing

Respiratory protection : Roller application or brushing: This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	: liquid
Color	: No data available
Odor	: No data available
Odor Threshold	: Not relevant
Melting point/freezing point	: not determined
Boiling point/boiling range	: not determined
Upper explosion limit / Upper flammability limit	: not determined
Lower explosion limit / Lower flammability limit	: not determined
Flash point	: 27 °C
Autoignition temperature	: not determined

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

Decomposition temperature : Not applicable

pH : 6,95  
Concentration: 10 %

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

Solubility(ies)

Water solubility : partly miscible

Partition coefficient: n-octanol/water : not determined

Vapor pressure : not determined

Relative density : not determined

Density : 0,9100 g/cm<sup>3</sup>

Relative vapor density : Heavier than air.

### 9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : Sustains combustion

Evaporation rate : Not applicable

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.  
Hazardous decomposition products formed under fire conditions.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

### 10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with acids.  
Incompatible with oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Harmful if inhaled.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 18,19 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

##### **xylene:**

Acute oral toxicity : LD50 (Rat): 4.300 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27,5 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

##### **ethylbenzene:**

Acute oral toxicity : LD50 Oral (Rat): 3.500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 17.800 mg/kg

##### **butan-1-ol:**



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

Acute oral toxicity : LD50 (Rat): 790 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 3.430 mg/kg

### **benzyl alcohol:**

Acute oral toxicity : LD50 (Rat, male and female): 1.230 mg/kg

### **Formaldehyde, polymer with benzeneamine, hydrogenated:**

Acute oral toxicity : LD50 (Rat): 367 mg/kg

### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Acute oral toxicity : Acute toxicity estimate: 1.030 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Acute dermal toxicity : LD50 (Rabbit): 1.840 mg/kg

### **m-phenylenebis(methylamine):**

Acute oral toxicity : LD50 (Rat): 930 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 3.100 mg/kg

### **3,6-diazaoctanethylenediamin:**

Acute dermal toxicity : LD50 (Rabbit): 1.465 mg/kg

### **salicylic acid:**

Acute oral toxicity : LD50 (Rat): 891 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

### **Skin corrosion/irritation**

Causes skin irritation.

### **Serious eye damage/eye irritation**

Causes serious eye damage.

### **Components:**

#### **benzyl alcohol:**

Species : Rabbit  
Assessment : Irritating to eyes.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT-single exposure

May cause respiratory irritation.

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### Aspiration toxicity

Not classified based on available information.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 12: Ecological information

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Uncured product residues and unpurified packaging should be disposed of as hazardous waste.  
Material residues: Allow the basic substance to harden with hardener and dispose of as paint waste.  
Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product  
080111\*, waste paint and varnish containing organic solvents or other dangerous substances

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADN : UN 1263

ADR : UN 1263

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

**RID** : UN 1263

**IMDG** : UN 1263

**IATA** : UN 1263

### 14.2 UN proper shipping name

**ADN** : PAINT RELATED MATERIAL

**ADR** : PAINT RELATED MATERIAL

**RID** : PAINT RELATED MATERIAL

**IMDG** : PAINT RELATED MATERIAL

**IATA** : Paint related material

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 3	
<b>ADR</b>	: 3	
<b>RID</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

### 14.4 Packing group

**ADN**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

. : RE70 Epoxy resin products, sensitising, containing solvents

Volatile organic compounds : Directive 2004/42/EC  
< 67 %  
< 610 g/l

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

## 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

## SECTION 16: Other information

### Full text of H-Statements

H225	: Highly flammable liquid and vapor.
H226	: Flammable liquid and vapor.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H361d : Suspected of damaging the unborn child.  
H373 : May cause damage to organs through prolonged or repeated exposure.  
H373 : May cause damage to organs through prolonged or repeated exposure if inhaled.  
H373 : May cause damage to organs through prolonged or repeated exposure if swallowed.  
H411 : Toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.  
EUH071 : Corrosive to the respiratory tract.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Repr. : Reproductive toxicity  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitization  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
TRGS 903 : TRGS 903 - Biological limit values  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit  
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

### Further information

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

#### Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs.

Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

#### Classification of the mixture:

Flam. Liq. 3	H226
Acute Tox. 4	H332
Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
STOT SE 3	H335
STOT RE 2	H373
Aquatic Chronic 3	H412

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboCOR 871 Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 20.04.2022
2.2	11.01.2023	6021064	Date of first issue: 10.12.2020

---

### REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN