

Dis	DisboCOR 860 Hellgrau							
Vers 4.0		Revision Date:SDS Number:11.01.20236020852			Pate of last issue: 28.02.2022 Pate of first issue: 23.07.2020			
SEC	CTION 1:	Identification of	the substand	ce/mixture	e and of the company/undertaking			
1.1	<b>1.1 Product identifier</b> Trade name       : DisboCOR 860 Hellgrau							
<b>1.2 Relevant identified uses of the substance or mixture and uses advised against</b> Use of the Sub- stance/Mixture								
	Recomme on use	ended restrictions	: within ad	equate app	lication - none			
1.3	Details of	the supplier of the	safety data s	heet				
	Company	••	: Disbon G Roßdörfe	: Disbon GmbH Roßdörfer Straße 50 64372 Ober-Ramstadt				
	Telephon Telefax	e	: +496154 : +496154	710				
	E-mail address Responsi- : msds@c ble/issuing person			r-rmi.com				
1.4	-	cy telephone cy telephone 1	: +4961328	84463 GBK	( GmbH			
SEC	CTION 2:	Hazards identific	cation					
2.1	Classifica	tion of the substar	nce or mixture	<b>;</b>				
		ation (REGULATIO le liquids, Category		-	ammable liquid and vapor.			
	Skin irrita	tion, Category 2		H315: Ca	uses skin irritation.			
	Eye irritat	ion, Category 2		H319: Ca	uses serious eye irritation.			
		arget organ toxicity ategory 3, Respirat		H335: Ma	ay cause respiratory irritation.			
		arget organ toxicity , Category 2	- repeated		ay cause damage to organs through pro- repeated exposure.			
	Long-tern	n (chronic) aquatic h	azard, Cat-	H411: To	xic to aquatic life with long lasting effects.			



Disbo	COR 860 Hellgr	au			
Version 4.0	Revision Date: 11.01.2023		SDS Num 020852	ber:	Date of last issue: 28.02.2022 Date of first issue: 23.07.2020
egor	ry 2				
2.2 Labe	l elements				
	eling (REGULATION ( ard pictograms	( <b>EC)</b>	No 1272/	2008)	
Sign	al Word	:	Warnin	g	
Haz	ard Statements	:	H335 H373	Causes Causes May cau May cau ed exposi	able liquid and vapor. skin irritation. serious eye irritation. use respiratory irritation. use damage to organs through prolonged or ure. aquatic life with long lasting effects.
Prec	cautionary Statements	:		Keep av and othe Do not b Do not g Use only	way from heat, hot surfaces, sparks, open er ignition sources. No smoking. preathe vapours/ spray. get in eyes, on skin, or on clothing. y outdoors or in a well-ventilated area. elease to the environment.
			<b>Respo</b> P370 + alcohol	P378	In case of fire: Use dry sand, dry chemical or t foam to extinguish.

Hazardous ingredients which must be listed on the label:

xylene

## **Additional Labeling**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



# DisboCOR 860 Hellgrau

Version	Revision Date:	SDS Number:	Date of last issue: 28.02.2022
4.0	11.01.2023	6020852	Date of first issue: 23.07.2020

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

Chemical nature : 1-C-universal primer

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Asp. Tox. 1; H304 STOT RE 2; H373 Aquatic Chronic 3; H412	>= 25 - < 30
titanium dioxide; [in powder form containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	>= 1 - < 10
ethylbenzene	100-41-4 202-849-4 601-023-00-4 01-2119489370-35	Acute Tox. 4; H332 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Flam. Liq. 2; H225	>= 2,5 - < 10
trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 2,5 - < 10
zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32, 01-2120089607-43, 01-2120767291-53	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 2,5 - < 10
N,N'-ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide)	123-26-2 204-613-6 01-2119978265-26	Skin Sens. 1B; H317 Aquatic Chronic 3; H412	>= 0,1 - < 0,25



# DisboCOR 860 Hellgrau

Version 4.0	Revision Date: 11.01.2023	SDS Number: 6020852	Date of last issue: 28.02.2022 Date of first issue: 23.07.2020
			specific concentration limit Skin Sens. 1B; H317 > 25 %
Subs	tances with a workpla	ce exposure limit :	
	m sulfate	7727-43-7 231-784-4 01-21194912	>= 10 - < 20
Talc (	(Mg3H2(SiO3)4)	14807-96-6 238-877-9 01-21201402	>= 10 - < 20

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first-aid measures

General advice	:	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Move out of dangerous area. First aider needs to protect himself.
If inhaled	:	Call a physician. If breathing is irregular or stopped, administer artificial respira- tion. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician. Move to fresh air.
In case of skin contact	:	Do NOT use solvents or thinners. In case of contact, immediately flush skin with soap and plenty of water. Take off all contaminated clothing immediately.
In case of eye contact	:	If eye irritation persists: Get medical advice/ attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If swallowed	:	Seek medical advice. Clean mouth with water and drink afterwards plenty of water. If swallowed, DO NOT induce vomiting.



Version 4.0	Revision Date: 11.01.2023	-	9S Number: 20852	Date of last issue: 28.02.2022 Date of first issue: 23.07.2020
4.2 Most i	mportant symptoms a	nd e	ffects, both acu	te and delayed
Risks		:	Causes skin irrit Causes serious May cause resp May cause dam exposure.	eye irritation.
4.3 Indicat	tion of any immediate	mec	lical attention ar	nd special treatment needed
Treatr	nent	:	No information a	available.
SECTION	5: Firefighting mea	sur	es	
5.1 Exting	uishing media			
Suitab	ble extinguishing media	:	cumstances and Use water spray bon dioxide.	ng measures that are appropriate to local cir- I the surrounding environment. r, alcohol-resistant foam, dry chemical or car Iid water stream as it may scatter and spread
Unsui media	table extinguishing	:	None known.	
5.2 Specia	II hazards arising from	the	substance or m	nixture
Specii fightin	fic hazards during fire g	:	In case of fire ha	tainers exposed to fire with water spray. azardous decomposition products may be as: de, carbon dioxide and unburned hydrocar-
5.3 Advice	e for firefighters			
	al protective equipment e-fighters	:	In the event of fi	re, wear self-contained breathing apparatus.
Furthe	er information	:		dure for chemical fires. re and/or explosion do not breathe fumes.

• • •			
Personal precautions	:	Do not get in eyes, on skin, or on clothing.	
		When workers are facing concentrations above the exposure	
		limit they must use appropriate certified respirators.	
		Ensure adequate ventilation.	





DisboCOR 860 Hellgrau							
Version 4.0	Revision Date: 11.01.2023	SDS Number: 6020852	Date of last issue: 28.02.2022 Date of first issue: 23.07.2020				
Remove all sources of ignition.							
6.2 Enviro	6.2 Environmental precautions						
Environmental precautions		<ul> <li>Prevent further leakage or spillage if safe to do so.</li> <li>If the product contaminates rivers and lakes or drains inform respective authorities.</li> <li>Do not flush into surface water or sanitary sewer system.</li> </ul>					
6.3 Methods and material for containment and cleaning up							
Methods for cleaning up :		Soak up with ine	Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).				

#### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet. , For personal protection see section 8., For disposal considerations see section 13.

#### **SECTION 7: Handling and storage**

<b>7.1 Precautions for safe handling</b> Advice on safe handling :	Non-sparking tools should be used. For personal protection see section 8. Avoid exceeding the given occupational exposure limits (see section 8). Provide sufficient air exchange and/or exhaust in work rooms. In addition, the current technical information for this product and its application on www.caparol.com must be observed.
Advice on protection against : fire and explosion	Vapors are heavier than air and may spread along floors. Va- pors may form explosive mixtures with air. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Hygiene measures :	Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protec- tive equipment before entering eating areas.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Storage class (TRGS 510)	:	3



# DisboCOR 860 Hellgrau

Version	Revision Date:	SDS Number:	Date of last issue: 28.02.2022
4.0	11.01.2023	6020852	Date of first issue: 23.07.2020

### 7.3 Specific end use(s)

Specific use(s)

: This information is not available.

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis					
xylene	1330-20-7	TWA	50 ppm 221 mg/m3	2000/39/EC					
		Further information: Identifies the possibility of significant uptake through the							
	skin, Indicativ								
		STEL	100 ppm 442 mg/m3	2000/39/EC					
	Further inform skin, Indicativ		possibility of significant upta	ke through the					
		AGW	50 ppm 220 mg/m3	DE TRGS 900					
	Peak-limit cat	egory: 2:(II)							
		Further information: Skin absorption							
barium sulfate	7727-43-7	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900					
	Peak-limit category: 2;(II)								
	Further inform	compliance with the OEL a f harming the unborn child	nd biological						
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900					
	Peak-limit category: 2;(II)								
			compliance with the OEL a f harming the unborn child						
		BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527					
Talc (Mg3H2(SiO3)4)	14807-96-6	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900					
	Peak-limit cat	egory: 2;(II)							
	Further inform	nation: When there is	compliance with the OEL a f harming the unborn child	nd biological					
				DE TRGS					
		AGW (Alveolate fraction)	1,25 mg/m3	900					
	Peak-limit cat								
			compliance with the OEL a f harming the unborn child	nd biological					
		BM (Alveolar	0,5 mg/m3	DE TRGS					



# DisboCOR 860 Hellgrau

ersion 0	Revision Da 11.01.2023	te: SDS 6020		ate of last issue: 28.02.2022 ate of first issue: 23.07.2020				
			dust fraction)		527			
powde taining more with a	im dioxide; [in er form con- g 1 % or of particles ierodynamic eter ≤ 10 μm]	13463-67-7	AGW (Inhalable fraction)	10 mg/m3 (Titanium dioxide)	DE TRGS 900			
		Peak-limit cat	egory: 2;(II)					
				s compliance with the OEL ar of harming the unborn child	nd biological			
			AGW (Alveolate	1,25 mg/m3	DE TRGS			
			fraction)	(Titanium dioxide)	900			
		Peak-limit category: 2;(II)						
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child						
			BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527			
ethylb	penzene	100-41-4	TWA	100 ppm 442 mg/m3	2000/39/EC			
		Further inform skin, Indicativ		possibility of significant uptal	ke through the			
			STEL	200 ppm 884 mg/m3	2000/39/EC			
		Further inform skin, Indicativ		possibility of significant uptal	-			
			AGW	20 ppm 88 mg/m3	DE TRGS 900			
		Peak-limit cat	egory: 2;(II)					
				ion, When there is compliance here is no risk of harming the				

#### **Biological occupational exposure limits**

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
ethylbenzene	100-41-4	mandelic acid + phenylglyoxylic acid: 250 mg/g Creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo-	Potential health ef-	Value
		sure	fects	
xylene	Consumers	Inhalation	Acute local effects	174,00 mg/m3
	Consumers	Skin contact	Long-term systemic	108,00 mg/kg
			effects	bw/day



# DisboCOR 860 Hellgrau

sion	Revision Date: 11.01.2023	SDS Nui 6020852		of last issue: 28.02.2022 of first issue: 23.07.2020	
		Consumers	Inhalation	Acute systemic ef- fects	174,00 mg/
		Consumers	Ingestion	Long-term systemic effects	1,60 mg/kg bw/day
		Consumers	Inhalation	Long-term systemic effects	14,80 mg/m
		Workers	Inhalation	Acute systemic ef- fects	289,00 mg/
		Workers	Inhalation	Acute local effects	289,00 mg/
		Workers	Inhalation	Long-term systemic effects	77,00 mg/m
		Workers	Skin contact	Long-term systemic effects	180,00 mg/ bw/day
barium	n sulfate	Consumers	Inhalation	Long-term systemic effects	10,00 mg/m
		Consumers	Ingestion	Long-term systemic effects	13000,00 mg/kg bw/d
		Workers	Inhalation	Long-term systemic effects	10,00 mg/m
		Workers	Inhalation	Long-term local ef- fects	10,00 mg/m
powde ing 1 % particle	m dioxide; [in r form contain- 6 or more of es with aerody- diameter $\leq 10$	Consumers	Ingestion	Long-term systemic effects	700,00 mg/l bw/day
•••		Workers	Inhalation	Long-term local ef- fects	10,00 mg/m
ethylbe	enzene	Consumers	Ingestion	Long-term systemic effects	1,60 mg/kg bw/day
		Consumers	Inhalation	Long-term systemic effects	15,00 mg/m
		Workers	Inhalation	Acute systemic ef- fects	884,00 mg/i
		Workers	Inhalation	Acute local effects	293,00 mg/ı
		Workers	Inhalation	Acute local effects	884,00 mg/r
		Workers	Inhalation	Long-term systemic effects	77,00 mg/m
		Workers	Inhalation	Long-term systemic effects	442,00 mg/r
		Workers	Inhalation	Long-term local ef- fects	442,00 mg/r
		Workers	Skin contact	Long-term systemic effects	180,00 mg/l bw/day
trizinc bis(ort	hophosphate)	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
		Consumers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day



# DisboCOR 860 Hellgrau

rsion )	Revision Date: 11.01.2023	SDS Nur 6020852		of last issue: 28.02.2022 of first issue: 23.07.2020	
		Consumers	Inhalation	Long-term systemic effects	2,50 mg/m3
		Workers	Inhalation	Long-term systemic effects	5,00 mg/m3
		Workers	Skin contact	Long-term systemic effects	83,00 mg/k bw/day
zinc oxid	de	Consumers	Skin contact	Long-term systemic effects	83,00 mg/k bw/day
		Consumers	Inhalation	Long-term systemic effects	2,50 mg/m3
		Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
		Workers	Skin contact	Long-term systemic effects	83,00 mg/k bw/day
		Workers	Inhalation	Long-term local ef- fects	0,50 mg/m3
		Workers	Inhalation	Long-term systemic effects	5,00 mg/m3
N,N'-ethane-1,2- diylbis(12- hydroxyoctadecan-1- amide)		Consumers	Inhalation	Long-term local ef- fects	0,83 mg/m3
		Workers	Inhalation	Long-term local ef- fects	3,35 mg/m3

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
xylene	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Soil	2,31 mg/kg dry weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Sea water	0,327 mg/l
	Sea sediment	12,46 mg/kg dry weight (d.w.)
barium sulfate	Fresh water	115 µg/l
	Fresh water sediment	600,4 mg/kg dry weight (d.w.)
	Soil	207,7 mg/kg dry weight (d.w.)
	Sewage treatment plant	62,2 mg/l
titanium dioxide; [in powder form containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 µm]	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry



# DisboCOR 860 Hellgrau

sion	Revision Date: 11.01.2023	SDS Number:Date of last issue6020852Date of first issue	
1		1	weight (d.w.)
		Sea water	0,0184 mg/l
		Fresh water sediment	1000 mg/kg dr
			weight (d.w.)
		Sea sediment	100 mg/kg dry
			weight (d.w.)
		Intermittent use/release	0,193 mg/l
ethylb	penzene	Intermittent use/release	0,1 mg/l
		Sewage treatment plant	9,6 mg/l
		Fresh water	0,1 mg/l
		Sea water	0,01 mg/l
		Fresh water sediment	13,7 mg/kg dry
			weight (d.w.)
		Soil	2,68 mg/kg dry
			weight (d.w.)
		Sea sediment	1,37 mg/kg dry
			weight (d.w.)
		Secondary Poisoning	0,02 g/kg food
		Sea water	0,1 mg/l
trizino	bis(orthophosphate)	Sea sediment	56,5 mg/kg dry
		Freeh weter	weight (d.w.)
		Fresh water Soil	20,6 µg/l
		501	35,6 mg/kg dry weight (d.w.)
		Sewage treatment plant	100 µg/l
		Fresh water sediment	117,8 mg/kg di
			weight (d.w.)
		Sea water	6,1 µg/l
zinc c	oxide	Fresh water sediment	117,8 mg/kg di
			weight (d.w.)
		Sea water	6,1 µg/l
		Fresh water	20,6 µg/l
		Sea sediment	56,5 mg/kg dry
			weight (d.w.)
		Sewage treatment plant	100 µg/l
		Soil	35,6 mg/kg dry
			weight (d.w.)
	ethane-1,2-diylbis(12-	Sewage treatment plant	0,1 mg/l
hydro	xyoctadecan-1-amide)		

### 8.2 Exposure controls

## Personal protective equipment

Eye/face protection	:	DGUV Regulation 112-192 - Use of eye and face protection
		Tightly fitting safety goggles
Hand protection Material	:	Nitrile rubber

**DisboCOR 860 Hellgrau** 

DE / EN



#### Version Revision Date: SDS Number: Date of last issue: 28.02.2022 4.0 11.01.2023 6020852 Date of first issue: 23.07.2020 Glove thickness 0,2 mm 1 Protective index Class 3 : Remarks Gloves should be discarded and replaced if there is any indi-5 cation of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374. DGUV Regulation 112-195 - Use of protective gloves Skin and body protection Safety shoes 2 Long sleeved clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place. Skin should be washed after contact. Remove and wash contaminated clothing before re-use. During spray application: impervious clothing Respiratory protection Roller application or brushing: This product should not be t used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Color	:	No data available
Odor	:	No data available
Odor Threshold	:	Not relevant
Melting point/freezing point	:	not determined
Boiling point/boiling range	:	not determined
Upper explosion limit / Upper flammability limit	:	not determined



# DisboCOR 860 Hellgrau

Vers 4.0	sion	Revision Date: 11.01.2023		S Number: 20852	Date of last issue: 28.02.2022 Date of first issue: 23.07.2020
		explosion limit / Lower bility limit	:	not determined	
	Flash p	oint	:	27 °C	
	Autoigr	nition temperature	:	not determined	
	Decom	position temperature	:	Not applicable	
	рН		:	6,95 Concentration: 1	0 %
	Viscosi Visc	ty cosity, dynamic	:	No data available	
	Visc	cosity, kinematic	:	> 20,5 mm2/s (40	0 °C)
	Flow tir	ne	:	80 s Cross section: 4	mm
	Solubili Wat	ty(ies) er solubility	:	partly miscible	
	Partitio octanol	n coefficient: n- /water	:	not determined	
	Vapor p	pressure	:	not determined	
	Relative	e density	:	not determined	
	Density	,	:	1,5000 g/cm3	
	Relative	e vapor density	:	Heavier than air.	
9.2	Other in	formation			
	Explosi	ves	:	Not applicable	
	Oxidizir	ng properties	:	Not applicable	
	Flamma	ability (liquids)	:	Sustains combus	stion
	Evapor	ation rate	:	Not applicable	



Disbo	DisboCOR 860 Hellgrau					
Version 4.0	Revision Date: 11.01.2023		S Number: 20852	Date of last issue: 28.02.2022 Date of first issue: 23.07.2020		
SECTION	N 10: Stability and I	eacti	vity			
10.1 Read	•					
	ecomposition if stored	and ap	oplied as directe	ed.		
	nical stability	and an	plied as directe	ed.		
	ibility of hazardous i		•			
Haza	rdous reactions	:		orm explosive mixture with air. composition products formed under fire condi-		
10.4 Cond	litions to avoid					
Cond	itions to avoid	:	Protect from f	rost, heat and sunlight.		
10.5 Incoi	mpatible materials					

Materials to avoid : Incompatible with acids and bases. Incompatible with oxidizing agents.

#### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Acute toxicity

Not classified based on available information.

## Product:

Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2.000 mg/kg Method: Calculation method
Components:		
xylene:		
Acute oral toxicity	:	LD50 (Rat): 4.300 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 27,5 mg/l Exposure time: 4 h Test atmosphere: vapor



ersion	Revision Date:	SDS Number:	Date of last issue: 28.02.2022			
0	11.01.2023	6020852	Date of first issue: 23.07.2020			
Acute	e dermal toxicity	: LD50 (Rabbit)	: > 2.000 mg/kg			
ethyl	benzene:					
Acute	oral toxicity	: LD50 Oral (Ra	t): 3.500 mg/kg			
Acute	e dermal toxicity	: LD50 Dermal	50 Dermal (Rabbit): 17.800 mg/kg			
	corrosion/irritation es skin irritation.					
	us eye damage/eye es serious eye irritatio					
Resp	iratory or skin sensi	tization				
-	<b>sensitization</b> lassified based on ava	ailable information.				
Respiratory sensitization Not classified based on available information.						
	Germ cell mutagenicity Not classified based on available information.					
	Carcinogenicity lot classified based on available information.					
-	oductive toxicity lassified based on ava	ailable information.				
	STOT-single exposure May cause respiratory irritation.					
	<b>F-repeated exposure</b> cause damage to orga		or repeated exposure.			
-	ation toxicity lassified based on ava	ailable information.				
1.2 Infor	mation on other haz	ards				
Endo	crine disrupting pro	perties				
Produ Asses	<u>uct:</u> ssment	ered to have e REACH Article	e/mixture does not contain components considered andocrine disrupting properties according to a 57(f) or Commission Delegated regulation 00 or Commission Regulation (EU) 2018/605 a or higher.			

DisboCOR 860 Hellorau



DE / EN

Version 4.0	Revision Date: 11.01.2023		DS Number: 20852	Date of last issue: 28.02.2022 Date of first issue: 23.07.2020
SECTION	12: Ecological infor	ma	ition	
12.1 Toxic	ity			
Comp	oonents:			
bariu	m sulfate:			
Toxici	ty to fish	:	Remarks: No to	xicity at the limit of solubility.
	ty to daphnia and other ic invertebrates	:	Remarks: No to	xicity at the limit of solubility.
Toxici plants	ty to algae/aquatic	:	Remarks: No to	xicity at the limit of solubility.
Toxici icity)	ty to fish (Chronic tox-	:	Remarks: No to	xicity at the limit of solubility.
	ty to daphnia and other ic invertebrates (Chron- city)	:	Remarks: No to	xicity at the limit of solubility.
	<b>stence and degradabil</b> ta available	ity		
	ccumulative potential ta available			
<b>12.4 Mobi</b> No da	l <b>ity in soil</b> ta available			
12.5 Resu	Its of PBT and vPvB as	sse	ssment	
<u>Produ</u> Asses	<u>uct:</u> ssment	:	to be either pers	mixture contains no components considere sistent, bioaccumulative and toxic (PBT), or and very bioaccumulative (vPvB) at levels c

## Product:

Assessment : The substance/mixture does not contain component ered to have endocrine disrupting properties accor REACH Article 57(f) or Commission Delegated reg (EU) 2017/2100 or Commission Regulation (EU) 20 levels of 0.1% or higher.
--



Version 4.0	Revision Date: 11.01.2023	SDS Number: 6020852	Date of last issue: 28.02.2022 Date of first issue: 23.07.2020
12.7 Othe	r adverse effects		
Prod	ict:		
	onal ecological infor-		ic organisms, may cause long-term adverse aquatic environment.
Additi matio	onal ecological infor- n	effects in the a	
Additi matio	onal ecological infor-	effects in the a siderations	

		Waste should not be disposed of via wastewater.
Contaminated packaging	:	Only completely emptied containers should be given for recy- cling.
Waste Code	:	used product 080112, waste paint and varnish other than those mentioned in 08 01 11*

# **SECTION 14: Transport information**

14.1 UN number or ID number			
ADN	:	UN 1263	
ADR	:	UN 1263	
RID	:	UN 1263	
IMDG	:	UN 1263	
ΙΑΤΑ	:	UN 1263	
14.2 UN proper shipping name			
ADN	:	PAINT	
ADR	:	PAINT	
RID	:	PAINT	
IMDG	:	PAINT (trizinc bis(orthophos)	phate), zinc oxide)
ΙΑΤΑ	:	Paint	
14.3 Transport hazard class(es)			
		Class	Subsidiary risks
ADN	:	3	



# DisboCOR 860 Hellgrau

Version 4.0	Revision Date: 11.01.2023		9S Number: 20852	Date of last issue: 28.02.2022 Date of first issue: 23.07.2020
ADR		:	3	
RID		:	3	
IMDG	ì	:	3	
ΙΑΤΑ		:	3	
14.4 Pack	ing group			
ADN				
Class	ng group ification Code rd Identification Number s	:	III F1 30 3	
<b>ADR</b> Packi Class Haza Label	ng group ification Code rd Identification Number	:	III F1 30 3 (D/E)	
Class	ng group ification Code rd Identification Number s	: : : : : : : : : : : : : : : : : : : :	III F1 30 3	
<b>IMDG</b> Packi Label EmS	ng group s	:	III 3 F-E, <u>S-E</u>	
Packi aircra	<b>(Cargo)</b> ng instruction (cargo ft) ng instruction (LQ)	:	366 Y344	
Packi Label	ng group s	:	III Flammable Liquic	ls
Packi	(Passenger) ng instruction (passen- rcraft)	:	355	
Packi	ng instruction (LQ) ng group	::	Y344 III Flammable Liquic	ls
14.5 Envir	onmental hazards			
<b>ADN</b> Enviro <b>ADR</b>	onmentally hazardous	:	yes	
	onmentally hazardous	:	yes	



# DisboCOR 860 Hellgrau

Version	Revision Date: 11.01.2023	SDS Number:	Date of last issue: 28.02.2022
4.0		6020852	Date of first issue: 23.07.2020

### RID

Environmentally hazardous	:	yes
IMDG		
Marine pollutant	:	yes

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).	: This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener- ated.
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	: Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	: None
Seveso III: Directive 2012/18/EU of the Euro-P5c pean Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	FLAMMABLE LIQUIDS
E2	ENVIRONMENTAL HAZARDS



# DisboCOR 860 Hellgrau

Version 4.0	Revision Date: 11.01.2023	SDS Number 6020852	: Date of last issue: 28.02.2022 Date of first issue: 23.07.2020
Wate ny)	r hazard class (Germa-		bviously hazardous to water tion according to AwSV, Annex 1 (5.2)
		: BSL60 Co dients, cla	pating materials, solvent-based, carcinogenic ingre- assified
Volat	ile organic compounds	: Directive < 33 % < 500 g/l	2004/42/EC
		Directive < 34 % < 510 g/l	2004/42/EC

#### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

#### **15.2 Chemical Safety Assessment**

A Chemical Safety Assessment is not required for this mixture.

## **SECTION 16: Other information**

#### Full text of H-Statements

H225 H226 H304 H312	<ul> <li>Highly flammable liquid and vapor.</li> <li>Flammable liquid and vapor.</li> <li>May be fatal if swallowed and enters airways.</li> <li>Harmful in contact with skin.</li> </ul>
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H351	: Suspected of causing cancer if inhaled.
H373	<ul> <li>May cause damage to organs through prolonged or repeated exposure.</li> </ul>
H373	: May cause damage to organs through prolonged or repeated exposure if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

: Acute toxicity



# DisboCOR 860 Hellgrau

Version 4.0	Revision Date: 11.01.2023	 DS Number: 20852	Date of last issue: 28.02.2022 Date of first issue: 23.07.2020
	it. Liq. rit. ens. RE SE	Specific target or	c) aquatic hazard
DE TRGS 527 DE TRGS 900 TRGS 903 2000/39/EC / TWA 2000/39/EC / STEL DE TRGS 527 / BM DE TRGS 900 / AGW		 list of indicative occupational exposure limit values Germany. TRGS 527 - Activities with nanomaterials Germany. TRGS 900 - Occupational exposure limit values. TRGS 903 - Biological limit values Limit Value - eight hours Short term exposure limit Assessment scale Time Weighted Average	

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELX - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Maritime Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity

#### Further information

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

#### Sources of key data used to compile the Material Safety Data Sheet: ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH NIOSH - Registry of toxic effects of chemical substances



# DisboCOR 860 Hellgrau

Version	Revision Date:	SDS Number:	Date of last issue: 28.02.2022
4.0	11.01.2023	6020852	Date of first issue: 23.07.2020

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance) Toxnet - Toxicology Data Network

Classification of the	e mixture:	Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

## **REACH Information**

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments. Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

#### DE / EN