according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 5.0 04.07.2023 6021072 Date of first issue: 04.09.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : DisboCOR 864 Sonderton

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Solvent-borne coatings

stance/Mixture

Recommended restrictions

on use

within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Disbon GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710 Telefax : +4961547170222

Website

E-mail address Responsi-

ble/issuing person

: msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapor.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 04.07.2023 6021072 Date of first issue: 04.09.2020 5.0

Long-term (chronic) aquatic hazard, Category 2

H411: Toxic to aquatic life with long lasting effects.

# 2.2 Label elements

# Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms









Signal Word Warning

Hazard Statements Flammable liquid and vapor. H226

May cause an allergic skin reaction. H317 H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or

repeated exposure.

Toxic to aquatic life with long lasting effects.

**Prevention: Precautionary Statements** 

> P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P260 Do not breathe vapours/ spray.

P262 Do not get in eyes, on skin, or on clothing. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

### Hazardous ingredients which must be listed on the label:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha 2-methoxy-1-methylethyl acetate

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6pentamethyl-4-piperidyl sebacate

#### **Additional Labeling**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 5.0 04.07.2023 6021072 Date of first issue: 04.09.2020

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

\_

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Low-solvent primer with anti-corrosion pigments

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	>= 10 - < 20
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9 265-150-3 649-327-00-6 01-2119457273-39, 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304 EUH066	>= 10 - < 20
zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32, 01-2120089607-43, 01-2120767291-53	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 2,5 - < 10
naphtha (petroleum), hydrodesul- phurized heavy; Low boiling point hydrogen treated naphtha	64742-82-1 265-185-4 649-330-00-2 01-2119458049-33, 01-2119473977-17, 01-2119463586-28	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 STOT RE 1; H372 (Central nervous system)	>= 2,5 - < 10

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 5.0 04.07.2023 6021072 Date of first issue: 04.09.2020

		EUH066	
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38, 01-2120076484-50	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 STOT SE 3; H335	>= 1 - < 3
trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2,5
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40	Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Repr. 2; H361f	>= 1 - < 2,5
2-ethylhexanoic acid, zirconium salt	22464-99-9 245-018-1 01-2119979088-21	Repr. 1B; H360D	>= 0,1 - < 0,3
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)	123-26-2 204-613-6 01-2119978265-26	Skin Sens. 1B; H317 Aquatic Chronic 3; H412	>= 0,1 - < 0,25
		specific concentration limit Skin Sens. 1B; H317 > 25 %	
2-methylpentane-2,4-diol	107-41-5 203-489-0 603-053-00-3 01-2119539582-35	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d	>= 0,1 - < 1
Substances with a workplace expos			
barium sulfate	7727-43-7 231-784-4 01-2119491274-35		>= 1 - < 10
Talc (Mg3H2(SiO3)4)	14807-96-6 238-877-9 01-2120140278-58		>= 1 - < 10

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 5.0 04.07.2023 6021072 Date of first issue: 04.09.2020

### **SECTION 4: First aid measures**

#### 4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled : Call a physician.

If breathing is irregular or stopped, administer artificial respira-

tion.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

Move to fresh air.

In case of skin contact : Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

Take off all contaminated clothing immediately.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed : Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated

exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

### **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 5.0 04.07.2023 6021072 Date of first issue: 04.09.2020

Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Do not use a solid water stream as it may scatter and spread

fire.

Unsuitable extinguishing

media

None known.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

Cool closed containers exposed to fire with water spray. In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

#### 5.3 Advice for firefighters

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

In the event of fire and/or explosion do not breathe fumes.

### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Ensure adequate ventilation. Remove all sources of ignition.

### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

#### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 04.07.2023 6021072 Date of first issue: 04.09.2020 5.0

# **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling Non-sparking tools should be used.

For personal protection see section 8.

Avoid exceeding the given occupational exposure limits (see

section 8).

Provide sufficient air exchange and/or exhaust in work rooms.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Advice on protection against

fire and explosion

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Keep away from

heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Avoid contact with the skin and the eyes. Wash hands before Hygiene measures

> eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protec-

tive equipment before entering eating areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition

and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) 3

7.3 Specific end use(s)

Specific use(s) This information is not available.

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide; [in powder form con- taining 1 % or more of particles	13463-67-7	AGW (Inhalable fraction)	10 mg/m3 (Titanium dioxide)	DE TRGS 900

<sup>,</sup> For personal protection see section 8., For disposal considerations see section 13.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

VersionRevision Date:SDS Number:Date of last issue: 11.01.20235.004.07.20236021072Date of first issue: 04.09.2020

with aerodynamic					
diameter ≤ 10 µm]					
	Peak-limit cat				
		s compliance with the OEL a of harming the unborn child	ind biological		
		AGW (Alveolate fraction)	1,25 mg/m3 (Titanium dioxide)	DE TRGS 900	
	Peak-limit cat	,	(Thaniam dioxide)	000	
			s compliance with the OEL a	nd hiological	
			of harming the unborn child	ina biological	
	tolorarios vale	BM (Alveolar	0,5 mg/m3	DE TRGS	
		dust fraction)	, o,og,o	527	
Naphtha (petrole- um), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	AGW	300 mg/m3	DE TRGS 900	
	Peak-limit cat	egory: 2:(II)			
			ure limit for hydrocarbon sol	vent mixtures	
barium sulfate	7727-43-7	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900	
	,				
	Peak-limit category: 2;(II)  Further information: When there is compliance with the OEL and biological				
		ies, there is no risk o	of harming the unborn child		
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900	
	Peak-limit category: 2;(II)				
	Further inform	nation: When there is	s compliance with the OEL and the office of the compliance with the office of the complex comp	and biological	
	tolerance valu	BM (Alveolar	0,5 mg/m3	DE TRGS	
		dust fraction)	0,5 mg/ms	527	
Talc	14807-96-6	AGW (Inhalable	10 mg/m3	DE TRGS	
(Mg3H2(SiO3)4)	14007 30 0	fraction)	10 1119/1113	900	
(Mg0112(0100)+)	Peak-limit cat		<u> </u>	300	
	Peak-limit category: 2;(II)  Further information: When there is compliance with the OEL and biological				
	tolerance valu	ies there is no risk (	of harming the unborn child	ina biologicai	
	tolerance vale	AGW (Alveolate	1,25 mg/m3	DE TRGS	
		fraction)		900	
	Peak-limit category: 2;(II)				
	Further information: When there is compliance with the OEL and biological				
	tolerance valu		of harming the unborn child	T	
		BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527	
2-methoxy-1- methylethyl ace- tate	108-65-6	STEL	100 ppm 550 mg/m3	2000/39/EC	
	Further inform skin, Indicativ		possibility of significant upta	ke through the	

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 5.0 04.07.2023 6021072 Date of first issue: 04.09.2020

		TWA	50 ppm 275 mg/m3	2000/39/EC		
		Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		AGW	50 ppm 270 mg/m3	DE TRGS 900		
	Peak-limit of	Peak-limit category: 1;(I)				
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
butan-1-ol	71-36-3	AGW	100 ppm 310 mg/m3	DE TRGS 900		
	Peak-limit of	Peak-limit category: 1;(I)				
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				

# **Biological occupational exposure limits**

Substance name	CAS-No.	Control parameters	Sampling time	Basis
butan-1-ol	71-36-3	1-butanol: 2 mg/g	Before next shift	TRGS 903
		Creatinine		
		(Urine)		
		1-butanol: 10 mg/g	Immediately after	TRGS 903
		Creatinine	exposure or after	
		(Urine)	working hours	

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health effects	Value
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
barium sulfate	Consumers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	13000,00 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
zinc oxide	Consumers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,50 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

VersionRevision Date:SDS Number:Date of last issue: 11.01.20235.004.07.20236021072Date of first issue: 04.09.2020

	Workers	Skin contact	Long-term systemic	83,00 mg/kg
			effects	bw/day
	Workers	Inhalation	Long-term local ef- fects	0,50 mg/m3
	Workers	Inhalation	Long-term systemic effects	5,00 mg/m3
2-methoxy-1- methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275,00 mg/m3
	Workers	Inhalation	Acute local effects	550,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	796,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33,00 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	33,00 mg/m3
	Consumers	Skin contact	Long-term systemic effects	320,00 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	36,00 mg/kg bw/day
butan-1-ol	Consumers	Inhalation	Long-term local ef- fects	55,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	3,13 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	310,00 mg/m3
trizinc bis(orthophosphate)	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,50 mg/m3
	Workers	Inhalation	Long-term systemic effects	5,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
Reaction mass of Bis(1,2,2,6,6- pentamethyl-4- piperidyl) sebacate and Methyl 1,2,2,6,6- pentamethyl-4- piperidyl sebacate	Consumers	Inhalation	Acute local effects	0,58 mg/m3
	Consumers	Ingestion	Long-term systemic effects	1,25 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,58 mg/m3
	Consumers	Inhalation	Acute systemic effects	0,58 mg/m3
	Consumers	Skin contact	Long-term systemic	1,25 mg/kg

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 5.0 04.07.2023 6021072 Date of first issue: 04.09.2020

			effects	bw/day
	Consumers	Skin contact	Acute systemic ef- fects	1,25 mg/kg bw/day
	Consumers	Ingestion	Acute systemic ef- fects	1,25 mg/kg bw/day
	Workers	Inhalation	Acute systemic effects	2,35 mg/m3
	Workers	Inhalation	Acute local effects	2,35 mg/m3
	Workers	Inhalation	Long-term systemic effects	2,35 mg/m3
	Workers	Skin contact	Acute systemic ef- fects	2,50 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	2,50 mg/kg bw/day
2-ethylhexanoic acid, zirconium salt	Consumers	Inhalation	Long-term systemic effects	8,13 mg/m3
	Consumers	Skin contact	Long-term systemic effects	3,25 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4,51 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	6,49 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	32,97 mg/m3
N,N'-ethane-1,2- diylbis(12- hydroxyoctadecan-1- amide)	Consumers	Inhalation	Long-term local effects	0,83 mg/m3
,	Workers	Inhalation	Long-term local ef- fects	3,35 mg/m3
2-methylpentane-2,4- diol	Consumers	Inhalation	Long-term local ef- fects	25,00 mg/m3
	Consumers	Inhalation	Long-term systemic effects	3,50 mg/m3
	Consumers	Ingestion	Long-term systemic effects	1,00 mg/kg bw/day
	Consumers	Inhalation	Acute local effects	49,00 mg/m3
	Consumers	Skin contact	Long-term systemic effects	1,00 mg/kg bw/day
	Workers	Inhalation	Acute local effects	98,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	14,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	49,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	2,00 mg/kg bw/day

# Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
----------------	---------------------------	-------

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

VersionRevision Date:SDS Number:Date of last issue: 11.01.20235.004.07.20236021072Date of first issue: 04.09.2020

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	Sewage treatment plant	100 mg/l
το μπη	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry
	John	weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sea sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l
barium sulfate	Fresh water	115 µg/l
	Fresh water sediment	600,4 mg/kg dry weight (d.w.)
	Soil	207,7 mg/kg dry weight (d.w.)
	Sewage treatment plant	62,2 mg/l
zinc oxide	Fresh water sediment	117,8 mg/kg dry weight (d.w.)
	Sea water	6,1 µg/l
	Fresh water	20,6 μg/l
	Sea sediment	56,5 mg/kg dry
	Sea Sediment	weight (d.w.)
	Sewage treatment plant	100 µg/l
	Soil	35,6 mg/kg dry
		weight (d.w.)
2-methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l
, , , , , , , , , , , , , , , , , , , ,	Intermittent use/release	6,35 mg/l
	Sea sediment	0,329 mg/kg dry
	Fresh water sediment	weight (d.w.) 3,29 mg/kg dry
	Fresh water sediment	weight (d.w.)
	Sewage treatment plant	100 mg/l
	Sea water	0,0635 mg/l
	Soil	0,29 mg/kg dry
	3011	weight (d.w.)
butan-1-ol	Sewage treatment plant	2476 mg/l
	Fresh water	0,082 mg/l
	Intermittent use/release	2,25 mg/l
	Fresh water sediment	0,178 mg/kg dry
		weight (d.w.)
	Sea water	0,0082 mg/l
	Sea sediment	0,0178 mg/kg dry
		weight (d.w.)
	Soil	0,015 mg/kg dry weight (d.w.)
trizinc bis(orthophosphate)	Sea sediment	56,5 mg/kg dry

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

VersionRevision Date:SDS Number:Date of last issue: 11.01.20235.004.07.20236021072Date of first issue: 04.09.2020

		weight (d.w.)
	Fresh water	20,6 µg/l
	Soil	35,6 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 μg/l
	Fresh water sediment	117,8 mg/kg dry
		weight (d.w.)
	Sea water	6,1 µg/l
Reaction mass of Bis(1,2,2,6,6- pentamethyl-4-piperidyl) seba- cate and Methyl 1,2,2,6,6- pentamethyl-4-piperidyl sebacate	Sea water	0,00022 mg/l
	Soil	0,21 mg/kg dry
	Fresh water	weight (d.w.)
	Fresh water	0,0022 mg/l
	Sewage treatment plant	1 mg/l
	Fresh water sediment	1,05 mg/kg dry weight (d.w.)
	Intermittent use/release	0,009 mg/l
	Sea sediment	0,009 mg/kg dry
	Sea sediment	weight (d.w.)
2-ethylhexanoic acid, zirconium	Fresh water	0,36 mg/l
salt	1 10311 Water	0,00 mg/i
Jan	Sea sediment	0,637 mg/kg dry weight (d.w.)
	Intermittent use/release	0,493 mg/l
	Sea water	0,036 mg/l
	Soil	1,06 mg/kg dry
		weight (d.w.)
	Fresh water sediment	6,37 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	71,7 mg/l
N,N'-ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide)	Sewage treatment plant	0,1 mg/l
2-methylpentane-2,4-diol	Soil	0,11 mg/kg dry weight (d.w.)
	Intermittent use/release	4,29 mg/l
	Secondary Poisoning	100 mg/kg food
	Fresh water sediment	1,79 mg/kg dry weight (d.w.)
	Sea water	0,0429 mg/l
	Sewage treatment plant	20 mg/l
	Sea sediment	0,179 mg/kg dry
		weight (d.w.)
	Fresh water	0,429 mg/l

# 8.2 Exposure controls

Personal protective equipment

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 5.0 04.07.2023 6021072 Date of first issue: 04.09.2020

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Tightly fitting safety goggles

Hand protection

Material : Nitrile rubber Glove thickness : 0,2 mm Protective index : Class 3

Remarks : Gloves should be discarded and replaced if there is any indi-

cation of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suita-

ble gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.

During spray application: impervious clothing

Respiratory protection : Roller application or brushing: This product should not be

used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to

standard EN 14387) is used.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : white

Odor : No data available

Odor Threshold : Not relevant

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 5.0 04.07.2023 6021072 Date of first issue: 04.09.2020

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Flash point : 40 °C

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 6,95

Concentration: 10 %

Viscosity

Viscosity, dynamic : 5,000 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Flow time : > 60 s at 23 °C

Cross section: 6 mm Method: ISO 2431

Solubility(ies)

Water solubility : partly miscible

Partition coefficient: n-

octanol/water

not determined

Vapor pressure : not determined

Relative density : not determined

Density : 1,4600 g/cm3

Relative vapor density : Heavier than air.

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : Sustains combustion

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 5.0 04.07.2023 6021072 Date of first issue: 04.09.2020

Evaporation rate : Not applicable

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.

Hazardous decomposition products formed under fire condi-

tions.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

Incompatible with oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

**Components:** 

butan-1-ol:

Acute oral toxicity : LD50 (Rat): 790 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 3.430 mg/kg

### Skin corrosion/irritation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 04.07.2023 6021072 Date of first issue: 04.09.2020 5.0

### Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause drowsiness or dizziness

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity** 

Not classified based on available information.

#### 11.2 Information on other hazards

# **Endocrine disrupting properties**

**Product:** 

Assessment The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

# **SECTION 12: Ecological information**

### 12.1 Toxicity

#### **Components:**

barium sulfate:

Toxicity to fish : Remarks: No toxicity at the limit of solubility.

aquatic invertebrates

Toxicity to daphnia and other : Remarks: No toxicity at the limit of solubility.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 04.07.2023 6021072 Date of first issue: 04.09.2020 5.0

Toxicity to algae/aquatic

plants

Remarks: No toxicity at the limit of solubility.

Toxicity to fish (Chronic tox-

icity)

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

Remarks: No toxicity at the limit of solubility.

#### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### **Components:**

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Partition coefficient: nlog Pow: 1,99 - 18,02 (20 °C)

octanol/water pH: 7

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naph-

tha:

Partition coefficient: nlog Pow: 1,99 - 18,02 (20 °C)

octanol/water pH: 7

2-methoxy-1-methylethyl acetate:

Partition coefficient: n-: log Pow: 1,2 (20 °C)

octanol/water Method: OECD Test Guideline 117

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-

pentamethyl-4-piperidyl sebacate:

log Pow: 2,37 - 2,77 (25 °C) Partition coefficient: n-

octanol/water pH: 7,0

12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:** 

This substance/mixture contains no components considered Assessment

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 5.0 04.07.2023 6021072 Date of first issue: 04.09.2020

### 12.6 Endocrine disrupting properties

### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

#### **Product:**

Additional ecological infor-

mation

: Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product :

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080112, waste paint and varnish other than those mentioned

in 08 01 11\*

### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

### 14.2 UN proper shipping name

ADN : PAINT RELATED MATERIAL
ADR : PAINT RELATED MATERIAL
RID : PAINT RELATED MATERIAL

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 5.0 04.07.2023 6021072 Date of first issue: 04.09.2020

**IMDG** : PAINT RELATED MATERIAL

(zinc oxide, trizinc bis(orthophosphate))

IATA : Paint related material

14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

### 14.4 Packing group

**ADN** 

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

**ADR** 

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

**RID** 

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

**IMDG** 

Packing group : III
Labels : 3
EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen: 355

ger aircraft)

Packing instruction (LQ) : Y344

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 04.07.2023 6021072 Date of first issue: 04.09.2020 5.0

Packing group Ш

Flammable Liquids Labels

#### 14.5 Environmental hazards

**ADN** 

Environmentally hazardous yes

**ADR** 

Environmentally hazardous yes

Environmentally hazardous yes

**IMDG** 

Marine pollutant yes

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener-

ated.

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

None

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 5.0 04.07.2023 6021072 Date of first issue: 04.09.2020

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

P5c FLAMMABLE LIQUIDS

Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a)

to (d)

Water hazard class (Germa-

ny)

: WGK 2 obviously hazardous to water

34

Classification according to AwSV, Annex 1 (5.2)

: BSL60 Coating materials, solvent-based, carcinogenic ingre-

dients, classified

Volatile organic compounds : Directive 2004/42/EC

< 25 % < 360 g/l

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

#### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

### **SECTION 16: Other information**

### **Full text of H-Statements**

H226 : Flammable liquid and vapor.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version 5.0	Revision Date: 04.07.2023		OS Number: 121072	Date of last issue: 11.01.2023 Date of first issue: 04.09.2020
H302 H304 H315 H317 H318 H319 H335 H336 H351 H360D H361d H361f H372 H400 H410 H411			Causes skin irrita May cause an alle Causes serious e Causes serious e May cause respir. May cause drows Suspected of cau May damage the Suspected of dan Causes damage e exposure. Very toxic to aqua Toxic to aquatic li	allowed and enters airways. tion. ergic skin reaction. ye damage. ye irritation. atory irritation. iness or dizziness. sing cancer if inhaled. unborn child. naging the unborn child. naging fertility. to organs through prolonged or repeated
EUH06	56	:	Repeated exposu	re may cause skin dryness or cracking.

### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Carc. : Carcinogenicity
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation

Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values Germany. TRGS 527 - Activities with nanomaterials

DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 903 : TRGS 903 - Biological limit values

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit

DE TRGS 527 / BM : Assessment scale
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELX - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 %

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 5.0 04.07.2023 6021072 Date of first issue: 04.09.2020

of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemicals Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

### Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

### Classification of the mixture: Classification procedure:

H226	Based on product data or assessment
H319	Calculation method
H317	Calculation method
H336	Calculation method
H373	Calculation method
H411	Calculation method
	H319 H317 H336 H373

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

according to Regulation (EC) No. 1907/2006



DE / EN

# **DisboCOR 864 Sonderton**

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 5.0 04.07.2023 6021072 Date of first issue: 04.09.2020

### **REACH Information**

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN